



Carboline Road Line Marking Paint

INTRODUCTION

A Solvent borne durable line marking paint for internal - external applications on car parks, factory floors, yard areas and walkways.

Available in 3 stock shades, Black, White, Yellow and Ral Classic, BS 4800 or BS 381c range and Developed for industrial applications

Available finish: Semi-Gloss

Substrates: Tarmac, Concrete and Manholes.

Drying time

Touch dry: 15 Minutes @ 20°C

Hard dry: 45 Minutes @ 20°C

Overcoat: between 1 & 2 hours or after 10 hours of application.

Drying times will be extended at low temperatures. Do not apply when ambient temperature falls below 5°C or relative humidity exceeds 90%.

TYPICAL PROPERTIES

Appearance:	Liquid
Solids Content % \pm 10:	50%
Viscosity RVT 3/20:	400 – 600 cps
Ph:	7.0 – 9.0
Density (25°C, g/cm ³) \pm 0.2 :	1.25
Storage stability:	Store in temperature range 5-40°C

Carboline Road Line Marking Paint

APPLICATION PROPERTIES

Dry Film Thickness: 20 - 30 μ

Wet Film Thickness: 40 - 60 μ

Theoretical Coverage Rate:

14m² per litre @ 25 μ DFT coverage rate can be affected by such variables as type and condition of substrate, type of application equipment and individual method of application.

Recommended Application Methods:

Conventional Spray. Airless Spray. Hot Spray. Electrostatic Spray (see spraying guidelines as adjustment may be required).

Brush or Solvent Resistant Roller.

Thinning: Use Palatine Multi-Purpose Thinners

PRODUCT HANDLING – STORAGE – SHELF LIFE

To ensure safe storage of this dispersion, containers should be well sealed to prevent the water evaporation and skin forming. The dispersion must be stored between 5-25°C for a maximum of 12 months.

HEALTH & SAFETY

For full details see separate Health & Safety Data Sheet.

The information given on this sheet is, to the best of our knowledge, true and accurate. No guarantee of the results implied, or any loss or damage arising out of this material, however, are possible as the conditions of application are beyond our control. This is notwithstanding any liability arising from the Consumer Protection Act 1987 and the Health & Safety at Work Act. Health and Safety data is available on this product and should be referred to prior to its use.

PALATINE PAINTS & CHEMICALS LTD
55 SMALLBROOK LANE
LEIGH
LANCASHIRE
WN7 5PZ
TEL: 01942 884122
FAX: 01942 887085

sales@palatinepaints.co.uk

www.palatinepaints.co.uk