

SECTION 1: Identification of t	SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1. Product identifier			
Product name	Indasa Abrasives UK Limited - Acrylic Matt Black 500ml Aerosols		
Product number	481868		
1.2. Relevant identified uses	1.2. Relevant identified uses of the substance or mixture and uses advised against		
Identified uses	Paint.		
1.3. Details of the supplier of	the safety data sheet		
Supplier	Indasa Abrasives UK Limited Viking Works Greenstead Road Colchester Essex CO1 2ST Tel: +44 1206 870366 Fax: +44 1206 860525 office@indasa.co.uk		
1.4. Emergency telephone number			
Emergency telephone	+44 (0) 1206 870 366 (Hours 09:00 - 17:00 Mon to Fri)		
SECTION 2: Hazards identification			
2.1. Classification of the subs	tance or mixture		
Classification (EC 1272/2008)	<u>)</u>		
Physical hazards	Aerosol 1 - H222, H229		
Health hazards	Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H336		
Environmental hazards	Aquatic Chronic 3 - H412		
Human health	Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards.		
Environmental	The product contains a substance which is harmful to aquatic organisms.		
Physicochemical	Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is extremely flammable. Vapours may form explosive mixtures with air.		
2.2. Label elements			
Hazard pictograms			

Signal word

Hazard statements	 H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	 P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTRE/doctor if you feel unwell. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	ACETONE, HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N- HEXANE, HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE, 1-METHOXY-2- PROPANOL, BUTANONE
Supplementary precautionary statements	 P264 Wash contaminated skin thoroughly after handling. P273 Avoid release to the environment. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE</td> 30-60% CAS number: 68476-85-7 EC number: 270-704-2 Classification Flam. Gas 1 - H220 Press. Gas (Comp.) - H280 Press.

ACETONE		10-3	.309
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01- 2119471330-49-XXXX	
Classification			
Flam. Liq. 2 - H225			
Eye Irrit. 2 - H319			
STOT SE 3 - H336			
HYDROCARBONS, C6-C7, N-AI CYCLICS, <5% N-HEXANE	LKANES, ISOALKANES,	5-1	-10%
CAS number: 92128-66-0	EC number: 921-024-6	REACH registration number: 01- 2119475514-35-XXXX	
Classification			
Flam. Liq. 2 - H225			
Skin Irrit. 2 - H315			
STOT SE 3 - H336			
Asp. Tox. 1 - H304			
Aquatic Chronic 2 - H411			
XYLENE		5-1	·10%
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01- 2119488216-32-XXXX	
Classification			
Flam. Liq. 3 - H226			
Acute Tox. 4 - H312			
Acute Tox. 4 - H332			
Skin Irrit. 2 - H315			
Eye Irrit. 2 - H319			
STOT SE 3 - H335			
STOT RE 2 - H373			
Asp. Tox. 1 - H304			
Aquatic Chronic 3 - H412			
·			
2-METHOXY-1-METHYLETHYL	ACETATE	5-1	-10%
CAS number: 108-65-6	EC number: 203-603-9	REACH registration number: 01- 2119475791-29-XXXX	
Classification			
Flam. Liq. 3 - H226			

HYDROCARBONS, C6 ISOALKAN	IES <5% N-HEXANE		1-5%
CAS number: 64742-49-0	EC number: 931-254-9	REACH registration number: 01- 2119484651-34-XXXX	
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			
1-METHOXY-2-PROPANOL			1-5%
CAS number: 107-98-2	EC number: 203-539-1	REACH registration number: 01- 2119457435-35-XXXX	1-070
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336			
BUTANONE			1-5%
CAS number: 78-93-3	EC number: 201-159-0	REACH registration number: 01- 2119457290-43-XXXX	
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336			
ETHYLBENZENE			<1%
CAS number: 100-41-4	EC number: 202-849-4	REACH registration number: 01- 2119489370-35-XXXX	
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H332 STOT RE 2 - H373 Asp. Tox. 1 - H304			
N-BUTYL ACETATE			<1%
CAS number: 123-86-4	EC number: 204-658-1	REACH registration number: 01- 2119485493-29-XXXX	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336			

2-methoxypropyl acetate		<1%
CAS number: 70657-70-4	EC number: 274-724-2	
Classification		
Flam. Liq. 3 - H226		
Repr. 1B - H360D		
STOT SE 3 - H335		
The full text for all hazard statements is displayed in Section 16.		

SECTION 4: First aid measures

4.1. Description of first aid measures		
General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.	
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.	
Ingestion	Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.	
Skin contact	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.	
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.	
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.	
4.2. Most important symptoms	and effects, both acute and delayed	
General information	See Section 11 for additional information on health hazards.	
4.3. Indication of any immedia	te medical attention and special treatment needed	
Notes for the doctor	Treat symptomatically.	
SECTION 5: Firefighting measurements	sures	
5.1. Extinguishing media		
Suitable extinguishing media	Foam, carbon dioxide or dry powder.	
5.2. Special hazards arising fr	om the substance or mixture	
Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.	
5.3. Advice for firefighters		
Protective actions during firefighting	Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.	
SECTION 6: Accidental release measures		
6.1. Personal precautions, pro	tective equipment and emergency procedures	
Personal precautions	Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.	

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe ha	Indling
Usage precautions	Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.
Advice on general occupational hygiene	Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke when using this product.
7.2. Conditions for safe stor	rage, including any incompatibilities
Storage precautions	Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.
7.3. Specific end use(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³ Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³ Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³ Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³ Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³ Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³ Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³ Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³ Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³ Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³ Sk, Sk

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 274 mg/m³ Short-term exposure limit (15-minute): WEL 100 ppm 548 mg/m³ Sk

1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m³ Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m³ Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m³ Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m³ Sk, Sk

BUTANONE

Long-term exposure limit (8-hour TWA): WEL 200 ppm 600 mg/m³ Long-term exposure limit (8-hour TWA): WEL 200 ppm 600 mg/m³ Short-term exposure limit (15-minute): WEL 300 ppm 899 mg/m³ Short-term exposure limit (15-minute): WEL 300 ppm 899 mg/m³ Sk, Sk

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m³ Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m³ Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m³ Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m³ Sk, Sk

N-BUTYL ACETATE

Short-term exposure limit (15-minute): WEL 966 mg/m3 200 ppm Long-term exposure limit (8-hour TWA): WEL 724 mg/m3 150 ppm WEL = Workplace Exposure Limit Sk = Can be absorbed through the skin.

ACETONE (CAS: 67-64-1)

DNEL	Workers - Dermal; Long term systemic effects: 186 mg/kg/day Workers - Inhalation; Short term local effects: 2420 mg/m³ Workers - Inhalation; Long term systemic effects: 1210 mg/m³
PNEC	- Sediment (Freshwater); 30.4 mg/kg - Sediment (Marinewater); 3.04 mg/kg - marine water; 1.06 mg/l - Soil; 29.5 mg/kg
HYDROCARBONS, C6	-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE (CAS: 92128-66-0)
DNEL	Consumer - Oral; Long term systemic effects: 699 mg/kg/day Workers - Oral; Long term systemic effects: 773 mg/kg/day Workers - Dermal; Long term systemic effects: 773 mg/kg/day Consumer - Dermal; Long term systemic effects: 699 mg/kg/day Consumer - Inhalation; Long term systemic effects: 608 mg/m ³ 2-METHOXY-1-METHYLETHYL ACETATE (CAS: 108-65-6)
DNEL	Consumer - Oral; Long term systemic effects: 1.67 mg/kg/day Consumer - Dermal; Long term systemic effects: 54.8 mg/kg/day Workers - Dermal; Long term systemic effects: 153.5 mg/kg/day Consumer - Inhalation; Long term systemic effects: 33 mg/m ³ Workers - Inhalation; Long term systemic effects: 275 mg/m ³
PNEC	- Fresh water; 0.635 mg/l - Sediment (Freshwater); 3.29 mg/kg - Sediment (Marinewater); 0.329 mg/kg - Soil; 0.29 mg/kg

XYLENE (CAS: 1330-20-7)

DNEL	Consumer - Dermal; Long term systemic effects: 108 mg/kg/day Workers - Dermal; Long term systemic effects: 180 mg/kg/day Consumer - Inhalation; Short term local effects: 174 mg/m ³ Consumer - Inhalation; Short term systemic effects: 174 mg/m ³ Workers - Inhalation; Short term systemic effects: 289 mg/m ³ Workers - Inhalation; Short term local effects: 289 mg/m ³ Consumer - Inhalation; Long term systemic effects: 14.8 mg/m ³ Workers - Inhalation; Long term systemic effects: 77 mg/m ³
PNEC	 Fresh water; 0.327 mg/l marine water; 0.327 mg/l Intermittent release; 0.327 mg/l STP; 6.58 mg/l Sediment (Freshwater); 12.46 mg/kg Sediment (Marinewater); 12.46 mg/kg Soil; 2.31 mg/kg
	HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE (CAS: 64742-49-0)
DNEL	Consumer - Oral; Long term systemic effects: 1301 mg/kg/day Consumer - Dermal; Long term systemic effects: 1377 mg/kg/day Workers - Dermal; Long term systemic effects: 13964 mg/kg/day Consumer - Inhalation; Long term systemic effects: 1131 mg/m ³ Workers - Inhalation; Long term systemic effects: 5306 mg/m ³
	1-METHOXY-2-PROPANOL (CAS: 107-98-2)
DNEL	Consumer - Oral; Long term systemic effects: 3.3 mg/kg/day Consumer - Dermal; Long term systemic effects: 18.1 mg/kg/day Consumer - Dermal; Long term systemic effects: 50.6 mg/kg/day Workers - Inhalation; Short term local effects: 553.5 mg/m ³ Consumer - Inhalation; Long term systemic effects: 43.9 mg/m ³ Workers - Inhalation; Long term systemic effects: 369 mg/m ³
PNEC	 Fresh water; 10 mg/l Sediment (Freshwater); 41.6 mg/kg Intermittent release; 100 mg/l Sediment (Marinewater); 4.17 mg/kg marine water; 1 mg/l Soil; 2.47 mg/kg
	BUTANONE (CAS: 78-93-3)
DNEL	Consumer - Dermal; Long term systemic effects: 412 mg/kg/day Consumer - Oral; Long term systemic effects: 31 mg/kg/day Workers - Dermal; Long term systemic effects: 1161 mg/kg/day Consumer - Inhalation; Long term systemic effects: 106 mg/m ³ Workers - Inhalation; Long term systemic effects: 600 mg/m ³

PNEC	 Fresh water; 55.8 mg/l Sediment (Freshwater); 284.7 mg/kg Intermittent release; 55.8 mg/l Sediment (Marinewater); 284.7 mg/kg marine water; 55.8 mg/l STP; 709 mg/l Soil; 22.5 mg/kg
	N-BUTYL ACETATE (CAS: 123-86-4)
DNEL	Consumer - Inhalation; Short term local effects: 859.7 mg/m ³ Consumer - Inhalation; Short term systemic effects: 859.7 mg/m ³ Workers - Inhalation; Short term systemic effects: 960 mg/m ³ Workers - Inhalation; Short term local effects: 960 mg/m ³ Consumer - Inhalation; Long term local effects: 102.34 mg/m ³ Workers - Inhalation; Long term local effects: 480 mg/m ³ Consumer - Inhalation; Long term systemic effects: 102.34 mg/m ³
PNEC	- Fresh water; 0.18 mg/l - Sediment (Freshwater); 0.981 mg/kg - Sediment (Marinewater); 0.981 mg/kg - marine water; 0.018 mg/l - STP; 35.6 mg/l - Soil; 0.0903 mg/kg
8.2. Exposure controls	
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
Hand protection	No specific requirements are anticipated under normal conditions of use.
Other skin and body protection	Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.
Respiratory protection	No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Black.
Odour	Solvent.
Odour threshold	No information available.
рН	No information available.
Melting point	No information available.
Initial boiling point and range	-41 (-41 TO 143)°C @
Flash point	-40°C Closed cup.
Evaporation rate	No information available.
Evaporation factor	No information available.

Flammability (solid, gas)	No information available.	
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.8 % Upper flammable/explosive limit: 13.1 %	
Vapour pressure	No information available.	
Vapour density	No information available.	
Relative density	0.716	
Solubility(ies)	Insoluble in water.	
Partition coefficient	No information available.	
Auto-ignition temperature	270°C	
Decomposition Temperature	No information available.	
Viscosity	No information available.	
Explosive properties	No information available.	
Oxidising properties	No information available.	
9.2. Other information		
Other information	None.	
SECTION 10: Stability and rea	activity	
10.1. Reactivity		
Reactivity	No test data specifically related to reactivity available for this product or its ingredients.	
10.2. Chemical stability		
Stability	The product may not be stable under some conditions of storage or use.	
10.3. Possibility of hazardous	reactions	
Possibility of hazardous reactions	None known.	
10.4. Conditions to avoid		
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.	
10.5. Incompatible materials		
Materials to avoid	None known.	
10.6. Hazardous decomposition products		
Hazardous decomposition products	None at ambient temperatures.	
SECTION 11: Toxicological information		
11.1. Information on toxicolog	ical effects	
<u>Acute toxicity - dermal</u> ATE dermal (mg/kg)	20,276.5	
	20,210.0	
Acute toxicity - inhalation ATE inhalation (vapours mg/l)	202.76	

Inhalation	May cause drowsiness or dizziness. Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.
Skin contact	Causes skin irritation. Repeated exposure may cause skin dryness or cracking.
Eye contact	Causes serious eye irritation.
Acute and chronic health hazards	No known chronic or acute health risks.
Route of exposure	Inhalation Skin and/or eye contact

Toxicological information on ingredients.

ACETONE

Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	5,800.0
Species	Rat
ATE oral (mg/kg)	5,800.0
Acute toxicity - dermal	
Acute toxicity dermal (LD∞ mg/kg)	7,800.0
Species	Rabbit
ATE dermal (mg/kg)	7,800.0
Acute toxicity - inhalation	
Acute toxicity inhalation (LC₅ vapours mg/l)	21.0
Species	Rat
ATE inhalation (vapours mg/l)	21.0
HYDROCARB	ONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE
Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	5,001.0
Species	Rat
ATE oral (mg/kg)	5,001.0
Acute toxicity - dermal	
Acute toxicity dermal (LD₅ mg/kg)	2,001.0
Species	Rabbit
ATE dermal (mg/kg)	2,001.0
	XYLENE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg)	4,300.0
Species	Rat
ATE oral (mg/kg)	4,300.0
Acute toxicity - dermal	
Acute toxicity dermal (LD₅₀ mg/kg)	3,200.0
Species	Rabbit
ATE dermal (mg/kg)	1,100.0
Acute toxicity - inhalation	
ATE inhalation (vapours mg/l)	11.0

2-METHOXY-1-METHYLETHYL ACETATE

Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	8,532.0
Species	Rat
ATE oral (mg/kg)	8,532.0
Acute toxicity - dermal	
Acute toxicity dermal (LD₅₀ mg/kg)	5,001.0
Species	Rat
ATE dermal (mg/kg)	5,001.0
Acute toxicity - inhalation	
Acute toxicity inhalation (LC50 vapours mg/l)	23.8
Species	Rat
ATE inhalation (vapours mg/l)	23.8
	HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE
Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	5,001.0
Species	Rat
ATE oral (mg/kg)	5,001.0
Acute toxicity - dermal	
Acute toxicity dermal (LD₅ mg/kg)	2,001.0

Species	Rabbit	
ATE dermal (mg/kg)	2,001.0	
Acute toxicity - inhalation		
Acute toxicity inhalation (LC50 vapours mg/l)	21.0	
Species	Rat	
ATE inhalation (vapours mg/l)	21.0	
		1-METHOXY-2-PROPANOL
Acute toxicity - oral		
Acute toxicity oral (LD₅₀ mg/kg)	5,660.0	
Species	Rat	
ATE oral (mg/kg)	5,660.0	
Acute toxicity - dermal		
Acute toxicity dermal (LD _∞ mg/kg)	13,000.0	
Species	Rabbit	
ATE dermal (mg/kg)	13,000.0	
Acute toxicity - inhalation		
Acute toxicity inhalation (LC50 vapours mg/l)	54.6	
Species	Rat	
ATE inhalation (vapours mg/l)	54.6	
		BUTANONE
Acute toxicity - oral		
Acute toxicity oral (LD₅₀ mg/kg)	2,194.0	
Species	Rat	
ATE oral (mg/kg)	2,194.0	
Acute toxicity - dermal		
Acute toxicity dermal (LD₅₀ mg/kg)	5,001.0	
Species	Rabbit	
ATE dermal (mg/kg)	5,001.0	

ETHYLBENZENE

Acute toxicity - inhalation

ATE inhalation (vapours 11.0 mg/l)

N-BUTYL ACETATE

Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	10,760.0
Species	Rat
ATE oral (mg/kg)	10,760.0
Acute toxicity - dermal	
Acute toxicity dermal (LD₅₀ mg/kg)	14,113.0
Species	Rabbit
ATE dermal (mg/kg)	14,113.0
Acute toxicity - inhalation	
Acute toxicity inhalation (LC₅ vapours mg/l)	23.4
Species	Rat
ATE inhalation (vapours mg/l)	23.4

SECTION 12: Ecological information

12.1. Toxicity

Ecological information on ingredients.

ACETONE

Acute aquatic toxicity			
Acute toxicity - fish	EC₅₀, 96 hours: 8300 mg/l, Lepomis macrochirus (Bluegill)		
Acute toxicity - aquatic invertebrates	EC₅₀, : 8800 mg/l, Daphnia magna		

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

Acute aquatic toxicity		
Acute toxicity - fish	LOEC, : 1-10 mg/l, Fish	
Acute toxicity - aquatic plants	LOEC, : 10-100 mg/l, Algae	
Acute toxicity - microorganisms	LOEC, : 1-10 mg/l, Activated sludge	
	XYLENE	
Acute aquatic toxicity		
Acute toxicity - fish	LOEC, : >1 - <10 mg/l, Fish	

Acute toxicity - plants	aquatic	LOEC, : >1 - <10 mg/l, Algae
		2-METHOXY-1-METHYLETHYL ACETATE
Acute aquatic t	toxicity	
Acute toxicity -	fish	LOEC, : >100 mg/l, Fish
Acute toxicity - plants	aquatic	LOEC, : >100 mg/l, Algae
Acute toxicity - microorganism		LOEC, : >100 mg/l, Activated sludge
		HYDROCARBONS, C6 ISOALKANES <5% N-HEXANE
Acute aquatic	toxicity	
Acute toxicity -	fish	LOEC, : 10-100 mg/l, Fish
Acute toxicity - plants	aquatic	LOEC, : 10-100 mg/l, Algae
		1-METHOXY-2-PROPANOL
Acute aquatic	toxicity	
Acute toxicity -	fish	$LC_{\mathfrak{so}},96$ hours: 20800 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - invertebrates	aquatic	EC₅₀, 48 hours: 23300 mg/l, Daphnia magna
Acute toxicity - plants	aquatic	EC₅₀, : 1001 mg/l, Selenastrum capricornutum
		BUTANONE
Acute aquatic t	toxicity	
Acute toxicity -	fish	LC₅₀, 24 hours: 5001 mg/l, Fish
Acute toxicity - plants	aquatic	LOEC, : 101 mg/l, Algae
		N-BUTYL ACETATE
Acute aquatic t	toxicity	
Acute toxicity -	fish	LC₅₀, 24 hours: 54 mg/l, Fish LC₅₀, 96 hours: 18 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - invertebrates	aquatic	EC₅₀, 48 hours: 44 mg/l, Daphnia magna
Acute toxicity - plants	aquatic	EC₅₀, 72 hours: 647.7 mg/l, Scenedesmus subspicatus
12.2. Persistence and degra	adability	
Persistence and degradabili	ty No data a	available.
12.3. Bioaccumulative poter	ntial	

12.3. Bioaccumulative potential

Partition coefficient

No information available.

12.4. Mobility in soil

Mobility	No data available.			
12.5. Results of PBT and vPv	'B assessment			
Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.			
12.6. Other adverse effects				
Other adverse effects	None known.			
SECTION 13: Disposal consi	derations			
13.1. Waste treatment metho	ds			
General information	Dispose of waste product or used containers in accordance with local regulations Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.			
Disposal methods	Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.			
Waste class	The waste code classification is to be carried out according to the European Waste Catalogue (EWC).			
SECTION 14: Transport infor	mation			

14.1. UN number			
UN No. (ADR/RID)	1950		
UN No. (IMDG)	1950		
UN No. (ICAO)	1950		
UN No. (ADN)	1950		
14.2. UN proper shipping name			
Proper shipping name (ADR/RID)	AEROSOLS, FLAMMABLE		
Proper shipping name (IMDG)	AEROSOLS, FLAMMABLE		
Proper shipping name (ICAO)	AEROSOLS, FLAMMABLE		
Proper shipping name (ADN)	AEROSOLS, FLAMMABLE		
14.3. Transport hazard class(es)			
ADR/RID class	2.1		
ADR/RID classification code	5F		
ADR/RID label	2.1		
IMDG class	2.1		
ICAO class/division	2.1		
ADN class	2.1		

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



EmS

14.6.	Special	precautions	for user
-------	---------	-------------	----------

F-D, S-U

ADR transport category

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

2

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

National regulations	The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
EU legislation	 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended). Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information Revision date 27/03/2019 Revision 2 Supersedes date 09/12/2014 SDS number 5175

Hazard statements in full	 H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H360D May damage the unborn child.
	H360D May damage the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.