



Etch Primer Aerosol

Etch primer is a ready to use material available in an aerosol can. It promotes adhesion of paint and can be used for priming bare metal, aluminium, galvanised and zinc coated steels. It has a tough film that offers excellent filling and adhesive properties.

Part No.	Description	Size
472965	Etch Primer Grey Aerosol	400ml
472958	Etch Primer Beige Aerosol	400ml

ADDITIONAL INFORMATION

APPLICATION

Ensure all surfaces to be applied are clean, dry and rust free. Shake Aerosol can for 2 - 3 minutes.

Apply 1 - 2 light even coats.

Allow 5 minutes flash off time between coats.

Over-paint after 15 - 20 minutes. Drying time is dependent on film thickness. Please note that product does not require flattening prior to over-painting.

excellent adhesion properties

fast drying

multi substrate adhesion

anti corrosion coating

non clog nozzle

Resin	Polyvinylbutyral
Pigments	Lead-free
Solids	12 %(m/m)
Rec film thickness	120 micron wet, 15 - 25 micron dry.
Gloss	±10, Gloss measuring angle 60°
Density	0.812 kg/l
Particle size	10-15 micron
VOC Content	303 gms
Storage	Store dry and cool
Shelf-life	12 months



INDASA

INDASA Abrasives (UK) Ltd
Viking Works, Greenstead Rd,
Colchester, CO1 2ST
Tel: 01206 870366
Fax: 01206 860525
Email: office@indasa.co.uk