



# PALATINE PAINTS

ORIGINAL ISSUE DATE: 10/12/20

REVISION DATE:

## TECHNICAL DATA SHEET QUICK GUIDE

### EPOXYTREAD 1K FLOOR PAINT

Epoxytread Single Pack floor paint looks great while providing a protective and flexible finish to your concrete floors. Good adhesive properties mean this floor paint is easy to apply. It is fast drying, so is a good option if a floor needs painting in a couple of days. Use instead of [Carbotread](#) if you need more chemical resistance. This is because Epoxytread Single Pack Floor paint is formulated to offer protection against oil and chemical splashes. If your floor is subject to heavy traffic or heavy chemical spillages you may want to consider a [Two Pack option](#). Ideal to use on concrete floors in factories and warehouses. It is also a great paint for garage floors, warehouses and shop floors.

#### Pack Sizes with Product Order Codes

5 Litre	P473LG, P473MG, P473AG, P473TR, P473LBG, P473DG, P473SR, P473SY, P473BLU, P473B, P473W, P473RAL, P473BS4800, P473BS381C
20 Litre	P474LG, P474MG, P474AG, P474TR, P474LBG, P474DG, P474SR, P474SY, P474BLU, P474B, P474W, P474RAL, P474BS4800, P474BS381C
205 Litre	Available on Request.

#### How to Apply

Stir the paint with a drill stirrer or wooden baton at least 2" wide. Apply by brush, solvent resistant roller or spray. For porous unpainted mature concrete, firstly apply a coat of [Pliocem Concrete Sealer](#), then two subsequent neat coats of Carbotread Floor Paint to enhance the performance of the coatings life cycle. For a more economical approach on porous surfaces, thin the first coat of Floor Paint 10-15% with White Spirit and one neat coat. On previously painted surfaces, ensure it is sound and non-flaking. Abrade the surface preferably by mechanical abrasion to provide a "key" and maximise adhesion of the Floor Paint. Clean tools and equipment with Palatine White Spirit.

#### Packaging Disposal

Completely emptied packaging should be put in recycling skips or appropriate container. Packaging which are not empty should be disposed of as special refuse. Please consult the relevant waste authority for clarification.



**BCF**  
British Coatings  
Federation

#### Product Highlights

- A high quality epoxy ester, single pack, gloss floor paint.
- Hard wearing coating for light to medium traffic areas.
- Helps identify and mark key production, loading and walk way areas.
- Available in a range of pack sizes and a wide choice of colours.
- Can be applied by roller, brush or spray.
- Can be used on concrete, wood and steel surfaces, both indoors and outside.
- Good resistance to oils, water and greases.
- Upto 13 m<sup>2</sup>/litre, a more economical choice with up to



Palatine Paints & Chemicals Limited  
55 Smallbrook Lane,  
Leigh, Lancashire,  
WN7 5PZ  
Tel: 01942 884122  
[sales@palatinepaints.co.uk](mailto:sales@palatinepaints.co.uk) <http://www.palatinepaints.co.uk>

The information given on this sheet is, to the best of our knowledge, true and accurate. No guarantee of the results implied, or any loss or damage arising out of this material, however, are possible as the conditions of application are beyond our control. This is notwithstanding any liability arising from the Consumer Protection Act 1987 and the Health & Safety at Work Act. Health and Safety data is available on this product and should be referred to prior to its use



# PALATINE PAINTS


ORIGINAL ISSUE DATE: 10/12/2020

REVISION DATE:


## TECHNICAL DATA SHEET QUICK GUIDE

### EPOXYTREAD 1K FLOOR PAINT


#### Colours Available




LIGHT GREY




MID GREY




AD GREY




TILE RED




LIGHT BRUNSWICK  
GREEN




DARK GREEN




SAFETY RED




SAFETY YELLOW




MID BLUE




BLACK




WHITE



RAL CLASSIC



BS 4800



BS 381 C



Palatine Paints & Chemicals Limited

55 Smallbrook Lane,

Leigh, Lancashire,

WN7 5PZ

Tel: 01942 884122

[sales@palatinepaints.co.uk](mailto:sales@palatinepaints.co.uk) <http://www.palatinepaints.co.uk>

The information given on this sheet is, to the best of our knowledge, true and accurate. No guarantee of the results implied, or any loss or damage arising out of this material, however, are possible as the conditions of application are beyond our control. This is not withstanding any liability arising from the Consumer Protection Act 1987 and the Health & Safety at Work Act. Health and Safety data is available on this product and should be referred to prior to its use