

THERMOSTRIP PRO WATER BASED PAINT REMOVER

Page: 1

Compilation date: 09/01/2017

Sent to: Thermoguard H&S Dept

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: THERMOSTRIP PRO WATER BASED PAINT REMOVER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: specialist paint and surface coating stripper/remover

1.3. Details of the supplier of the safety data sheet

Company name:	Thermoguard Ltd
	Kirkby Street
	Hull
	Yorkshire
	HU2 0HE
	United Kingdom
Tel:	01142 768 008
Fax:	01624 825526
Email:	technical@thermoguard.co.uk

1.4. Emergency telephone number

Emergency tel: 01624 825 115

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Acute Tox. 4: H302; Eye Irrit. 2: H319

Most important adverse effects: Harmful if swallowed. Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: H302: Harmful if swallowed. H319: Causes serious eye irritation.

Hazard pictograms: GHS07: Exclamation mark



Signal words:	Warning
Precautionary statements:	P264: Wash hands thoroughly after handling.
	P270: Do not eat, drink or smoke when using this product.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.

THERMOSTRIP PRO WATER BASED PAINT REMOVER

Page: 2

P301+P312: IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P330: Rinse mouth.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BENZYL ALCOHOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
202-859-9	100-51-6	-	Acute Tox. 4: H332; Acute Tox. 4: H302	30-50%

C9-11 ALCOHOL ETHOXOLATE

-	68439-46-3	-	Acute Tox. 4: H302+H312+H332; Eye	1-10%
			Dam. 1: H318	

Contains: BENZYL ALCOHOL

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

- **Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Transfer to hospital as soon as possible.
- Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: In all cases of doubt, or when symptoms persist seek medical attention.

THERMOSTRIP PRO WATER BASED PAINT REMOVER

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

THERMOSTRIP PRO WATER BASED PAINT REMOVER

	Page: 4	
DNEL/PNEC Values		
DNEL / PNEC	No data available.	
8.2. Exposure controls		
Engineering measures:	Ensure there is sufficient ventilation of the area. Avoid inhalation of vapours	
	Respiratory protection not required.	
	Protective gloves.	
Eye protection:	Safety glasses. Ensure eye bath is to hand.	
Skin protection:	Protective clothing.	
Environmental	Handle in accordance with good industrial hygiene and safety practices	
Section 9: Physical and che	mical properties	
9.1. Information on basic ph	ysical and chemical properties	
State	Liquid	
Colour:	White	
Odour:	Characteristic odour	
Evaporation rate:	Slow	
Solubility in water:	Slightly soluble	
Also soluble in:	Most organic solvents.	
Viscosity:	Non-viscous	
Relative density:	1.01 VOC g/l: 449	
9.2. Other information		
Other information: Not in Scope of VOC Product regulations 2004/42/CE		
Section 10: Stability and rea	ctivity	
10.1. Reactivity		
Reactivity	Stable under recommended transport or storage conditions.	
10.2. Chemical stability		
Chemical stability:	Stable under normal conditions.	
10.3. Possibility of hazardou	s reactions	
Hazardous reactions:	Hazardous reactions will not occur under normal transport or storage conditions.	
	Decomposition may occur on exposure to conditions or materials listed below.	
10.4. Conditions to avoid		
Conditions to avoid:	Heat.	
10.5. Incompatible materials		
	Strong oxidising agents. Strong acids.	

THERMOSTRIP PRO WATER BASED PAINT REMOVER

Page: 5

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
ORAL	RAT	LD50	1230	mg/kg
VAPOURS	RAT	LD50	53	mg/kg
ORAL	MUS	LD50	1360	mg/kg

Hazardous ingredients:

BENZYL ALCOHOL

IVN	RAT	LD50	53	mg/kg
ORL	MUS	LD50	1360	mg/kg
ORL	RAT	LD50	1230	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	ING	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact:There may be mild irritation at the site of contact.Eye contact:There may be irritation and redness.Ingestion:There may be soreness and redness of the mouth and throat. There may be difficulty
swallowing. Nausea and stomach pain may occur. There may be vomiting.Inhalation:Absorption through the lungs can occur causing symptoms similar to those of ingestion.Delayed / immediate effects:Immediate effects can be expected after short-term exposure.Other information:In all cases of doubt or where symptons persist obtain medical attention

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

THERMOSTRIP PRO WATER BASED PAINT REMOVER

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal
	company.
Waste code number:	08 01 17
Disposal of packaging:	Drained and rigorously scraped out empty containers are controlled wastes and should
	be disposed of according with the regulations made under the Control of Pollution Act
	and Enviromental Protection Act
NB:	The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information	
Other information:	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation
	(EU) 2015/830
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H302: Harmful if swallowed.
	H302+H312+H332: Harmful if swallowed, in contact with skin or if inhaled
	H318: Causes serious eye damage.
	H319: Causes serious eye irritation.
	H332: Harmful if inhaled.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive

THERMOSTRIP PRO WATER BASED PAINT REMOVER

and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

Page: 7

Thermoguard H&S Dept