

# **CARBOMAC TARMAC RESTORER**

# **DESCRIPTION**

TARMAC RESTORER is a blend of bitumens formulated to restore worn tarmac and asphalt surfaces. It can be used on paths, drives, car parks, etc., to repair small cracks and holes and restore appearance.

### **BENEFITS**

- · Ready to use
- Easy to apply
- Quick drying

#### **PREPARATION**

Remove moss, lichen etc. by scraping and prewashing with a powerwasher. Thoroughly **clean** so that they are free from loose material. Ensure there are no residues or contaminants on the surface. **Surface must be fully dry** before application, to avoid moisture getting trapped and lifting product.

#### **APPLICATION**

**Stir well before use**. Apply a single thick, even coat using a brush or roller. Repair small holes and cracks by first applying a coat of Tarmac Restorer and then immediately applying a coat of Tarmac Restorer mixed with sand, to form a thick paste.

**Drying time:** Approximately 5 hours. Rain will delay curing. Protect from rain for 30 minutes after application.

Coverage: 1-2 m2 per litre per coat.

# **CLEANING**

Clean tools immediately after use with white spirit

# **PACKAGING**

Packed in 5 litre cans, available in Black or Red. Other sizes available on request

# **HEALTH & SAFETY**

As with all Paints and Coatings, as long as reasonable standards of safe working are maintained there should be no major hazards in the handling of this product. However, care should be taken to avoid contact with skin and eyes. For further information please refer to the Safety Data Sheet.

# STORAGE LIFE

Shelf life is at least 12 months when stored as directed in undamaged and unopened containers.

We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.