

Supercedes Date: 14/06/2016

SAFETY DATA SHEET Marine Anti-Corrosive Primer White_Grey

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Marine Anti-Corrosive Primer White_Grey

Product number BB131 - BB132 - BB133 - (W) for White (G) for Grey

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

Revision Date: 02/02/2023

1.3. Details of the supplier of the safety data sheet

Supplier Palatine Paints & Chemicals Limited

55 Smallbrook Lane, Leigh,

Lancashire, WN7 5PZ

UK

+44 (0)1942 884122 (T) sales@palatinepaints.co.uk

Contact person Technical Department - 08.00 - 17.00 hrs Mon - Thurs, 08.00 - 13.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1942 884 122 08.00 - 17.00 hrs Mon - Thurs, 08.00 - 13.00 hrs Fri)

SDS No. 20278

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards STOT SE 3 - H336

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Pictogram







Signal word Warning

Hazard statements H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Page 1 of 12 Revision Number: 2

Revision Date: 02/02/2023

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

Supercedes Date: 14/06/2016

smoking.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label information

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains HYDROCARBONS, C9-C11, <2% AROMATICS

Supplementary precautionary

statements

P260 Do not breathe vapour/ spray.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P391 Collect spillage.

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCARRONS CO.C11 <2% AROMATICS	30_60%

CAS number: — EC number: 919-857-5 REACH registration number: 01-

2119463258-33-XXXX

Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 3 - H226 Xn;R65. R10,R66,R67.

STOT SE 3 - H336 Asp. Tox. 1 - H304

Calcium Carbonate 10-30%

CAS number: 1317-65-3 EC number: 215-279-6

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified -

TRIZINC BIS(ORTHOPHOSPHATE) 5-10%

CAS number: 7779-90-0 EC number: 231-944-3 REACH registration number: 01-

2119485044-40-0000

M factor (Acute) = 1 M factor (Chronic) = 1

Classification Classification (67/548/EEC or 1999/45/EC)

Aquatic Acute 1 - H400 N;R50/53

Aquatic Chronic 1 - H410

Page 2 of 12 Revision Number: 2

Titanium Dioxide 10-30%

CAS number: 13463-67-7 EC number: 236-675-5 REACH registration number: 01-

2119489379-17-xxxx

Supercedes Date: 14/06/2016

Classification Classification (67/548/EEC or 1999/45/EC)

Carc. 2 - H351 -

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The product contains organic solvents.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Never give anything by mouth to an unconscious person.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and

ensure breathing can take place.

Ingestion DO NOT induce vomiting. Get medical attention immediately. Move affected person to fresh

air and keep warm and at rest in a position comfortable for breathing.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing

immediately and wash skin with soap and water.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information Get medical attention promptly if symptoms occur after washing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an

extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Toxic gases or vapours. FLAMMABLE. Solvent vapours may form explosive mixtures with air.

5.3. Advice for firefighters

Protective actions during

firefighting

Risk of re-ignition after fire has been extinguished. Cool containers exposed to flames with water until well after the fire is out. Avoid the spillage or runoff entering drains, sewers or

watercourses.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. No

smoking, sparks, flames or other sources of ignition near spillage. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

protection is worn during removal or spinages in commed areas

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Contain spillage with sand,

earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate

regulatory body.

Page 3 of 12 Revision Number: 2

Revision Date: 02/02/2023

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

Supercedes Date: 14/06/2016

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists. Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not eat, drink or smoke when using the product. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Keep container tightly closed. Keep containers upright. Store away from the following materials: Oxidising materials. Alkalis. Acids.

Storage class

Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

Usage description

Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Calcium Carbonate

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

TRIZINC BIS(ORTHOPHOSPHATE)

Long-term exposure limit (8-hour TWA): 10 mg/m³

Page 4 of 12 Revision Number: 2

HYDROCARBONS, C9-C11, <2% AROMATICS

DNEL Consumer - Oral; Long term systemic effects: 300 mg/kg/day

Industry - Inhalation; Long term systemic effects: 1500 mg/m³ Industry - Dermal; Long term systemic effects: 300 mg/kg/day Consumer - Dermal; Long term systemic effects: 300 mg/kg/day Consumer - Inhalation; Long term systemic effects: 900 mg/m³

PNEC No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this

endpoint are intended for single substances and are not appropriate for the risk

Supercedes Date: 14/06/2016

assessment of this complex substance.

TRIZINC BIS(ORTHOPHOSPHATE) (CAS: 7779-90-0)

DNEL Consumer - Inhalation; Long term systemic effects: 2.5 mg/m³

- Inhalation; : 5.0 insoluble Zn mg/m³

Professional - Inhalation; Long term systemic effects: 5 mg/m³

- Inhalation; : 1.0 soluble Zn mg/m3

Professional - Dermal; Long term systemic effects: 83 mg/kg/day Consumer - Dermal; Long term systemic effects: 83 mg/kg/day Consumer - Oral; Long term systemic effects: 0.83 mg/kg/day

PNEC - Fresh water; 0.02 Zn mg/l

- marine water; 0.006 Zn mg/l

Sediment (Freshwater); 117.8 mg/kgSediment (Marinewater); 56.5 Zn mg/kg

- Soil; 35.6 Zn mg/kg

- STP; 0.1 Zn mg/l

8.2. Exposure controls

Protective equipment





Revision Date: 02/02/2023

Appropriate engineering controls

Wear chemical splash goggles.

limits for the product or ingredients.

Eye/face protection

Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Wear protective gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.31 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

Provide adequate general and local exhaust ventilation. Observe any occupational exposure

Other skin and body protection

Wear appropriate clothing to prevent reasonably probable skin contact.

Hygiene measures

No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. In case of inadequate ventilation use suitable respirator. It is recommended to use respiratory equipment with combination filter, type A2/P2.

Page 5 of 12

Revision Number: 2

Supercedes Date: 14/06/2016

SECTION 9: Physical and chemical properties

Revision Date: 02/02/2023

9.1. Information on basic physical and chemical properties

Appearance Viscous liquid. Coloured liquid.

Colour White, Grey.

Odour Organic solvents.

Odour threshold Not determined.

pH Technically not feasible.

Melting point Not determined.

Initial boiling point and range Not determined.

Flash point 38 approx.°C Closed cup.

Evaporation rate Not determined.

Evaporation factor Not determined.

Upper/lower flammability or

explosive limits

Not determined.

Other flammability

Vapour pressure

Not determined.

Vapour density

heavier than air

Relative density 1.30 approx. @ @ 20°C

Solubility(ies) Insoluble in water

Partition coefficient Not determined.

Auto-ignition temperature Not determined.

Decomposition Temperature Not determined.

Viscosity 6 (Rotothinner) P @ 25°C

Explosive properties Not determined.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties Not determined.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

Not determined.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Acids. Oxidising agents.

10.5. Incompatible materials

Materials to avoid Strong alkalis. Strong acids. Strong oxidising agents.

Page 6 of 12 Revision Number: 2

Marine Anti-Corrosive Primer White_Grey

10.6. Hazardous decomposition products

Revision Date: 02/02/2023

Hazardous decomposition

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and

Supercedes Date: 14/06/2016

products

other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation Vapour from this product may be hazardous by inhalation. Vapour may irritate respiratory

system/lungs.

Ingestion Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

Skin contact Product has a defatting effect on skin. Repeated exposure may cause skin dryness or

cracking. May cause allergic contact eczema. Prolonged or repeated exposure may cause

severe irritation.

Eye contact May cause temporary eye irritation.

Acute and chronic health

hazards

This product has low toxicity. Only large quantities are likely to have adverse effects on

human health.

Route of exposure Inhalation Skin absorption. Ingestion. Skin and/or eye contact.

5,100.0

Medical considerations Skin disorders and allergies. Avoid vomiting and stomach flushing because of the risk of

aspiration.

Toxicological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

Species Rat

ATE oral (mg/kg) 5,100.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 5,100.0

mg/kg)

Species Rabbit

ATE dermal (mg/kg) 5,100.0

Acute toxicity - inhalation

Acute toxicity inhalation 5,100.0

(LC50 vapours mg/l)

Species Rat

ATE inhalation (vapours 5,100.0

mg/l)

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Serious eye Not irritating.

damage/irritation

Respiratory sensitisation

Page 7 of 12 Revision Number: 2

Revision Date: 02/02/2023 Marine Anti-Corrosive Primer White_Grey Supercedes Date: 14/06/2016

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative. This substance has no evidence of mutagenic

properties.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity -

fertility

Fertility: - , Inhalation, Rat This substance has no evidence of toxicity to

reproduction.

Reproductive toxicity -

Developmental toxicity: -:, Inhalation, Rat This substance has no evidence of

development toxicity to reproduction.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not available.

Aspiration hazard

Aspiration hazard Kinematic viscosity <= 20.5 mm2/s.

Inhalation Vapours may cause drowsiness and dizziness. Central nervous system depression.

Ingestion Harmful: danger of serious damage to health by prolonged exposure if swallowed.

Skin contact Product has a defatting effect on skin. May cause allergic contact eczema.

Eye contact No specific health hazards known.

Route of exposure Inhalation Dermal

SECTION 12: Ecological information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause

long term adverse effects in the aquatic environment.

12.1. Toxicity

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Acute aquatic toxicity

Acute toxicity - fish LC50, > 96 hours: 1000 mg/l, Oncorhynchus mykiss (Rainbow trout)

Substance did not cause acute toxicity to fish

Acute toxicity - aquatic

invertebrates

Substance did not cause acute toxicity to the freshwater invertebrates

EC₅o, 48 hours: >1000 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅o, > 72 hours: 1000 mg/l, Freshwater algae

Substance did not cause acute toxicity to the freshwater green algae

Acute toxicity - microorganisms

EC₅₀, >: 100 mg/l, Activated sludge

Chronic aquatic toxicity

Page 8 of 12 Revision Number: 2

Carboxide Anti-Corrosive Metal Primer White_Grey
Marine Anti-Corrosive Primer White_Grey

Revision Date: 02/02/2023 Marine Anti-Corrosive Primer White_Grey Supercedes Date: 14/06/2016

Chronic toxicity - fish early NOEC, 28 days: 0.131 mg/l, Oncorhynchus mykiss (Rainbow trout)

life stage

Chronic toxicity - aquatic NOEC, 28 days: 0.23 mg/l, Daphnia magna

invertebrates

12.2. Persistence and degradability

Persistence and degradability The product is not expected to be biodegradable.

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Persistence and The product is readily biodegradable.

degradability

Phototransformation Oxidises rapidly by photo-chemical reactions in air

Biodegradation - 80 Degradation (%): 28 days

Test - 301F Ready Biodegradability - Manometric Respiratory Test

12.3. Bioaccumulative potential

Bioaccumulative potential The product contains potentially bioaccumulating substances.

Partition coefficient Not determined.

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Bioaccumulative potential The product contains potentially bioaccumulating substances.

Partition coefficient log Pow: 5 - 6.7

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all

surfaces.

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Mobility The product contains volatile organic compounds (VOCs) which will evaporate

easily from all surfaces. Readily absorbed into soil.

Adsorption/desorption

coefficient

Not available.

Surface tension 24.5 mN/m @ 20°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Results of PBT and vPvB This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

12.6. Other adverse effects

Other adverse effects The product contains volatile organic compounds (VOCs) which have a photochemical ozone

creation potential.

Page 9 of 12 Revision Number: 2

Ecological information on ingredients.

Revision Date: 02/02/2023

HYDROCARBONS, C9-C11, <2% AROMATICS

Supercedes Date: 14/06/2016

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Avoid the spillage or runoff entering drains, sewers or watercourses.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

Waste class When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as

hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02

(plastic packaging) or 15 01 04 (metal packaging).

SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR

and IMDG.

14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

PAINT, Contains Zinc Phosphate, Class 9, Packing Group III, MARINE POLLUTANT, and

Low Aromatic White Spirit, Class 3, Packing Group III (38 °C)

Proper shipping name (IMDG) PAINT
Proper shipping name (ICAO) PAINT

Proper shipping name (ADN) PAINT

14.3. Transport hazard class(es)

ADR/RID class 1263

IMDG class 3

ICAO class/division 3

Transport labels



14.4. Packing group

ICAO packing group

ADR/RID packing group III

IMDG packing group III

Ш

Page 10 of 12 Revision Number: 2

Tunnel restriction code

Revision Date: 02/02/2023

(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 **EU** legislation

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Supercedes Date: 14/06/2016

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Guidance Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet ADR: European Agreement concerning the International Carriage of Dangerous Goods by

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

IATA: International Air Transport Association.

ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate.

LC₅₀: Lethal Concentration to 50 % of a test population.

LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).

EC₅₀: 50% of maximal Effective Concentration.

PBT: Persistent, Bioaccumulative and Toxic substance.

vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations

Acute Tox. = Acute toxicity

and acronyms

Aguatic Acute = Hazardous to the aguatic environment (acute) Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Asp. Tox. = Aspiration hazard Flam. Liq. = Flammable liquid

STOT RE = Specific target organ toxicity-repeated exposure STOT SE = Specific target organ toxicity-single exposure

Training advice Read and follow manufacturer's recommendations.

> Page 11 of 12 Revision Number: 2

Revision Date: 02/02/2023

Revision comments

Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU)

No. 2015/830 Revision to sections 2, 8, 11 & 12 for reclassification of solvents.

Supercedes Date: 14/06/2016

Issued by Technical Dept. (P.E.)

Revision date 02/02/2023

Revision 2

Supersedes date 14/06/2016

SDS number 20278
SDS status Approved.

Hazard statements in full H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

Signature Initials: JH

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Page 12 of 12 Revision Number: 2