

# SAFETY DATA SHEET Marine Anti-Corrosive Primer Red

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of	the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	Marine Anti-Corrosive Primer Red
Product number	BB131R - BB132R - BB133R
1.2. Relevant identified uses	of the substance or mixture and uses advised against
Identified uses	Paint.
1.3. Details of the supplier of	the safety data sheet
Supplier	Palatine Paints & Chemicals Limited 55 Smallbrook Lane, Leigh, Lancashire, WN7 5PZ UK +44 (0)1942 884122 (T) sales@palatinepaints.co.uk
Contact person	Technical Department - 08.00 - 17.00 hrs Mon - Thurs, 08.00 - 13.00 hrs Fri, as above
1.4. Emergency telephone nu	
Emergency telephone	+44 (0) 1942 884 122 08.00 - 17.00 hrs Mon - Thurs, 08.00 - 13.00 hrs Fri) 20279
SDS No.	
SECTION 2: Hazards identified	
2.1. Classification of the subs Classification (EC 1272/2008	
Physical hazards	2 Flam. Liq. 3 - H226
Health hazards	STOT SE 3 - H336
Environmental hazards	Aquatic Chronic 2 - H411
2.2. Label elements Pictogram Signal word Hazard statements	Warning H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements	<ul> <li>P101 If medical advice is needed, have product container or label at hand.</li> <li>P102 Keep out of reach of children.</li> <li>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P271 Use only outdoors or in a well-ventilated area.</li> <li>P273 Avoid release to the environment.</li> <li>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</li> <li>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.</li> <li>Rinse skin with water or shower.</li> <li>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P403+P235 Store in a well-ventilated place. Keep cool.</li> <li>P501 Dispose of contents/ container in accordance with national regulations.</li> </ul>
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	HYDROCARBONS, C9-C11, <2% AROMATICS
Supplementary precautionary statements	<ul><li>P260 Do not breathe vapour/ spray.</li><li>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</li><li>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</li><li>P391 Collect spillage.</li></ul>

# 2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

# SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCARBONS, C9-C11, <2% AROMATICS 30-60%		
CAS number: —	EC number: 919-857-5	REACH registration number: 01- 2119463258-33-XXXX
Classification	Classificati	on (67/548/EEC or 1999/45/EC)
Flam. Liq. 3 - H226	Xn;R65. R <sup>2</sup>	10,R66,R67.
STOT SE 3 - H336		
Asp. Tox. 1 - H304		
Calcium Carbonate		10-30%
CAS number: 1317-65-3	EC number: 215-279-6	
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -	
TRIZINC BIS(ORTHOPHOSPHATE)		5-15%
CAS number: 7779-90-0	EC number: 231-944-3	REACH registration number: 01- 2119485044-40-0000
M factor (Acute) = 1	M factor (Chronic) = 1	
Classification	Classificati	on (67/548/EEC or 1999/45/EC)
<b>Classification</b> Aquatic Acute 1 - H400	<b>Classificati</b> N;R50/53	on (67/548/EEC or 1999/45/EC)

Red Iron Oxide	5-25%
CAS number: 1309-37-1	
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC)
The Full Text for all R-Phrases	s and Hazard Statements are Displayed in Section 16.
Composition comments	The product contains organic solvents.
SECTION 4: First aid measure	3S
4.1. Description of first aid me	asures
General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	DO NOT induce vomiting. Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.
4.2. Most important symptoms	and effects, both acute and delayed
General information	Get medical attention promptly if symptoms occur after washing.
4.3. Indication of any immedia	te medical attention and special treatment needed
Notes for the doctor	No specific recommendations.
SECTION 5: Firefighting meas	ures
5.1. Extinguishing media	
Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising fro	om the substance or mixture
Specific hazards	Toxic gases or vapours. FLAMMABLE. Solvent vapours may form explosive mixtures with air.
5.3. Advice for firefighters	
Protective actions during firefighting	Risk of re-ignition after fire has been extinguished. Cool containers exposed to flames with water until well after the fire is out. Avoid the spillage or runoff entering drains, sewers or watercourses.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
SECTION 6: Accidental releas	e measures
6.1. Personal precautions, pro	tective equipment and emergency procedures
Personal precautions	Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.
6.2. Environmental precaution	<u>s</u>
Environmental precautions	Do not discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

regulatory body.

#### 6.3. Methods and material for containment and cleaning up

### Methods for cleaning up

Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

#### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8.

#### SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Usage precautions Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists. Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not eat, drink or smoke when using the product. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Keep container tightly closed. Keep containers upright. Store away from the following materials: Oxidising materials. Alkalis. Acids.
Storage class	Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate , marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.
7.3. Specific end use(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
Usage description	Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

### SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

### Occupational exposure limits

### Calcium Carbonate

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

#### **TRIZINC BIS(ORTHOPHOSPHATE)**

Long-term exposure limit (8-hour TWA): 10 mg/m<sup>3</sup>

## HYDROCARBONS, C9-C11, <2% AROMATICS

DNEL	Consumer - Oral; Long term systemic effects: 300 mg/kg/day Industry - Inhalation; Long term systemic effects: 1500 mg/m <sup>3</sup> Industry - Dermal; Long term systemic effects: 300 mg/kg/day Consumer - Dermal; Long term systemic effects: 300 mg/kg/day Consumer - Inhalation; Long term systemic effects: 900 mg/m <sup>3</sup>
PNEC	No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.
	TRIZINC BIS(ORTHOPHOSPHATE) (CAS: 7779-90-0)
DNEL	Consumer - Inhalation; Long term systemic effects: 2.5 mg/m <sup>3</sup> - Inhalation; : 5.0 insoluble Zn mg/m <sup>3</sup> Professional - Inhalation; Long term systemic effects: 5 mg/m <sup>3</sup> - Inhalation; : 1.0 soluble Zn mg/m <sup>3</sup> Professional - Dermal; Long term systemic effects: 83 mg/kg/day Consumer - Dermal; Long term systemic effects: 83 mg/kg/day Consumer - Oral; Long term systemic effects: 0.83 mg/kg/day - Fresh water; 0.02 Zn mg/l
	- marine water; 0.006 Zn mg/l - Sediment (Freshwater); 117.8 mg/kg - Sediment (Marinewater); 56.5 Zn mg/kg - Soil; 35.6 Zn mg/kg - STP; 0.1 Zn mg/l
8.2. Exposure controls	
Protective equipment	
Appropriate engineering	Provide adequate general and local exhaust ventilation. Observe any occupational exposure

Eye/face protection

Hand protection

controls

protection

Wear chemical splash goggles.

limits for the product or ingredients.

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Wear protective gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.31 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

Other skin and body Wear appropriate clothing to prevent reasonably probable skin contact.

Hygiene measures No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. In case of inadequate ventilation use suitable respirator. It is recommended to use respiratory equipment with combination filter, type A2/P2.

# SECTION 9: Physical and chemical properties

CECTION 0: 1 Hysical and one		
9.1. Information on basic physical and chemical properties		
Appearance	Viscous liquid. Coloured liquid.	
Colour	Red.	
Odour	Organic solvents.	
Odour threshold	Not determined.	
рН	Technically not feasible.	
Melting point	Not determined.	
Initial boiling point and range	Not determined.	
Flash point	38 approx.°C Closed cup.	
Evaporation rate	Not determined.	
Evaporation factor	Not determined.	
Upper/lower flammability or explosive limits	Not determined.	
Other flammability	Not determined.	
Vapour pressure	Not determined.	
Vapour density	heavier than air	
Relative density	1.30 approx. @ @ 20°C	
Solubility(ies)	Insoluble in water	
Partition coefficient	Not determined.	
Auto-ignition temperature	Not determined.	
Decomposition Temperature	Not determined.	
Viscosity	6 (Rotothinner) P @ 25°C	
Explosive properties	Not determined.	
Explosive under the influence of a flame	Not considered to be explosive.	
Oxidising properties	Not determined.	
9.2. Other information		
SECTION 10: Stability and rea	ctivity	
10.1. Reactivity		
Reactivity	There are no known reactivity hazards associated with this product.	
10.2. Chemical stability		
Stability	Stable at normal ambient temperatures and when used as recomme	nded.
10.3. Possibility of hazardous reactions		
Possibility of hazardous reactions	Not determined.	
10.4. Conditions to avoid		
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with t Acids. Oxidising agents.	he following materials:
10.5. Incompatible materials		

## 10.6. Hazardous decomposition products

Hazardous decomposition	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and
products	other toxic gases or vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Inhalation	Vapour from this product may be hazardous by inhalation. Vapour may irritate respiratory system/lungs.
Ingestion	Liquid irritates mucous membranes and may cause abdominal pain if swallowed.
Skin contact	Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause allergic contact eczema. Prolonged or repeated exposure may cause severe irritation.
Eye contact	May cause temporary eye irritation.
Acute and chronic health hazards	This product has low toxicity. Only large quantities are likely to have adverse effects on human health.
Route of exposure	Inhalation Skin absorption. Ingestion. Skin and/or eye contact.
Medical considerations	Skin disorders and allergies. Avoid vomiting and stomach flushing because of the risk of aspiration.

## Toxicological information on ingredients.

# HYDROCARBONS, C9-C11, <2% AROMATICS

Acute toxicity - oral	
 Acute toxicity oral (LD₅₀ mg/kg)	5,100.0
Species	Rat
ATE oral (mg/kg)	5,100.0
Acute toxicity - dermal	
Acute toxicity dermal (LD₅₀ mg/kg)	5,100.0
Species	Rabbit
ATE dermal (mg/kg)	5,100.0
Acute toxicity - inhalation	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	5,100.0
Species	Rat
ATE inhalation (vapours mg/l)	5,100.0
Skin corrosion/irritation	
Skin corrosion/irritation	Not irritating.
Serious eye damage/irritation	on
Serious eye damage/irritation	Not irritating.
Respiratory sensitisation	

Respiratory sensitisation	Not sensitising.
Skin sensitisation	
Skin sensitisation	Not sensitising.
Germ cell mutagenicity	
Genotoxicity - in vitro	Chromosome aberration: Negative. This substance has no evidence of mutagenic properties.
Carcinogenicity	
Carcinogenicity	Based on available data the classification criteria are not met.
Reproductive toxicity	
Reproductive toxicity - fertility	Fertility: - , Inhalation, Rat This substance has no evidence of toxicity to reproduction.
Reproductive toxicity - development	Developmental toxicity: - : , Inhalation, Rat This substance has no evidence of toxicity to reproduction.
Specific target organ toxicit	y - repeated exposure
STOT - repeated exposure	Not available.
Aspiration hazard	
Aspiration hazard	Kinematic viscosity <= 20.5 mm2/s.
Inhalation	Vapours may cause drowsiness and dizziness. Central nervous system depression.
Ingestion	Harmful: danger of serious damage to health by prolonged exposure if swallowed.
Skin contact	Product has a defatting effect on skin. May cause allergic contact eczema.
Eye contact	No specific health hazards known.
Route of exposure	Inhalation Dermal
SECTION 12: Ecological information	

Ecotoxicity

The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

## 12.1. Toxicity

Ecological information on ingredients.

# HYDROCARBONS, C9-C11, <2% AROMATICS

Acute aquatic toxicity	
Acute toxicity - fish	LC50, > 96 hours: 1000 mg/l, Oncorhynchus mykiss (Rainbow trout) Substance did not cause acute toxicity to fish
Acute toxicity - aquatic invertebrates	Substance did not cause acute toxicity to the freshwater invertebrates $EC_{50}$ , 48 hours: >1000 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC₅₀, > 72 hours: 1000 mg/l, Freshwater algae Substance did not cause acute toxicity to the freshwater green algae
Acute toxicity - microorganisms	EC₅₀, >: 100 mg/l, Activated sludge
Chronic aquatic toxicity	

Chronic toxicity - fish early NOEC, 28 days: 0.131 mg/l, Oncorhynchus mykiss (Rainbow trout) life stage

Chronic toxicity - aquatic NOEC, 28 days: 0.23 mg/l, Daphnia magna invertebrates

### 12.2. Persistence and degradability

**Persistence and degradability** The product is not expected to be biodegradable.

### Ecological information on ingredients.

### HYDROCARBONS, C9-C11, <2% AROMATICS

Persistence and degradability	The product is readily biodegradable.
Phototransformation	Oxidises rapidly by photo-chemical reactions in air
Biodegradation	- 80 Degradation (%): 28 days Test - 301F Ready Biodegradability - Manometric Respiratory Test

### 12.3. Bioaccumulative potential

Bioaccumulative potential	The product contains potentially bioaccumulating substances.
---------------------------	--

Partition coefficient Not determined.

#### Ecological information on ingredients.

#### HYDROCARBONS, C9-C11, <2% AROMATICS

	Bioaccumulative potential	The product contains potentially bioaccumulating substances.
	Partition coefficient	log Pow: 5 - 6.7
12.4. Mobili	ity in soil	
Mobility	The pro- surfaces	duct contains volatile organic compounds (VOCs) which will evaporate easily from all s.
Ecological i	nformation on ingredients.	
		HYDROCARBONS, C9-C11, <2% AROMATICS
	Mobility	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. Readily absorbed into soil.
	Adsorption/desorption coefficient	Not available.
	Surface tension	24.5 mN/m @ 20°C
12.5. Results of PBT and vPvB assessment		
Results of I assessmen	•	duct does not contain any substances classified as PBT or vPvB.
Ecological i	information on ingredients.	

### HYDROCARBONS, C9-C11, <2% AROMATICS

Results of PBT and vPvB	This substance is not classified as PBT or vPvB according to current EU criteria.
assessment	

#### 12.6. Other adverse effects

Other adverse effects

The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

# Ecological information on ingredients.

IMDG packing group

ICAO packing group

Ш

Ш

# HYDROCARBONS, C9-C11, <2% AROMATICS

HYDROCARBONS, C9-C11, <2% AROMATICS	
Other adverse effe	ects Not known.
SECTION 13: Disposal conside	prations
13.1. Waste treatment methods	
General information	Avoid the spillage or runoff entering drains, sewers or watercourses.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).
SECTION 14: Transport inform	ation
General	This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.
14.1. UN number	
UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
14.2. UN proper shipping name	
Proper shipping name (ADR/RID)	PAINT, Contains Zinc Phosphate, Class 9, Packing Group III, MARINE POLLUTANT, and Low Aromatic White Spirit, Class 3, Packing Group III (38 °C)
Proper shipping name (IMDG)	PAINT
Proper shipping name (ICAO)	PAINT
Proper shipping name (ADN)	PAINT
14.3. Transport hazard class(es	5)
ADR/RID class	1263
IMDG class	3
ICAO class/division	3
Transport labels	
14.4. Packing group ADR/RID packing group	111

Tunnel restriction code (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Safety Data Sheets for Substances and Preparations.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### Inventories

### EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

## SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
	ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
	RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
	IATA: International Air Transport Association.
	ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.
	IMDG: International Maritime Dangerous Goods.
	CAS: Chemical Abstracts Service.
	ATE: Acute Toxicity Estimate.
	$LC_{50}$ : Lethal Concentration to 50 % of a test population.
	$LD_{50}$ : Lethal Dose to 50% of a test population (Median Lethal Dose).
	EC <sub>50</sub> : 50% of maximal Effective Concentration.
	PBT: Persistent, Bioaccumulative and Toxic substance.
	vPvB: Very Persistent and Very Bioaccumulative.
Classification abbreviations	Acute Tox. = Acute toxicity
and acronyms	Aquatic Acute = Hazardous to the aquatic environment (acute)
	Aquatic Chronic = Hazardous to the aquatic environment (chronic)
	Asp. Tox. = Aspiration hazard
	Flam. Liq. = Flammable liquid
	STOT RE = Specific target organ toxicity-repeated exposure STOT SE = Specific target organ toxicity-single exposure
Training advice	Read and follow manufacturer's recommendations.

Marine Anti-Corrosive Primer Red

Revision comments	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Revision to sections 2, 8, 11 & 12 for reclassification of solvents.
Issued by	Technical Dept. (P.E.)
Revision date	03/02/2023
Revision	2
Supersedes date	15/06/2016
SDS number	20279
SDS status	Approved.
Hazard statements in full	<ul> <li>H226 Flammable liquid and vapour.</li> <li>H302 Harmful if swallowed.</li> <li>H304 May be fatal if swallowed and enters airways.</li> <li>H315 Causes skin irritation.</li> <li>H317 May cause an allergic skin reaction.</li> <li>H318 Causes serious eye damage.</li> <li>H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.</li> <li>H335 May cause respiratory irritation.</li> <li>H336 May cause drowsiness or dizziness.</li> <li>H400 Very toxic to aquatic life.</li> <li>H410 Very toxic to aquatic life with long lasting effects.</li> <li>H411 Toxic to aquatic life with long lasting effects.</li> </ul>
Signature	Initials: JH

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.