

COO-VAR®

PAINTS, PRIMERS AND SPECIALISED COATINGS

SAFETY DATA SHEET

120/W223 - POWER FLOATED FLOOR PRIMER - HARDENER

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 120/W223 - POWER FLOATED FLOOR PRIMER - HARDENER
Product number 120/W223/HP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses HARDENER FOR TWO COMPONENT PRIMER

1.3. Details of the supplier of the safety data sheet

Supplier COO-VAR
 Lockwood Street
 Hull
 HU2 0HN
 +44 (0) 1482 328053(T)
 +44 (0) 1482 219266(F)
 info@coo-var.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 328053 Coo-Var (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SDS No. 20930

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Eye Dam. 1 - H318
Environmental hazards Not Classified

Classification (67/548/EEC or -
 1999/45/EC)

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H318 Causes serious eye damage.

120/W223 - POWER FLOATED FLOOR PRIMER - HARDENER

Precautionary statements	P102 Keep out of reach of children.
	P101 If medical advice is needed, have product container or label at hand.
	P262 Do not get in eyes, on skin, or on clothing.
	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P310 Immediately call a POISON CENTER/ doctor.
	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
	P501 Dispose of contents/ container in accordance with national regulations.

Contains	FORMALDEHYDE, POLYMERS WITH 1.3-BENZENEDIMETHANAMINE, BISPHENOL A, DIETHYLENETRIAMINE-GLYCIDYL PH ETHER REACTION PRODUCTS, EPICHLOROHYDRIN, PROPYLENE OXIDE AND TRIETHYLENTETRAAMINE, REACTION PRODUCTS WITH GLYCIDYL O-TOLYL ETHER, SULFAMATES (SALTS)
-----------------	---

Supplementary precautionary statements	P403+P235 Store in a well-ventilated place. Keep cool.
---	--

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

FORMALDEHYDE, POLYMERS WITH 1.3-BENZENEDIMETHANAMINE, BISPHENOL A, DIETHYLENETRIAMINE-GLYCIDYL PH ETHER REACTION PRODUCTS, EPICHLOROHYDRIN, PROPYLENE OXIDE AND TRIETHYLENTETRAAMINE, REACTION PRODUCTS WITH GLYCIDYL O-TOLYL ETHER, SULFAMATES (SALTS) CAS number: 238080-05-2	17.41%
Classification Acute Tox. 4 - H302 Eye Dam. 1 - H318	
Barium Sulphate CAS number: 7727-43-7 EC number: 231-784-4 REACH registration number: 01-2119491274-35-0001	10-30%
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -
Calcium Magnesium Silicate CAS number: 14807-96-6 EC number: 238-877-9	10-30%
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -

120/W223 - POWER FLOATED FLOOR PRIMER - HARDENER

Silicon dioxide, chemically prepared	<1%
CAS number: 112945-52-5	EC number: 231-545-4
	REACH registration number: 01-2119379499-16-0000
Classification	
Not Classified	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove affected person from source of contamination. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Give plenty of water to drink. Get medical attention immediately.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.

4.2. Most important symptoms and effects, both acute and delayed

Ingestion	Harmful if swallowed.
Eye contact	Causes serious eye damage. May cause permanent damage if eye is not immediately irrigated.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.
--------------------------------------	--

5.3. Advice for firefighters

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation.
-----------------------------	---

6.2. Environmental precautions

120/W223 - POWER FLOATED FLOOR PRIMER - HARDENER

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb with inert, damp, non-combustible material, then flush area with water. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid inhalation of vapours/spray and contact with skin and eyes. Provide adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Barium Sulphate

Long-term exposure limit (8-hour TWA): 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): 4 mg/m³ respirable dust

Calcium Magnesium Silicate

Long-term exposure limit (8-hour TWA): WEL 1 mg/m³

Silicon dioxide, chemically prepared

Long-term exposure limit (8-hour TWA): WEL 2.4 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): WEL 6 mg/m³ inhalable dust

WEL = Workplace Exposure Limit

Ingredient comments No exposure limits known for ingredient(s).

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Mechanical ventilation or local exhaust ventilation may be required. Ensure operatives are trained to minimise exposure.

Personal protection

Unprotected persons should be kept away from treated areas.

120/W223 - POWER FLOATED FLOOR PRIMER - HARDENER

Eye/face protection	The following protection should be worn: Wear eye protection. Tight-fitting safety glasses. Full face visor or shield. Workers should not contact their eyes or skin with hands contaminated with the material.
Hand protection	To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Nitrile rubber. Thickness: ≥ 0.3 mm Neoprene. Thickness: ≥ 0.4 mm or Butyl rubber. Thickness: ≥ 0.3 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.
Other skin and body protection	Wear suitable protective clothing as protection against splashing or contamination.
Hygiene measures	Wash at the end of each work shift and before eating, smoking and using the toilet.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid. Liquid
Colour	White / off-white.
Odour	Ammonia.
Odour threshold	Not determined.
pH	pH (concentrated solution): 8.9
Initial boiling point and range	>100°C @ 760 mm Hg
Flash point	above 100°C Closed cup.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Data lacking.
Vapour pressure	15 mm Hg @ °C
Vapour density	Not determined.
Relative density	1.30 @ @ 20 C°C
Solubility(ies)	Soluble in water.
Auto-ignition temperature	150°C
Decomposition Temperature	Not determined.
Explosive properties	Not applicable.

120/W223 - POWER FLOATED FLOOR PRIMER - HARDENER

Oxidising properties Data lacking.

9.2. Other information

Other information No information required.

Volatile organic compound This product contains a maximum VOC content of 0 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions The following materials may react violently with the product: Peroxides.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Acids. sodium hypochlorite Peroxides.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 2,872.08

Skin corrosion/irritation

Animal data Data lacking.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye damage.

Respiratory sensitisation

Respiratory sensitisation Data lacking.

Skin sensitisation

Skin sensitisation Data lacking.

Germ cell mutagenicity

Genotoxicity - in vitro Data lacking.

Carcinogenicity

Carcinogenicity Data lacking.

Reproductive toxicity

Reproductive toxicity - fertility Data lacking.

Specific target organ toxicity - single exposure

120/W223 - POWER FLOATED FLOOR PRIMER - HARDENER

STOT - single exposure Data lacking.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Data lacking.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Inhalation Gas or vapour in high concentrations may irritate the respiratory system.

Ingestion Harmful if swallowed.

Skin contact May cause sensitisation or allergic reactions in sensitive individuals. Prolonged skin contact may cause temporary irritation.

Eye contact Causes serious eye damage.

Toxicological information on ingredients.

**FORMALDEHYDE, POLYMERS WITH 1.3-BENZENEDIMETHANAMINE, BISPHENOL A,
DIETHYLENTRIAMINE-GLYCIDYL PH ETHER REACTION PRODUCTS, EPICHLOROHYDRIN, PROPYLENE
OXIDE AND TRIETHYLENTETRAAMINE, REACTION PRODUCTS WITH GLYCIDYL O-TOLYL ETHER,
SULFAMATES (SALTS)**

Acute toxicity - oral

ATE oral (mg/kg) 500.0

Silicon dioxide, chemically prepared

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 5,000.0

Species Rabbit

ATE dermal (mg/kg) 5,000.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ dust/mist mg/l) 139.0

Species Rat

ATE inhalation (dusts/mists mg/l) 139.0

SECTION 12: Ecological information

Ecotoxicity The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish No information available.

Ecological information on ingredients.

Silicon dioxide, chemically prepared

120/W223 - POWER FLOATED FLOOR PRIMER - HARDENER

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: >10000 mg/l, Brachydanio rerio (Zebra Fish)

Acute toxicity - aquatic invertebrates EC₅₀, 24 hours: >1000 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

Silicon dioxide, chemically prepared

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Do not puncture or incinerate even when empty.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging). Wear protective clothing during disposal operations. If disposal is by waste contractor, make sure that he has sufficient information and that waste containers are properly labelled. Ideally this component should be mixed with the appropriate resin base and allowed to react fully producing a solid non hazardous waste.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

120/W223 - POWER FLOATED FLOOR PRIMER - HARDENER

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Commission Regulation (EU) No 2015/830 of 28 May 2015.
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE: Acute Toxicity Estimate.
BCF: Bioconcentration Factor.
CAS: Chemical Abstracts Service.
cATpE: Converted Acute Toxicity Point Estimate.
DNEL: Derived No Effect Level.
EC₅₀: 50% of maximal Effective Concentration.
GHS: Globally Harmonized System.
IMDG: International Maritime Dangerous Goods.
LC₅₀: Lethal Concentration to 50 % of a test population.
LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
PBT: Persistent, Bioaccumulative and Toxic substance.
PNEC: Predicted No Effect Concentration.
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
SVHC: Substances of Very High Concern.
vPvB: Very Persistent and Very Bioaccumulative.

120/W223 - POWER FLOATED FLOOR PRIMER - HARDENER

Classification abbreviations and acronyms	Acute Tox. = Acute toxicity Aquatic Acute = Hazardous to the aquatic environment (acute) Aquatic Chronic = Hazardous to the aquatic environment (chronic) Asp. Tox. = Aspiration hazard Carc. = Carcinogenicity Eye Dam. = Serious eye damage Eye Irrit. = Eye irritation Flam. Liq. = Flammable liquid Repr. = Reproductive toxicity Resp. Sens. = Respiratory sensitisation Skin Corr. = Skin corrosion Skin Irrit. = Skin irritation Skin Sens. = Skin sensitisation STOT RE = Specific target organ toxicity-repeated exposure STOT SE = Specific target organ toxicity-single exposure
Revision comments	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Changes to composition information.
Issued by	Technical Dept. (P.E.)
Revision date	04/03/2020
Revision	1.0
Supersedes date	20/08/2019
SDS number	20930
SDS status	Approved.
Hazard statements in full	H302 Harmful if swallowed. H318 Causes serious eye damage.
Signature	Initials

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.