

## WATER BASED OIL REMOVER

103/Q227/1

### DESCRIPTION:

An efficient cleaner designed to provide rapid release of oil and hydrocarbon contamination from floors, walls and other substrates.

### RECOMMENDED USE:

Coo-Var Water Based Oil Remover is an aqueous cleaner designed for use on floors, walls and other hard surfaces. It rapidly releases heavy oils, hydrocarbons and ground-in dirt from surfaces such as concrete, brick and breezeblock. Use to deep clean floor surfaces prior to the application of coatings, seals and other finishes. Also use to remove slip hazards following leaks and spills.

### AVAILABILITY:

5 litres

### FINISH:

N/A

### COLOUR:

Golden liquid

### TYPICAL S.G. (SPECIFIC GRAVITY):

1.01

### VOLUME SOLIDS:

N/A

### WET FILM THICKNESS W.F.T

### DRY FILM THICKNESS D.F.T

### EXPECTED SPREADING RATE:

1 - 2 sq.m / litre

N/A

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

### TYPICAL VISCOSITY

N/A

### FLASH POINT:

N/A

### DRYING TIME: @ RECOMMENDED D.F.T

Touch dry: N/A

Hard dry: N/A

Full hardness: N/A

Low temperature and high humidity will adversely affect application, drying and performance of any coating.

### MINIMUM OVERCOATING TIME:

N/A

### APPLICATION SPECIAL CONDITIONS:

Oil remover is supplied ready for use. Protect from frost.

### VOC CONTENT:

0 g / litre

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

### APPLICATION DETAILS:

Application restrictions

Method      Apply manually      or use a back pack spray system

Thinner (Max vol):

Nozzle size:

Nozzle pressure:

Cleaning solvent:

For further advice contact Coo-Var Technical Services on +44(0)1482 328053

The physical constants are subject to normal manufacturing tolerances.

**"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"**

Ellenshaw Works

Lockwood Street, Hull HU2 0HN

Tel.: +44(0)1482 328053. Fax: +44(0)1482 219266

COO-VAR

Email: [info@coo-var.co.uk](mailto:info@coo-var.co.uk)

[www.coo-var.co.uk](http://www.coo-var.co.uk)

**WATER BASED OIL REMOVER****103/Q227/1**

---

Recoat N/A  
interval:

**SURFACE PREPARATION:**

Sweep floor to remove debris.

**MIXING INSTRUCTIONS:**

Supplied ready for use

**APPLICATION CONDITIONS:**

Apply liberally to the area to be cleaned. Work well into the surface with a stiff brush and leave for 20 to 60 minutes. Rinse the area well with a pressure washer or hose, collect the rinse water with a wet vac machine. Once the surface oil contamination has been removed, continue with any surface preparation as necessary i.e. mechanical abrasion or chemical etching as required to provide a key for a subsequent coating.

**PRECEDING COAT:**

n/a

**SUBSEQUENT COAT:**

Allow the surface to dry thoroughly. This can take up to several days. Apply a suitable primer for the surface if overcoating.

**REMARKS:**

Oil remover contains no dangerous caustic chemicals, harmful solvents, phosphates or aggressive biocides. It is safer for the user and the environment.

Shelf Life: 12 Months in original container

**HEALTH AND SAFETY:**

See SDS 11099

**ISSUED:**

20 May 2009

**REVISION:**

0

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, since the conditions of use are beyond our control. This data sheet does not constitute a specification. In case of doubt as to the suitability of the product please contact our Technical Service Department.

**For further advice contact Coo-Var Technical Services on +44(0)1482 328053**

**The physical constants are subject to normal manufacturing tolerances.**

**"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"**

---

Ellenshaw Works  
Lockwood Street, Hull HU2 0HN  
Tel.: +44(0)1482 328053. Fax: +44(0)1482 219266

COO-var  
Email: [info@coo-var.co.uk](mailto:info@coo-var.co.uk)  
[www.coo-var.co.uk](http://www.coo-var.co.uk)