



# PALATINE PAINTS

## SAFETY DATA SHEET Palatine Gloss Metal Cladding Paint

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** Palatine Satin Metal Cladding Paint  
**Product code** P534MC  
**Product size** 5L

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Paint.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** Palatine Paints & Chemicals Limited  
 55 Smallbrook Lane, Leigh,  
 Lancashire,  
 WN7 5PZ  
 UK  
 +44 (0)1942 884122 (T)  
 sales@palatinepaints.co.uk

**Contact person** Sales Department - 08.00 - 17.00 hrs Mon - Fri

**1.4. Emergency telephone** +44 (0)1942 884122 (T) - 08.00 - 17.00 hrs Mon - Fri (not 24hr)

**National emergency telephone number** 0344 892 0111

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture Classification (EC 1272/2008)

**Physical hazards** Flam. Liq. 3 - H226  
**Health hazards** STOT SE 3 - H336  
**Environmental hazards** Aquatic Chronic 3 - H412

#### 2.2. Label elements Hazard

pictograms



**Signal word** Warning

<b>Hazard statements</b>	<p>EUH208 Contains NEODECANOATE ACID, COBALT SALT. May produce an allergic reaction.</p> <p>H226 Flammable liquid and vapour.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>
<b>Precautionary statements</b>	<p>P101 If medical advice is needed, have product container or label at hand.</p> <p>P102 Keep out of reach of children.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
<b>Supplemental label information</b>	EUH066 Repeated exposure may cause skin dryness or cracking.
<b>Contains</b>	HYDROCARBONS, C9-C11, <2% AROMATICS, HYDROCARBONS, C9, AROMATICS
<b>Supplementary precautionary statements</b>	<p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p>

**2.3. Other hazards**

This substance is not classified as PBT or vPvB according to current EU criteria.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

<b>HYDROCARBONS, C9-C11, &lt;2% AROMATICS</b>		<b>10-30%</b>
CAS number: —	EC number: 919-857-5	REACH registration number: 01-2119463258-33-XXXX
<b>Classification</b>		
Flam. Liq. 3 - H226		
STOT SE 3 - H336		
Asp. Tox. 1 - H304		
<b>NEODECANOATE ACID, COBALT SALT</b>		<b>&lt;1%</b>
CAS number: 27253-31-2	EC number: 248-373-0	
<b>Classification</b>		<b>Classification (67/548/EEC or 1999/45/EC)</b>
Acute Tox. 4 - H302		Xn;R22. Repr. Cat. 3;R62. N;R51/53. R43.
Acute Tox. 4 - H332		
Skin Sens. 1 - H317		
Repr. 2 - H361f		
Aquatic Chronic 3 - H412		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### Composition comments

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	DO NOT induce vomiting. Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
<b>Skin contact</b>	Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	Get medical attention promptly if symptoms occur after washing.
----------------------------	---

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations.
-----------------------------	------------------------------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.
-------------------------------------	---

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Toxic gases or vapours. FLAMMABLE. Solvent vapours may form explosive mixtures with air.
-------------------------	--

### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	Risk of re-ignition after fire has been extinguished. Cool containers exposed to flames with water until well after the fire is out. Avoid the spillage or runoff entering drains, sewers or watercourses.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.
-----------------------------	--

### 6.2. Environmental precautions

<b>Environmental precautions</b>	Do not discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
----------------------------------	--

### **6.3. Methods and material for containment and cleaning up**

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

### **6.4. Reference to other sections**

**Reference to other sections** For personal protection, see Section 8.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

**Usage precautions** Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists. Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not eat, drink or smoke when using the product. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

### **7.2. Conditions for safe storage, including any incompatibilities**

**Storage precautions** Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Keep container tightly closed. Keep containers upright. Store away from the following materials: Oxidising materials. Alkalis. Acids.

**Storage class** Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

**7.3. Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

**Specific end use(s)** Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

**Usage description**

## **SECTION 8: Exposure controls/Personal protection**

### **8.1. Control parameters**

#### **Occupational exposure limits**

#### **HYDROCARBONS, C9, AROMATICS**

Long-term exposure limit (8-hour TWA): WEL 19 ppm 100 mg/m<sup>3</sup> vapour

#### **NEODECANOATE ACID, COBALT SALT**

Long-term exposure limit (8-hour TWA): WEL 0.1 mg/m<sup>3</sup> Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <

**HYDROCARBONS, C9-C11, <2% AROMATICS**

<b>DNEL</b>	Industry - Inhalation; Long term systemic effects: 1500 mg/m <sup>3</sup> Consumer - Inhalation; Long term systemic effects: 900 mg/m <sup>3</sup> Consumer - Dermal; Long term systemic effects: 300 mg/kg/day Consumer - Oral; Long term systemic effects: 300 mg/kg/day Industry - Dermal; Long term systemic effects: 300 mg/kg/day
<b>PNEC</b>	No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.
<b>Ingredient comments</b>	WEL = Workplace Exposure Limits

**NEODECANOATE ACID, COBALT SALT (CAS: 27253-31-2)**

<b>DNEL</b>	Workers - Inhalation; Long term local effects: 0.2732 mg/m <sup>3</sup> General population - Inhalation; Long term local effects: 0.043 mg/m <sup>3</sup> General population - Oral; Long term systemic effects: 0.0649 mg/kg/day
<b>PNEC</b>	- Fresh water; 0.003 Co mg/ - marine water; 0.00236 Co mg/ - STP; 0.37 Co mg/ - Sediment (Freshwater); 9.5 Co mg/kg/da - Sediment (Marinewater); 9.5 Cp mg/kg/da - Soil; 10.9 Co mg/kg/da

**8.2. Exposure controls**

**Protective equipment**



**Appropriate engineering controls**

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

**Eye/face protection**

Wear chemical splash goggles.

**Hand protection**

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturers' performance data suggest that the optimum glove for use should be: Wear protective gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.31 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

**Other skin and body protection**

Wear appropriate clothing to prevent reasonably probable skin contact.

**Hygiene measures**

No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

**Respiratory protection**

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. In case of inadequate ventilation use suitable respirator. It is recommended to use respiratory equipment with combination filter, type A2/P2.

<b>SECTION 9: Physical and chemical properties</b>
--

**9.1. Information on basic physical and chemical properties**

<b>Appearance</b>	Viscous Liquid
<b>Colour</b>	Colours
<b>Odour</b>	Organic solvents.
<b>Odour threshold</b>	Not determined.
<b>pH</b>	
<b>Melting point</b>	Technically not feasible. Not determined.
<b>Initial boiling point and range</b>	Not determined.
<b>Flash point</b>	38 approx. °C Closed cup.
<b>Evaporation rate</b>	Not determined.
<b>Evaporation factor</b>	Not determined.
<b>Upper/lower flammability or explosive limits</b>	0.8
<b>Other flammability Vapour pressure</b>	Not determined.
<b>Vapour density</b>	Heavier than air
<b>Relative density</b>	0.95 approx. @ 20°C Will vary with colour.
<b>Solubility(ies)</b>	Insoluble in water
<b>Partition coefficient</b>	Not determined.
<b>Auto-ignition temperature</b>	Not determined.
<b>Decomposition Temperature</b>	Not determined.
<b>Viscosity</b>	6 P (Rot thinner) @ 20°C
<b>Explosive properties</b>	Not determined.
<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Not determined.
<b>9.2. Other information</b>	
<b>Volatility</b>	53
<b>Volatile organic compound</b>	This product contains a maximum VOC content of <399 g/litre.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity** There are no known reactivity hazards associated with this product.

**10.2. Chemical stability**

**Stability** Stable at normal ambient temperatures and when used as recommended.

**10.3. Possibility of hazardous reactions**

**Possibility of hazardous reactions** Not determined.

**10.4. Conditions to avoid**

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Acids. Oxidising agents.

**10.5. Incompatible materials**

**Materials to avoid** Strong alkalis. Strong acids. Strong oxidising agents.

**10.6. Hazardous decomposition products**

**Hazardous decomposition products** Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

**Inhalation** Vapour from this product may be hazardous by inhalation. Vapour may irritate respiratory system/lungs.

**Ingestion** Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

**Skin contact** Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause allergic contact eczema. Prolonged or repeated exposure may cause severe irritation.

**Eye contact** May cause temporary eye irritation.

**Acute and chronic health hazards** This product has low toxicity. Only large quantities are likely to have adverse effects on human health.

**Route of exposure** Inhalation Skin absorption. Ingestion. Skin and/or eye contact.

**Medical considerations** Skin disorders and allergies. Avoid vomiting and stomach flushing because of the risk of aspiration.

**Inhalation** Vapour from this product may be hazardous by inhalation. Vapour may irritate respiratory system/lungs.

**Ingestion** Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

**Skin contact** Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause allergic contact eczema. Prolonged or repeated exposure may cause severe irritation.

**Eye contact** May cause temporary eye irritation.

**Acute and chronic health hazards** This product has low toxicity. Only large quantities are likely to have adverse effects on human health.

**Route of exposure** Inhalation Skin absorption. Ingestion. Skin and/or eye contact.

**Medical considerations** Skin disorders and allergies. Avoid vomiting and stomach flushing because of the risk of aspiration.

**Toxicological information on ingredients.****HYDROCARBONS, C9-C11, <2% AROMATICS****Acute toxicity - oral**

Acute toxicity oral (LD<sub>50</sub>  
mg/kg) 5,100.0

Species Rat

ATE oral (mg/kg) 5,100.0

**Acute toxicity - dermal**

Acute toxicity dermal (LD<sub>50</sub>  
mg/kg) 5,100.0

Species Rabbit

ATE dermal (mg/kg) 5,100.0

**Acute toxicity - inhalation**

Acute toxicity inhalation  
(LC<sub>50</sub> vapours mg/l) 5,100.0

Species Rat

ATE inhalation (vapours  
mg/l) 5,100.0

**Skin corrosion/irritation**

Skin corrosion/irritation Not irritating.

**Serious eye damage/irritation**

Serious eye  
damage/irritation Not irritating.

**Respiratory sensitisation**

Respiratory sensitisation Not sensitising.

**Skin sensitisation**

Skin sensitisation Not sensitising.

**Germ cell mutagenicity**

Genotoxicity - in vitro Chromosome aberration: Negative. This substance has no evidence of mutagenic properties.

**Carcinogenicity**

Carcinogenicity Based on available data the classification criteria are not met.

**Reproductive toxicity**

Reproductive toxicity - fertility Fertility: - , Inhalation, Rat This substance has no evidence of toxicity to reproduction.

Reproductive toxicity - development Developmental toxicity: - : , Inhalation, Rat This substance has no evidence of toxicity to reproduction.

**Specific target organ toxicity - repeated exposure**

STOT - repeated exposure Not available.

**Aspiration hazard**



<b>Aspiration hazard</b>	Kinematic viscosity <= 20.5 mm <sup>2</sup> /s.
<b>Inhalation</b>	Vapours may cause drowsiness and dizziness. Central nervous system depression.
<b>Ingestion</b>	Harmful: danger of serious damage to health by prolonged exposure if swallowed.
<b>Skin contact</b>	Product has a defatting effect on skin. May cause allergic contact eczema.
<b>Eye contact</b>	No specific health hazards known.
<b>Route of exposure</b>	Inhalation Dermal

**SECTION 12: Ecological information**

**Ecotoxicity** The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

**12.1. Toxicity**

Ecological information on ingredients.

**HYDROCARBONS, C9-C11, <2% AROMATICS**

**Acute aquatic toxicity**

<b>Acute toxicity - fish</b>	LC50, > 96 hours: 1000 mg/l, Oncorhynchus mykiss (Rainbow trout) Substance did not cause acute toxicity to fish
<b>Acute toxicity - aquatic invertebrates</b>	Substance did not cause acute toxicity to the freshwater invertebrates EC <sub>50</sub> , 48 hours: >1000 mg/l, Daphnia magna
<b>Acute toxicity - aquatic plants</b>	EC <sub>50</sub> , > 72 hours: 1000 mg/l, Freshwater algae Substance did not cause acute toxicity to the freshwater green algae
<b>Acute toxicity - microorganisms</b>	EC <sub>50</sub> , >: 100 mg/l, Activated sludge

**Chronic aquatic toxicity**

<b>Chronic toxicity - fish early life stage</b>	NOEC, 28 days: 0.131 mg/l, Oncorhynchus mykiss (Rainbow trout)
<b>Chronic toxicity - aquatic invertebrates</b>	NOEC, 28 days: 0.23 mg/l, Daphnia magna

**12.2. Persistence and degradability**

**Persistence and degradability** The product is not expected to be biodegradable.

Ecological information on ingredients.

**HYDROCARBONS, C9-C11, <2% AROMATICS**

<b>Persistence and degradability</b>	The product is readily biodegradable.
<b>Phototransformation</b>	Oxidises rapidly by photo-chemical reactions in air
<b>Biodegradation</b>	- 80 Degradation (%): 28 days Test - 301F Ready Biodegradability - Manometric Respiratory Test

**12.3. Bioaccumulative potential**

**HYDROCARBONS, C9-C11, <2% AROMATICS**

**Bioaccumulative potential** The product contains potentially bioaccumulating substances.  
**Partition coefficient** log Pow: 5 - 6.7

**HYDROCARBONS, C9-C11, <2% AROMATICS**

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. Readily absorbed into soil.  
**Adsorption/desorption coefficient** Not available.  
**Surface tension** 24.5 mN/m @ 20°C

**12.5. Results of PBT and vPvB assessment**

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

**Ecological information on ingredients.**

**HYDROCARBONS, C9-C11, <2% AROMATICS**

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

**12.6. Other adverse effects**

**Other adverse effects** The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

**Ecological information on ingredients.**

**HYDROCARBONS, C9-C11, <2% AROMATICS**

**Other adverse effects** Not known.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**General information** Avoid the spillage or runoff entering drains, sewers or watercourses.  
**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.  
**Waste class** When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11\* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11\* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

**SECTION 14: Transport information**

**General** This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

**14.1. UN number**

UN No. (ADR/RID) 1263  
 UN No. (IMDG) 1263  
 UN No. (ICAO) 1263

**14.2. UN proper shipping name**

Proper shipping name (ADR/RID) PAINT, Contains Low Aromatic White Spirit, Class 3, Packing Group III (38 °C)

Proper shipping name (IMDG) PAINT

Proper shipping name (ICAO) PAINT  
 PAINT

Proper shipping name (ADN)

**14.3. Transport hazard class(es)**

ADR/RID class 1263  
 IMDG class 3  
 ICAO class/division 3

**Transport labels**



**14.4. Packing group**

ADR/RID packing group III  
 IMDG packing group III  
 ICAO packing group III

**14.5. Environmental hazards**

Environmentally hazardous substance/marine pollutant

No

**14.6. Special precautions for user**

EmS F-E, S-E  
 Tunnel restriction code (D/E)

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

<b>EU legislation</b>	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
<b>Guidance</b>	Safety Data Sheets for Substances and Preparations.

**15.2. Chemical safety assessment**

No chemical safety assessment has been carried out.

**Inventories****EU - EINECS/ELINCS**

None of the ingredients are listed or exempt.

**SECTION 16: Other information**

<b>Abbreviations and acronyms used in the safety data sheet</b>	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail. IATA: International Air Transport Association. ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air. IMDG: International Maritime Dangerous Goods. CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate. LC <sub>50</sub> : Lethal Concentration to 50 % of a test population. LD <sub>50</sub> : Lethal Dose to 50% of a test population (Median Lethal Dose). EC <sub>50</sub> : 50% of maximal Effective Concentration. PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.
<b>Classification abbreviations and acronyms</b>	Acute Tox. = Acute toxicity Aquatic Acute = Hazardous to the aquatic environment (acute) Aquatic Chronic = Hazardous to the aquatic environment (chronic) Asp. Tox. = Aspiration hazard Flam. Liq. = Flammable liquid STOT RE = Specific target organ toxicity-repeated exposure STOT SE = Specific target organ toxicity-single exposure
<b>Training advice</b>	Read and follow manufacturer's recommendations.
<b>Revision comments</b>	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Addition of EU supplier information
<b>Issued by</b>	Technical Dept. (N.O.)
<b>Revision date</b>	10/03/2020
<b>Revision</b>	1.0
<b>Supersedes date</b>	20/10/2016
<b>SDS number</b>	20318
<b>SDS status</b>	Approved.

**Hazard statements in full**

H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H332 Harmful if inhaled  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H361 Suspected of damaging fertility or the unborn child  
H412 Harmful to aquatic life with long lasting effects.

**Signature: J.H**

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.