

## **ProSolve™ Graffiti Remover**

# Safety Data Sheet

According to Regulation (EU) No 830/2015 and Regulation (EC) No 1272/2008

Date Revised: 19/09/2021 / Version: 2.1

## 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: GRAFFITI REMOVER

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Uses: Graffiti Remover

Usage: designed to safely remove paint

1.3 Details of the supplier of the safety data sheet

Company name: ProSolve

Company Address: Sandall Stones Road, Kirk Sandall Industrial Estate, Doncaster, South Yorkshire,

DN3 1QR

Tel: +44 (0) 1302 310 113

E-mail: enquiries@prosolveproducts.com

Web: www.prosolveproducts.com

**EU Details:** 

Address: Portfolio House, Kilbarrack Parage, Dublin D05 TF86

Phone: 003531 9120925

1.4. Emergency Telephone Number

National Health Service (NHS) NHS England or Scotland: 111 NHS Wales: 0300 0604400

Northern Ireland: Call your local GP

For life-threatening emergencies: Call 999 for an ambulance.

#### 2. Hazards identification

#### 2.1. Classification of the substance or mixture

Classification (EC

1272/2008)

Physical and Chemical Hazards

Human health Environment EUH066;STOT SE 3 - H336

Flam. Aerosol 1 - H222

Not classified.

Classification (1999/45/EEC) F+;R12. R66, R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### 2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



Signal Word Danger

**Hazard Statements** H222 Extremely flammable aerosol.

H336 May cause drowsiness or dizziness.

**Precautionary Statements** P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P271 Use only outdoors or in a well-ventilated area.

P261 Avoid breathing vapour/spray. P280 Wear protective gloves.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337+313 If eye irritation persists: Get medical advice/attention. P501 Dispose of contents/container in accordance with local regulations.

Supplementary

**Precautionary Statements** 

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell. P332+313 If skin irritation occurs: Get medical advice/attention.

P403+233 Store in a well-ventilated place. Keep container tightly closed. P410+412 Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

Supplemental label information

EUH066 Repeated exposure may cause skin dryness or cracking.

#### 2.3. Other hazards

# 3. Composition/information on ingredients

## 3.2. Mixtures

2-METHOXY-1-METHYLETHYL ACETATE	5-10%		
Index No.	REACH Registration No.		
CAS-No.: 108-65-6	EC No.: 203-603-9		
Classification (EC 1272/2008)	Classification (67/548/EEC)		
Flam. Liq. 3 - H226	R10		
ACETONE	10-30%		
Index No.	REACH Registration No.		
CAS-No.: 67-64-1	EC No.: 200-662-2		
Classification (EC 1272/2008)	Classification (67/548/EEC)		
Flam. Liq. 2 - H225 EUH066	F;R11 Xi;R36		
Eye Irrit. 2 - H319	R66		
STOT SE 3 - H336	R67		
BUTANE	5-10%		
Index No.	REACH Registration No.		
CAS-No.: 106-97-8	EC No.: 203-448-7		
Classification (EC 1272/2008)	Classification (67/548/EEC)		
Flam. Gas 1 - H220	F+;R12		
BUTYL ACETATE -norm	10-30%		
Index No.	REACH Registration No.		
CAS-No.: 123-86-4	EC No.: 204-658-1		
Classification (EC 1272/2008)	Classification (67/548/EEC) R10		
Flam. Liq. 3 - H226 EUH066	R10 R66		
STOT SE 3 - H336	R67		
FATTY ALCOHOL ETHOXYLATE	1-5%		
Index No.	REACH Registration No.		
CAS-No.:	EC No.:		
Classification (EC 1272/2008)	Classification (67/548/EEC)		
Not classified.	Xi;R41.		
ISOBUTANE	1-5%		
Index No.	REACH Registration No.		
CAS-No.: 75-28-5	EC No.: 200-857-2		
Classification (EC 1272/2008)	Classification (67/548/EEC)		
Flam. Gas 1 - H220	F+;R12		
METHYLAL	5-10%		
Index No.	REACH Registration No.		
CAS-No.: 109-87-5	EC No.: 203-714-2		
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) F;R11.		
เพนะ ผลออกเซน.	1,1X11.		

PROPANE 10-30%

Index No. REACH Registration No. CAS-No.: 74-98-6 EC No.: 200-827-9

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Gas 1 - H220 F+;R12

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

## 4. First aid measures

## 4.1. Description of first aid measures

**General information** Move the exposed person to fresh air at once. Get medical attention if any discomfort

continues.

**Inhalation** Move the exposed person to fresh air at once. When breathing is difficult, properly

trained personnel may assist affected person by administering oxygen. Keep the

affected person warm and at rest. Get prompt medical attention.

Ingestion DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large

amounts of milk or water to people not unconscious. Get medical attention if any

discomfort continues.

**Skin contact** Wash the skin immediately with soap and water. Get medical attention if any

discomfort continues.

**Eye contact** Make sure to remove any contact lenses from the eyes before rinsing. Promptly

wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least

15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

## 5. Firefighting measures

#### 5.1 Extinguishing Media

**Extinguishing media** Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

#### 5.2. Special hazards arising from the substance or mixture

**Unusual Fire & Explosion** 

**Hazards** 

Aerosol cans may explode in a fire.

## 5.3. Advice for firefighters

Special Fire Fighting

Procedures .

Containers close to fire should be removed or cooled with water. Use water to keep

fire exposed containers cool and disperse vapours.

## 6. Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
- 6.2. Environmental precautions
- 6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

#### 6.4. Reference to other sections

## 7. Handling and storage

#### 7.1 Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

## 7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

#### 7.3. Specific end use(s)

## 8. Exposure controls/personal protection

#### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min	
2-METHOXY-1-METHYLETHYL ACETATE	WEL	50 ppm(Sk)	274 mg/ m3(Sk)	100 ppm(Sk)	548 mg/ m3(Sk)
ACETONE				500 ppm	1210 mg/m3
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m3	200 ppm	966 mg/m3
ISOBUTANE	WEL	800 ppm		800 ppm	
METHYLAL			1900 mg/m3(c)		
PROPANE		Asphyxiating	Asphyxiating	Asphyxiating	Asphyxiating

WEL = Workplace Exposure Limits

## 8.2. Exposure controls

**Protective equipment** 





**Engineering measures** Provide adequate general and local exhaust ventilation.

**Respiratory equipment** No specific recommendation made, but respiratory protection must be used if the

general level exceeds the recommended occupational exposure limit. Use chemical

cartridge protection with appropriate cartridge.

**Hand protection** Use protective gloves.

**Eye protection** Wear approved chemical safety goggles where eye exposure is reasonably

probable.

Other Protection Wear appropriate clothing to prevent any possibility of liquid contact and repeated

or prolonged vapour contact.

Hygiene measures DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and

before eating, smoking and using the toilet. Promptly remove any clothing that

becomes contaminated. When using do not eat, drink or smoke.

## 9. Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Appearance Aerosol
Colour Typical

Odour Characteristic.

Flammability Limit -

Lower(%)

3.0

Flammability Limit -

Upper(%)

18.6

9.2. Other information

## 10. Stability and reactivity

#### 10.1. Reactivity

#### 10.2. Chemical stability

Stable under normal temperature conditions.

#### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

## 11. Toxicological information

#### 11.1. Information on toxicological effects

Inhalation May cause irritation to the respiratory system. Vapours may cause headache,

fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may

damage respiratory system.

**Ingestion** May cause discomfort if swallowed. May cause stomach pain or vomiting.

Gastrointestinal symptoms, including upset stomach.

**Skin contact** Prolonged or repeated exposure may cause severe irritation. Acts as a defatting

agent on skin. May cause cracking of skin, and eczema.

**Eye contact** Irritating to eyes.

**Route of entry** Inhalation. Skin and/or eye contact.

## 12. Ecological information

## **Ecotoxicity**

Dangerous for the environment if discharged into watercourses.

- 12.1. Toxicity
- 12.2. Persistence and degradability
- 12.3. Bioaccumulative potential
- 12.4. Mobility in soil
- 12.5. Results of PBT and vPvB assessment
- 12.6. Other adverse effects

## 13. Disposal considerations

13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

## 14. Transport information

14.1. UN number

 UN No. (ADR/RID/ADN)
 1950

 UN No. (IMDG)
 1950

 UN No. (ICAO)
 1950

14.2. UN proper shipping name

Proper Shipping Name AEROSOLS

14.3. Transport hazard class(es)

ADR/RID/ADN Class 2

ADR/RID/ADN Class Class 2: Gases

ADR Label No. 2.1

IMDG Class 2.1

ICAO Class/Division 2.1

**Transport Labels** 



## 14.4. Packing group

Packing group Not applicable.

14.5. Environmental hazards

**Environmentally Hazardous** No **Substance/Marine Pollutant** 

14.6. Special precautions for user

**EMS** 2-13

**Tunnel Restriction Code** 

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

#### 15. Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Uk Regulatory References** The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

**Statutory Instruments** The Control of Substances Hazardous to Health Regulations 2002.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

Approved Code Of Practice Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG(108).

#### 15.2. Chemical safety assessment

#### 16. Other information

Risk Phrases In Full R12 Extremely flammable.

R10 Flammable. R11 Highly flammable R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R41 Risk of serious damage to eyes.

R67 Vapours may cause drowsiness and dizziness.

Hazard Statements In Full H319 Causes serious eye irritation.

H222 Extremely flammable aerosol.
H220 Extremely flammable gas.
H226 Flammable liquid and vapour.
H225 Highly flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

## Classification according to Regulation (EC) No.

This information is provided for documentation purposes only. This product is not considered hazardous under normal conditions of use.

The complete range of conditions or methods of use are beyond our control therefore we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein believed to be true and accurate. However, all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of information, the hazards connected with the use of material or the results to be obtained from the use thereof. Compliance with all applicable federal, state and local laws and local regulations remains the responsibility of the user. This material safety sheet cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, or where additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. Please note that due to the on-going change in regulation from CHIP to CLP, any MSDS information in this MSDS is only considered accurate at the time of its creation. During this time classifications of substances may change. Therefore it is possible that can art work and MSDS information may differ. As such if you have any concerns we recommend you request a new MSDS from us every 6-12 months.