



SAFETY DATA SHEET

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 530/G115 - BILGE PAINT (RED, GREY, & GREEN)
Product number 530/G115/65/241/1323
UFI UFI: DCYP-F2AQ-D00T-QSDC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses As a coating for bilges

1.3. Details of the supplier of the safety data sheet

Supplier	TEAL & MACKRILL LIMITED Lockwood Street Hull HU2 OHN UK +441482320194 (T) +441482219266 (F) info@teamac.co.uk	TEAL AND MACKRILL EU B.V. Queens Towers Delflandlaan 1 1062 EA Amsterdam The Netherlands +31 (0)208 004828 (T) +441482219266 (F) info@teamac.co.uk
Contact person	Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above	

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 320194 Teamac (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)
SDS No. 10494

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226
Health hazards STOT SE 3 - H336
Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Hazard pictograms



Signal word Warning

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

Hazard statements	<p>EUH208 Contains NEODECANOATE ACID, COBALT SALT, C18-unsatd., dimers, compds. with coco alkylamines. May produce an allergic reaction.</p> <p>H226 Flammable liquid and vapour.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>
Precautionary statements	<p>P101 If medical advice is needed, have product container or label at hand.</p> <p>P102 Keep out of reach of children.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	HYDROCARBONS, C9-C11, <2% AROMATICS
Supplementary precautionary statements	<p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P370+P378 In case of fire: Use dry powder, dry sand or dry earth to extinguish.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p>

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCARBONS, C9-C11, <2% AROMATICS	30-60%
CAS number: —	EC number: 919-857-5
	REACH registration number: 01-2119463258-33-XXXX

Classification

Flam. Liq. 3 - H226

STOT SE 3 - H336

Asp. Tox. 1 - H304

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

Xylene Isomer Mixture 1-5%		
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-0000
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412		
2-METHOXY-1-METHYLETHYL ACETATE <1%		
CAS number: 108-65-6	EC number: 203-603-9	REACH registration number: 01-2119475791-29-xxxx
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336		
HYDROCARBONS, C9, AROMATICS <1%		
CAS number: —	EC number: 918-668-5	REACH registration number: 01-2119455851-35-xxxx
Classification Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		
NEODECANOATE ACID, COBALT SALT <1%		
CAS number: 27253-31-2	EC number: 248-373-0	
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H332 Skin Sens. 1 - H317 Repr. 2 - H361f Aquatic Chronic 3 - H412		

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics			<1%
CAS number: —	EC number: 918-481-9	REACH registration number: 01-2119457273-39-XXXX	
Classification			
Asp. Tox. 1 - H304			
C18-unsatd., dimers, compds. with coco alkylamines			<1%
CAS number: 68647-95-0	REACH registration number: 01-2120099181-55-0000		
Strontium bis(2-ethylhexanoate)			<1%
CAS number: 2457-02-5	EC number: 219-536-3	REACH registration number: 01-2120783571-49-0001	
Classification			
Acute Tox. 4 - H302			
Skin Irrit. 2 - H315			
Eye Dam. 1 - H318			
Repr. 2 - H361			
Dipropylene Glycol Methyl Ether			<1%
CAS number: 34590-94-8	EC number: 252-104-2	REACH registration number: 01-2119450011-60-XXXX	
Classification		Classification (67/548/EEC or 1999/45/EC)	
Not Classified		-	
PHTHALIC ANHYDRIDE			<1%
CAS number: 85-44-9	EC number: 201-607-5	REACH registration number: 01-2119457017-41-0000	
Classification			
Acute Tox. 4 - H302			
Skin Irrit. 2 - H315			
Eye Dam. 1 - H318			
Resp. Sens. 1 - H334			
Skin Sens. 1 - H317			
STOT SE 3 - H335			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	DO NOT induce vomiting. Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information Get medical attention promptly if symptoms occur after washing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Toxic gases or vapours. FLAMMABLE. Solvent vapours may form explosive mixtures with air.

5.3. Advice for firefighters

Protective actions during firefighting Risk of re-ignition after fire has been extinguished. Cool containers exposed to flames with water until well after the fire is out. Avoid the spillage or runoff entering drains, sewers or watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists. Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not eat, drink or smoke when using the product. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Keep container tightly closed. Keep containers upright. Store away from the following materials: Oxidising materials. Alkalis. Acids.

Storage class

Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

Usage description

Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Xylene Isomer Mixture

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 274 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 548 mg/m³

Sk

HYDROCARBONS, C9, AROMATICS

Long-term exposure limit (8-hour TWA): WEL 19 ppm 100 mg/m³ vapour

NEODECANOATE ACID, COBALT SALT

Long-term exposure limit (8-hour TWA): WEL 0.1 mg/m³

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

Long-term exposure limit (8-hour TWA): WEL 1000 mg/m³

Dipropylene Glycol Methyl Ether

Long-term exposure limit (8-hour TWA): WEL 50 ppm 308 mg/m³

Sk

PHTHALIC ANHYDRIDE

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³(Sen)

Short-term exposure limit (15-minute): WEL 12 mg/m³(Sen)

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

Sk = Can be absorbed through the skin.

HYDROCARBONS, C9-C11, <2% AROMATICS

DNEL	Industry - Inhalation; Long term systemic effects: 1500 mg/m ³ Consumer - Inhalation; Long term systemic effects: 900 mg/m ³ Consumer - Dermal; Long term systemic effects: 300 mg/kg/day Consumer - Oral; Long term systemic effects: 300 mg/kg/day Industry - Dermal; Long term systemic effects: 300 mg/kg/day
PNEC	No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

Xylene Isomer Mixture (CAS: 1330-20-7)

DNEL	Industry - Inhalation; Short term : 442 mg/m ³ Consumer - Inhalation; Long term systemic effects: 65.3 mg/m ³ Consumer - Dermal; Long term systemic effects: 1872 mg/kg/day Industry - Inhalation; Long term systemic effects: 221 mg/m ³ Consumer - Oral; Long term systemic effects: 12.5 mg/kg/day Industry - Dermal; Long term systemic effects: 3182 mg/kg/day Consumer - Inhalation; Short term : 260 mg/m ³
PNEC	- Fresh water; 0.327 mg/l - marine water; 0.327 mg/l - Intermittent release; 0.327 mg/l - STP; 6.58 mg/l - Sediment (Freshwater); 12.46 mg/kg - Sediment (Marinewater); 12.46 mg/kg - Soil; 2.31 mg/kg

2-METHOXY-1-METHYLETHYL ACETATE (CAS: 108-65-6)

DNEL	Workers - Inhalation; Long term systemic effects: 275 mg/m ³ Workers - Dermal; Long term systemic effects: 796 mg/kg/day Consumer - Inhalation; Long term systemic effects: 33 mg/m ³ Consumer - Dermal; Long term systemic effects: 320 mg/kg/day Consumer - Oral; Long term systemic effects: 36 mg/kg/day
-------------	--

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

PNEC	<ul style="list-style-type: none"> - marine water; 0.0635 mg/l - Soil; 0.29 mg/kg - Fresh water; 0.635 mg/l - STP; 100 mg/l - Sediment; 3.29 mg/kg - Intermittent release; 6.35 mg/l - Sediment (Marinewater); 0.329 mg/kg
-------------	---

HYDROCARBONS, C9, AROMATICS

DNEL	<p>Consumer - Oral; Long term systemic effects: 11 mg/kg/day Consumer - Dermal; Long term systemic effects: 11 mg/kg/day Consumer - Inhalation; Long term systemic effects: 32 mg/m³ Industry - Dermal; Long term systemic effects: 25 mg/kg/day Industry - Inhalation; Long term systemic effects: 150 mg/m³</p>
PNEC	No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

NEODECANOATE ACID, COBALT SALT (CAS: 27253-31-2)

DNEL	<p>Workers - Inhalation; Long term local effects: 0.2732 mg/m³ General population - Inhalation; Long term local effects: 0.043 mg/m³ General population - Oral; Long term systemic effects: 0.0649 mg/kg/day</p>
PNEC	<ul style="list-style-type: none"> - Fresh water; 0.003 Co mg/l - marine water; 0.00236 Co mg/l - STP; 0.37 Co mg/l - Sediment (Freshwater); 9.5 Co mg/kg/day - Sediment (Marinewater); 9.5 Cp mg/kg/day - Soil; 10.9 Co mg/kg/day

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Ingredient comments	WEL = Workplace Exposure Limits
	<u>Dipropylene Glycol Methyl Ether (CAS: 34590-94-8)</u>
DNEL	<p>Industry - Dermal; Long term : 65 mg/kg/day Industry - Inhalation; Long term : 310 mg/m³ Consumer - Dermal; Long term : 15 mg/kg/day Consumer - Inhalation; Long term : 37.2 mg/m³ Consumer - Oral; Long term : 1.67 mg/kg/day</p>
PNEC	<p>Fresh water; 19 mg/l marine water; 1.9 mg/l STP; 4168 mg/l Sediment (Freshwater); 70.2 mg/kg Sediment (Marinewater); 7.02 mg/kg Soil; 2.74 mg/kg Intermittent release; 19 mg/l</p>
	<u>Calcium bis(2-ethylhexanoate) (CAS: 136-51-6)</u>

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

DNEL	Workers - Dermal; Long term systemic effects: 5.67 mg/kg Workers - Inhalation; Long term systemic effects: 39.98 mg/m ³ General population - Oral; Long term systemic effects: 2.83 mg/kg General population - Dermal; Long term systemic effects: 2.83 mg/kg General population - Inhalation; Long term systemic effects: 9.86 mg/m ³
PNEC	STP; 71.7 mg/l Soil; 1.06 mg/kg Intermittent release; 0.493 mg/l Fresh water; 0.36 mg/l marine water; 0.036 mg/l Sediment (Freshwater); 6.37 mg/kg Sediment (Marinewater); 0.637 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturers' performance data suggest that the optimum glove for use should be: Wear protective gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.31 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

Respiratory protection	Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Wear a respirator fitted with the following cartridge: Gas filter, type A2.
Environmental exposure controls	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid. Coloured liquid.
Colour	Various colours.
Odour	Organic solvents.
Odour threshold	Not determined.
pH	Technically not feasible.
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	38 approx. °C Closed cup.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Upper/lower flammability or explosive limits	: 0.8
Other flammability	Not determined.
Vapour pressure	Not determined.
Vapour density	heavier than air
Relative density	1.46 @ @ 20°C
Solubility(ies)	Insoluble in water
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	3.0 (ICI Rotothinner) P @ 25 C°C
Explosive properties	Not determined.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not determined.

9.2. Other information

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

Volatile organic compound This product contains a maximum VOC content of 420 - 540 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not determined.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Acids. Oxidising agents.

10.5. Incompatible materials

Materials to avoid Strong alkalis. Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal

ATE dermal (mg/kg) 84,615.38

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 846.15

Inhalation Vapour from this product may be hazardous by inhalation. Vapour may irritate respiratory system/lungs.

Ingestion Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

Skin contact Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause allergic contact eczema. Prolonged or repeated exposure may cause severe irritation.

Eye contact May cause temporary eye irritation.

Acute and chronic health hazards This product has low toxicity. Only large quantities are likely to have adverse effects on human health.

Route of exposure Inhalation Skin absorption. Ingestion. Skin and/or eye contact.

Medical considerations Skin disorders and allergies. Avoid vomiting and stomach flushing because of the risk of aspiration.

Toxicological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Acute toxicity - oral

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

Acute toxicity oral (LD₅₀ mg/kg) 5,100.0

Species Rat

ATE oral (mg/kg) 5,100.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 5,100.0

Species Rabbit

ATE dermal (mg/kg) 5,100.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 5,100.0

Species Rat

ATE inhalation (vapours mg/l) 5,100.0

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Not irritating.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative. This substance has no evidence of mutagenic properties.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Fertility: - , Inhalation, Rat This substance has no evidence of toxicity to reproduction.

Reproductive toxicity - development Developmental toxicity: - : , Inhalation, Rat This substance has no evidence of toxicity to reproduction.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not available.

Aspiration hazard

Aspiration hazard Kinematic viscosity <= 20.5 mm²/s.

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

Inhalation	Vapours may cause drowsiness and dizziness. Central nervous system depression.
Ingestion	Harmful: danger of serious damage to health by prolonged exposure if swallowed.
Skin contact	Product has a defatting effect on skin. May cause allergic contact eczema.
Eye contact	No specific health hazards known.
Route of exposure	Inhalation Dermal

SECTION 12: Ecological information

Ecotoxicity The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

12.1. Toxicity

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Acute aquatic toxicity

Acute toxicity - fish	LC50, > 96 hours: 1000 mg/l, Oncorhynchus mykiss (Rainbow trout) Substance did not cause acute toxicity to fish
Acute toxicity - aquatic invertebrates	Substance did not cause acute toxicity to the freshwater invertebrates EC ₅₀ , 48 hours: >1000 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , > 72 hours: 1000 mg/l, Freshwater algae Substance did not cause acute toxicity to the freshwater green algae
Acute toxicity - microorganisms	EC ₅₀ , >: 100 mg/l, Activated sludge

Chronic aquatic toxicity

Chronic toxicity - fish early life stage	NOEC, 28 days: 0.131 mg/l, Oncorhynchus mykiss (Rainbow trout)
Chronic toxicity - aquatic invertebrates	NOEC, 28 days: 0.23 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is not expected to be biodegradable.

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Persistence and degradability	The product is readily biodegradable.
Phototransformation	Oxidises rapidly by photo-chemical reactions in air
Biodegradation	- 80 Degradation (%): 28 days Test - 301F Ready Biodegradability - Manometric Respiratory Test

12.3. Bioaccumulative potential

Bioaccumulative potential The product contains potentially bioaccumulating substances.

Partition coefficient Not determined.

Ecological information on ingredients.

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

HYDROCARBONS, C9-C11, <2% AROMATICS

Bioaccumulative potential The product contains potentially bioaccumulating substances.

Partition coefficient log Pow: 5 - 6.7

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. Readily absorbed into soil.

Adsorption/desorption coefficient Not available.

Surface tension 24.5 mN/m @ 20°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Avoid the spillage or runoff entering drains, sewers or watercourses.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT, contains Hydrocarbons, C9-C11, <2% Aromatics, Class 3, PGIII, (38°C) and hydrocarbons, C9, Aromatics (MARINE POLLUTANT)

Proper shipping name (IMDG) PAINT, contains Hydrocarbons, C9-C11, <2% Aromatics, Class 3, PGIII, (38°C) and hydrocarbons, C9, Aromatics (MARINE POLLUTANT)

Proper shipping name (ICAO) PAINT, contains Hydrocarbons, C9-C11, <2% Aromatics, Class 3, PGIII, (38°C) and hydrocarbons, C9, Aromatics (MARINE POLLUTANT)

Proper shipping name (ADN) PAINT, contains Hydrocarbons, C9-C11, <2% Aromatics, Class 3, PGIII, (38°C) and hydrocarbons, C9, Aromatics (MARINE POLLUTANT)

14.3. Transport hazard class(es)

ADR/RID class 3

IMDG class 3

ICAO class/division 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-E, S-E

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

530/G115 - BILGE PAINT (RED, GREY, & GREEN)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Commission Regulation (EU) No 2015/830 of 28 May 2015.
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

None of the ingredients are listed or exempt.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
IATA: International Air Transport Association.
ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.
IMDG: International Maritime Dangerous Goods.
CAS: Chemical Abstracts Service.
ATE: Acute Toxicity Estimate.
LC₅₀: Lethal Concentration to 50 % of a test population.
LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
EC₅₀: 50% of maximal Effective Concentration.
PBT: Persistent, Bioaccumulative and Toxic substance.
vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations and acronyms

Acute Tox. = Acute toxicity
Aquatic Acute = Hazardous to the aquatic environment (acute)
Aquatic Chronic = Hazardous to the aquatic environment (chronic)
Asp. Tox. = Aspiration hazard
Flam. Liq. = Flammable liquid
STOT RE = Specific target organ toxicity-repeated exposure
STOT SE = Specific target organ toxicity-single exposure

Revision comments

Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Addition of EU supplier information

Issued by Technical Dept. (N.O.)

Revision date 01/11/2021

Revision 10.0

Supersedes date 06/01/2021

SDS number 10494

530/G115 - BILGE PAINT (RED, GREY, & GREEN)**SDS status**

Approved.

Hazard statements in full

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H361f Suspected of damaging fertility.
H373 May cause damage to organs (Respiratory system, lungs) through prolonged or repeated exposure if inhaled.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH208 Contains NEODECANOATE ACID, COBALT SALT, C18-unsatd., dimers, compds. with coco alkylamines. May produce an allergic reaction.

Signature

Initials _____

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.