

Fire Varnish Overcoat Gloss / Satin / Matt

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 and SI 2020/1577

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1 Product identifier**

Product Name Fire Varnish Overcoat Gloss / Satin / Matt

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) /Uses identified against For professional use

1.3 Details of the supplier of the safety data sheet**Manufacturer**

Company Identification Thermoguard Limited
Address of Manufacturer Units B1-B2
Enterprise Park
Wigwam Lane
Hucknall
Nottingham
Postal code NG15 7SZ
Telephone: 01142768008
Fax 01624825526
E-mail sales@thermoguard.co.uk
Office hours 08:00 - 17:00

Supplier

Company Identification Thermoguard Limited
Address of Supplier Units B1-B2
Enterprise Park
Wigwam Lane
Hucknall
Nottingham
Postal code NG15 7SZ
Telephone: 01142768008
Fax 01624825526
E-mail sales@thermoguard.co.uk
Office hours 08:00 - 17:00

1.4 Emergency telephone number

Emergency Phone No. 01142 768008. 07858 518430. 07624 485725.
Contact Technical Department
National response centre
Address NHS Direct
Emergency Phone No. +44 111

SECTION 2: HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

Fire Varnish Overcoat Gloss / Satin / Matt

GB CLP Regulation, UK SI 2019/720 and Flam. Liq. 3 :Flammable liquid and vapour.
UK SI 2020/1567 STOT SE 3 :May cause drowsiness or dizziness.

2.2 Label elements

According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567

Product Name Fire Varnish Overcoat Gloss

Hazard Pictogram(s)



GHS02



GHS07

Signal Word(s)

Warning

Hazard Statement(s)

H226: Flammable liquid and vapour.
H336: May cause drowsiness or dizziness.
EUH208: Contains: (octabenzene) May produce an allergic reaction.

Precautionary Statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P370+P378: In case of fire: Use water spray, dry powder or carbon dioxide to extinguish.
P403+P235: Store in a well-ventilated place. Keep cool.

2.3 Other hazards

None known.

2.4 Additional Information

For full text of H/P Statements see section 16.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable.

3.2 Mixtures

HAZARDOUS INGREDIENT(S)	CAS No.	EC No. / Registration number(s)	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		919-857-5	40-60	Flam. Liq. 3 H226 Asp. Tox. 1 H304	GHS02 GHS08

Fire Varnish Overcoat Gloss / Satin / Matt

				STOT SE 3 H336	GHS07
octabenzene	1843-05-6	217-421-2	<1	Skin Sens. 1B H317	GHS07
2-methylpentane-2,4-diol	107-41-5	203-489-0	<1	Skin Irrit. 2 H315 Eye Irrit. 2 H319	GHS07
oxydipropyl dibenzoate	27138-31-4	248-258-5	<1	Aquatic Chronic 3 H412	None
2-ethylhexanoic acid, zirconium salt	22464-99-9	245-018-1	<1	Repr. 2 H361	GHS08
Xylene	1330-20-7	215-535-7	<0.5	Expl. 1.1 H201 Acute Tox. 4 H302 Acute Tox. 4 H312 Acute Tox. 4 H332 STOT RE 2 H373	GHS01 GHS08 GHS07
zirconium propionate	84057-80-7	281-897-8	<1	Not classified	None
2,6-di-tert-butyl-p-cresol	128-37-0	204-881-4	<1	Aquatic Chronic 3 H412	None

For full text of H/P Statements see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.
Skin Contact	Take off immediately all contaminated clothing. Rinse skin with water.
Eye Contact	Treat symptomatically.
Ingestion	Treat symptomatically.

4.2 Most important symptoms and effects, both acute and delayed

None anticipated. Treat symptomatically.

4.3 Indication of any immediate medical attention and special treatment needed

Call a POISON CENTRE/doctor if you feel unwell. Unlikely to be required but if necessary treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Fire Varnish Overcoat Gloss / Satin / Matt

Suitable Extinguishing media Use water spray, dry powder or carbon dioxide to extinguish.
Unsuitable extinguishing media Water jet spray

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour. Combustion or thermal decomposition will evolve toxic and irritant vapours.

5.3 Advice for firefighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. If it is safe to do so, containers should be removed from fire area because they are likely to rupture under fire conditions.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Ensure full personal protection (including respiratory protection) during removal of spillages.

6.2 Environmental precautions

Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.

6.3 Methods and material for containment and cleaning up

Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Containers must not be punctured or destroyed by burning, even when empty.

6.4 Reference to other sections

See Also Section 8, 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting/equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Keep cool.

Storage temperature Ambient.

Storage life Stable under normal conditions.

Incompatible materials None known.

7.3 Specific end use(s)

Not known.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Fire Varnish Overcoat Gloss / Satin / Matt

8.1 Control parameters

8.1.1 Occupational Exposure Limits

Occupational Exposure Limits						
SUBSTANCE.	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
2-Methylpentane-2,4-diol	107-41-5	25	123	25	123	
Zirconium compounds (as Zr)	22464-99-9		5		10	
Xylene, o-,m-,p- or mixed isomers	1330-20-7	50	220	100	441	Sk, BMGV
Zirconium compounds (as Zr)	84057-80-7		5		10	
2,6-Di-tert-butyl-p-cresol	128-37-0		10			

Region Source
 United Kingdom UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)

Remark Notes
 Sk Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.
 BMGV Biological monitoring guidance values are listed in Table 2.

Biological Exposure Indices						
Substances	CAS Number	Sampling	Tissues	Control parameters	Biological monitoring guidance value	Comments
Xylene, o-, m-, p- or mixed isomers	1330-20-7	Post shift	urine	methyl hippuric acid	650 mmol methyl hippuric acid/mol creatinine	

Remark Notes

8.2 Exposure controls

8.2.1. Appropriate engineering controls Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Ensure adequate ventilation.

8.2.2. Personal protection equipment



Eye Protection

Wear eye protection with side protection (EN166).



Skin protection

Wear protective clothing and gloves: Impervious gloves (EN 374).

Fire Varnish Overcoat Gloss / Satin / Matt



Respiratory protection Normally no personal respiratory protection is necessary. Handling of larger amounts A suitable mask with filter type A (EN14387 or EN405) may be appropriate.



Thermal hazards None known.

8.2.3. Environmental Exposure Controls Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Liquid. Colour : Viscous liquid Yellowish
Odour	Solvent odour.
Odour threshold	Not known.
pH	Not known.
Melting point/freezing point	Not known.
Initial boiling point and boiling range	Not known.
Flash Point	38 approx CC (closed cup)
Evaporation rate	Not known.
Flammability (solid, gas)	Not known.
Upper/lower flammability or explosive limits	Not known.
Vapour pressure	Not known.
Vapour density	heavier than air
Density (g/ml)	Not known.
Relative density	Not known.
Solubility(ies)	Solubility (Water) : Insoluble in water. Solubility (Other) : Not known.
Partition coefficient: n-octanol/water	Not known.
Auto-ignition temperature	Not known.
Decomposition Temperature (°C)	Not known.
Viscosity	>25 seconds kinematic@40C
Explosive properties	Not known.
Oxidising properties	Not known.

9.2 Other information

None.

Fire Varnish Overcoat Gloss / Satin / Matt

SECTION 10: STABILITY AND REACTIVITY**10.1 Reactivity**

None anticipated.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

Avoid friction, sparks, or other means of ignition.

10.5 Incompatible materials

Not known.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 Information on toxicological effects**

Acute toxicity - Ingestion

Calculation method : Not classified.

Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 500000.00000

Acute toxicity - Skin Contact

Calculation method : Not classified.

Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 1000000.00000

Acute toxicity - Inhalation

Calculation method : Not classified.

Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 11000.00000

Skin corrosion/irritation

Calculation method : Not classified.

Serious eye damage/irritation

Calculation method : Not classified.

Skin sensitization data

Calculation method : Not classified.

Respiratory sensitization data

Calculation method : Not classified.

Germ cell mutagenicity

Calculation method : Not classified.

Carcinogenicity

Calculation method : Not classified.

Reproductive toxicity

Calculation method : Not classified.

Lactation

Calculation method : Not classified.

STOT - single exposure

Calculation method : May cause drowsiness or dizziness.

STOT - repeated exposure

Calculation method : Not classified.

Aspiration hazard

Calculation method : May be fatal if swallowed and enters airways.

11.2 Other information

Not known.

SECTION 12: ECOLOGICAL INFORMATION

Fire Varnish Overcoat Gloss / Satin / Matt

12.1 Toxicity

Toxicity - Aquatic invertebrates	Low toxicity to invertebrates.
Toxicity - Fish	Low toxicity to fish.
Toxicity - Algae	Low toxicity to algae.
Toxicity - Sediment Compartment	Not classified.
Toxicity - Terrestrial Compartment	Not classified.

12.2 Persistence and degradability

Not known.

12.3 Bioaccumulative potential

Not known.

12.4 Mobility in soil

Not known.

12.5 Results of PBT and vPvB assessment

Not known.

12.6 Other adverse effects

Not known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Dispose of contents in accordance with local, state or national legislation. Recycle only completely emptied packaging. Containers must not be punctured or destroyed by burning, even when empty. Do not allow to enter drains, sewers or watercourses. Do NOT landfill. Normal disposal is via incineration operated by an accredited disposal contractor. Send to a licensed recycler, reclaimer or incinerator. Dispose at suitable refuse site.

13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number

UN No. 1263

14.2 UN proper shipping name

UN proper shipping name PAINT

14.3 Transport hazard class(es)

ADR/RID

ADR/RID Class 3

Fire Varnish Overcoat Gloss / Satin / Matt

ADR Classification Code	F1
Special Provisions	163, 367, 650
Limited Quantities	5 L
Excepted Quantities	E1
Emergency Action Code	•3Y
Mixed Packing Instructions for Packages	P001 IBC03 LP01 R001
Special Packing Provisions for Packages	PP1
Mixed Packing Instructions for Packages	MP19
Packing Instructions for Portable Tanks	T2
Special Provisions for Portable Tanks	TP1 TP29
Tank Code for Tanks	LGBF
Special Provisions for Tanks	
Vehicle for Tank Carriage	FL
ADR Transport Category	3
Tunnel Restriction Code	D/E
Special Provisions for Carriage - Packages	V12
Special Provisions for Carriage - Bulk	
Special Provisions for Carriage - Loading, Unloading and Handling	
Special Provisions for Carriage - Operation	S2
ADR HIN	30
IMDG	
IMDG Class	3
Special Provisions	163, 367, 650
Limited Quantities	5 L
Excepted Quantities	E1
Mixed Packing Instructions for Packages	P001 IBC03 LP01 R001
Special Packing Provisions for Packages	PP1
Packing Instructions for Portable Tanks	T2
Special Provisions for Portable Tanks	TP1 TP29
IMDG EMS	F-E, S-E
Stowage and Handling	Category A
Segregation	
Marine Pollutant	
ICAO/IATA	
IATA Proper Shipping Name	PAINT
Excepted Quantities	E1
Passenger and Cargo Aircraft Limited Quantities Packing Instructions	Y344
Passenger and Cargo Aircraft Limited Quantities Max net Qty	10L
Passenger and Cargo Aircraft Packing Instructions	355

Fire Varnish Overcoat Gloss / Satin / Matt

Passenger and Cargo Aircraft Max net Qty	60L
Cargo Aircraft Packing Instructions	366
Cargo Aircraft Max net Qty	220L
Special Provisions	A3, A72, A192
Emergency Response Guidebook (ERG) Code	3L
Labels	
Labels	3



14.4 Packing group

Packing group III

14.5 Environmental hazards

Environmental hazards Not classified as a Marine Pollutant.

14.6 Special precautions for user

Special precautions for user Not known.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No information available

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

United Kingdom Regulations - Authorisations and/or Restrictions On Use

UK REACH Candidate List of Substances Not listed

of Very High Concern for Authorisation

UK REACH Authorisation List (Annex XIV) list of substances subject to

authorisation

UK REACH Restrictions List (Annex XVII) octabenzene (1843-05-6), 2-methylpentane-2,4-diol (107-41-5), oxydipropyl dibenzoate (27138-31-4), Xylene (1330-20-7), 2,6-di-tert-butyl-p-cresol (128-37-0), Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics ()

Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

UK REACH Rolling Action Plan (RAP) Not listed

The Persistent Organic Pollutants Regulations 2007 (SI 2007/3106) as amended Not listed

The Ozone-Depleting Substances and Fluorinated Greenhouse Gases (Amendment etc.) (EU Exit) Regulations 2019 (SI 2019/583) Not listed

The Prior Informed Consent (PIC) Regulations concerning the export and

Fire Varnish Overcoat Gloss / Satin / Matt

import of hazardous chemicals

SI2008/2108 as amended

European Regulations - Authorisations and/or Restrictions On Use

Community Rolling Action Plan (CoRAP) Octabenzene (1843-05-6), oxydipropyl dibenzoate (27138-31-4), Xylene (1330-20-7), 2,6-di-tert-butyl-p-cresol (128-37-0)

15.2 Chemical Safety Assessment

United Kingdom

A REACH chemical safety assessment has not been carried out.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements:

LEGEND

Hazard Pictogram(s)



GHS02



GHS07

GHS01: GHS: Exploding bomb

GHS08: GHS: Health hazard

Hazard classification

Expl. 1.1 : Explosive, Category 1.1

Flam. Liq. 3 : Flammable liquid, Category 3

Acute Tox. 4 : Acute toxicity, Category 4

Asp. Tox. 1 : Aspiration hazard, Category 1

Acute Tox. 4 : Acute toxicity, Category 4

Skin Irrit. 2 : Skin corrosion/irritation, Category 2

Fire Varnish Overcoat Gloss / Satin / Matt

Skin Sens. 1B : Skin sensitization, Category 1B

Eye Irrit. 2 : Serious eye damage/irritation, Category 2

Acute Tox. 4 : Acute toxicity, Category 4

STOT SE 3 : Specific target organ toxicity — single exposure, Category 3

Repr. 2 : Reproductive toxicity, Category 2

STOT RE 2 : Specific target organ toxicity — repeated exposure, Category 2

Aquatic Chronic 3 : Hazardous to the aquatic environment, Chronic, Category 3

Hazard Statement(s)

H201: Explosive; mass explosion hazard.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H361: Suspected of damaging fertility or the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

H412: Harmful to aquatic life with long lasting effects.

Precautionary Statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233: Keep container tightly closed.

P240: Ground and bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/equipment.

P242: Use non-sparking tools.

P243: Take action to prevent static discharges.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTRE/doctor if you feel unwell.

Fire Varnish Overcoat Gloss / Satin / Matt

P370+P378: In case of fire: Use water spray, dry powder or carbon dioxide to extinguish.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

P501: Dispose of contents in accordance with local, state or national legislation.

Acronyms

ADN : European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE : Acute Toxicity Estimate

CAS : Chemical Abstracts Service

DNEL : Derived No Effect Level

EC : European Community

EINECS : European Inventory of Existing Commercial Chemical Substances

IATA : International Air Transport Association

IBC : Intermediate Bulk Container

ICAO : International Civil Aviation Organization

IMDG : International Maritime Dangerous Goods

LTEL : Long term exposure limit

PBT : Persistent, Bioaccumulative and Toxic

PNEC : Predicted No Effect Concentration

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STEL : Short term exposure limit

STOT : Specific Target Organ Toxicity

UN : United Nations

vPvB : very Persistent and very Bioaccumulative

Key literature references and sources for GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 data used to compile the SDS

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Thermoguard Limited gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Thermoguard Limited accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.