



SAFETY DATA SHEET

Carboetch Acid Etch for Floors

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Carboetch Acid Etch for Floors
Product number H005 - H007
REACH registration number 01-2119484862-27-0000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Solvent for Industrial Use

1.3. Details of the supplier of the safety data sheet

Supplier Palatine Paints & Chemicals Limited
 55 Smallbrook Lane
 Leigh
 Greater Manchester
 WN7 5PZ
 01942 884122 NOT 24HR
 sales@palatinepaints.co.uk

1.4. Emergency telephone number

Emergency telephone 0870 190 6777 (National Chemical Emergency Centre) +44 (0)1270 502891

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Met. Corr. 1 - H290
Health hazards Skin Corr. 1B - H314 STOT SE 3 - H335
Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H290 May be corrosive to metals.
 H314 Causes severe skin burns and eye damage.
 H335 May cause respiratory irritation.

Carboetch Acid Etch for Floors

Precautionary statements	P260 Do not breathe vapour/ spray.
	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
	P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P308+P313 IF exposed or concerned: Get medical advice/ attention.

Contains HYDROCHLORIC ACID ...%

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCHLORIC ACID ...%		5-10%
CAS number: 7647-01-0	EC number: 231-595-7	REACH registration number: 01-2119484862-27-0000
Classification		
Met. Corr. 1 - H290		
Skin Corr. 1B - H314		
STOT SE 3 - H335		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Inhalation	Remove affected person from source of contamination. If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention immediately. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
Skin contact	Remove contaminated clothing and rinse skin thoroughly with water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Vapours irritate the respiratory system. Shortness of breath. Burning sensation in the throat.
Ingestion	May cause chemical burns in mouth, oesophagus and stomach.
Skin contact	Causes severe skin burns and eye damage. Blistering may occur.
Eye contact	Causes severe skin burns and eye damage. Corneal damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

Carboetch Acid Etch for Floors

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours. Can react with most common metals to produce hydrogen.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Fight fire from safe distance or protected location.

Special protective equipment for firefighters Wear chemical protective suit. Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with skin and eyes. Avoid inhalation of vapours and contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains. Avoid release to the environment. Avoid or minimise the creation of any environmental contamination.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Wash thoroughly after dealing with a spillage. Do not touch or walk into spilled material. Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid inhalation of vapours/spray and contact with skin and eyes. Provide adequate ventilation. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from food, drink and animal feeding stuffs.

Storage class Corrosive storage.

7.3. Specific end use(s)

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Carboetch Acid Etch for Floors

HYDROCHLORIC ACID ...%

Long-term exposure limit (8-hour TWA): WEL 1 ppm 2 mg/m³ gas and aerosol mists

Short-term exposure limit (15-minute): WEL 5 ppm 8 mg/m³ gas and aerosol mists

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn. To protect hands from chemicals, gloves should comply with European Standard EN374. It is recommended that gloves are made of the following material: Polyvinyl chloride (PVC). Butyl rubber. Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination.

Hygiene measures

Provide eyewash station. Wash promptly if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.

Respiratory protection

Wear a full facepiece, supplied-air respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Colourless.
Odour	Odourless.
Initial boiling point and range	97.7°C
Vapour pressure	11 @ 20°C
Relative density	1.05 @ 20°C
Solubility(ies)	Soluble in water.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Reacts violently with strong oxidising substances.

10.2. Chemical stability

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

Carboetch Acid Etch for Floors

Possibility of hazardous reactions Under normal conditions of storage and use, no hazardous reactions will occur. Gives off hydrogen by reaction with metals. Can react violently with oxidising agents liberating chlorine. Exothermic reaction with alkalis.

10.4. Conditions to avoid

Conditions to avoid Contact with some metals may result in the release of hydrogen gas. Alkalis.

10.5. Incompatible materials

Materials to avoid Metals. Alkalis.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Chlorine. Hydrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General information Exposure may cause coughing and wheezing. Nausea and stomach pain may occur.

Inhalation Vapours irritate the respiratory system. Shortness of breath. Burning sensation in the throat.

Ingestion May cause chemical burns in mouth, oesophagus and stomach.

Skin contact Causes severe burns.

Eye contact Risk of serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 20.5 mg/l,

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 0.45 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability Will disperse as ions.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

12.4. Mobility in soil

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects No known significant effects.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Carboetch Acid Etch for Floors

General information Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Confirm disposal procedures with environmental engineer and local regulations.

Disposal methods Do not allow runoff to sewer, waterway or ground.

SECTION 14: Transport information

2491

14.1. UN number

UN No. (ADR/RID)	1789
UN No. (IMDG)	1789
UN No. (ICAO)	1789
UN No. (ADN)	1789

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	HYDROCHLORIC ACID
Proper shipping name (IMDG)	HYDROCHLORIC ACID
Proper shipping name (ICAO)	HYDROCHLORIC ACID
Proper shipping name (ADN)	HYDROCHLORIC ACID

14.3. Transport hazard class(es)

ADR/RID class	8
ADR/RID classification code	C1
ADR/RID label	8
IMDG class	8
ICAO class/division	8
ADN class	8

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ICAO packing group	II
ADN packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Carboetch Acid Etch for Floors

EmS	F-A, S-B
ADR transport category	2
Emergency Action Code	2R
Hazard Identification Number (ADR/RID)	80
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1272/2008 CLP. Regulation (EC) No 1907/2006 REACH.
----------------	--

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	Only trained personnel should use this material. Since empty containers retain product residue, follow label warnings, even after container is emptied. For further Health and Safety information contact: Health and Safety Officer. Labels should not be removed from containers until they have been cleaned and no product remains within.
Revision comments	ID code added.
Issued by	Compliance Department
Revision date	11/04/2019
Revision	3
Supersedes date	14/03/2018
SDS number	20247
Hazard statements in full	H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. H335 May cause respiratory irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.