

SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1. Product identifier		
Product name	Indasa Abrasives UK Limited - Black Stone Chip 500ml Aerosols	
Product number	472484	
1.2. Relevant identified uses	of the substance or mixture and uses advised against	
Identified uses	Underbody coat.	
1.3. Details of the supplier of	the safety data sheet	
Supplier	Indasa Abrasives UK Limited Viking Works Greenstead Road Colchester Essex CO1 2ST Tel: +44 1206 870366 Fax: +44 1206 860525 office@indasa.co.uk	
1.4. Emergency telephone nu	mber	
Emergency telephone	+44 (0) 1206 870 366 (Hours 09:00 - 17:00 Mon to Fri)	
SECTION 2: Hazards identified	cation	
2.1. Classification of the subs	tance or mixture	
Classification (EC 1272/2008		
Classification (EC 1272/2008) Physical hazards	Aerosol 1 - H222, H229	
Physical hazards	Aerosol 1 - H222, H229	
Physical hazards Health hazards	Aerosol 1 - H222, H229 Eye Irrit. 2 - H319 STOT SE 3 - H336	
Physical hazards Health hazards Environmental hazards	Aerosol 1 - H222, H229 Eye Irrit. 2 - H319 STOT SE 3 - H336 Aquatic Chronic 2 - H411 Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional	
Physical hazards Health hazards Environmental hazards Human health	Aerosol 1 - H222, H229 Eye Irrit. 2 - H319 STOT SE 3 - H336 Aquatic Chronic 2 - H411 Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards.	
Physical hazards Health hazards Environmental hazards Human health Environmental	Aerosol 1 - H222, H229 Eye Irrit. 2 - H319 STOT SE 3 - H336 Aquatic Chronic 2 - H411 Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards. The product contains a substance which is toxic to aquatic organisms. Containers can burst violently or explode when heated, due to excessive pressure build-up.	
Physical hazards Health hazards Environmental hazards Human health Environmental Physicochemical	Aerosol 1 - H222, H229 Eye Irrit. 2 - H319 STOT SE 3 - H336 Aquatic Chronic 2 - H411 Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards. The product contains a substance which is toxic to aquatic organisms. Containers can burst violently or explode when heated, due to excessive pressure build-up.	
Physical hazards Health hazards Environmental hazards Human health Environmental Physicochemical 2.2. Label elements	Aerosol 1 - H222, H229 Eye Irrit. 2 - H319 STOT SE 3 - H336 Aquatic Chronic 2 - H411 Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards. The product contains a substance which is toxic to aquatic organisms. Containers can burst violently or explode when heated, due to excessive pressure build-up.	

Hazard statements	EUH208 Contains reaction mass of: N,N'-ethane-1,2-diylbis(hexanamide), 2-butanone oxime. May produce an allergic reaction. H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	 P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTRE/doctor if you feel unwell. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	ACETONE
Supplementary precautionary statements	 P264 Wash contaminated skin thoroughly after handling. P273 Avoid release to the environment. P337+P313 If eye irritation persists: Get medical advice/ attention. P391 Collect spillage. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

3.2. Mixtures		
ACETONE		10-309
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-
		2119471330-49-XXXX
Classification		
Flam. Liq. 2 - H225		
Eye Irrit. 2 - H319		
STOT SE 3 - H336		

PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE		10-5	30%
CAS number: 68476-85-7	EC number: 270-704-2		
Classification Flam. Gas 1 - H220 Press. Gas (Comp.) - H280			
XYLENE		5-	·10%
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01- 2119488216-32-XXXX	
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412			
trizinc bis(orthophosphate)		1	1-5%
CAS number: 7779-90-0	EC number: 231-944-3	REACH registration number: 01- 2119485044-40-XXXX	
M factor (Acute) = 1	M factor (Chronic) = 1		
Classification Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410			
reaction mass of: N,N'-ethane-1,2	2-diylbis(hexanamide)		<1%
CAS number: —	EC number: 432-430-3	REACH registration number: 01- 0000017860-69-XXXX	
Classification Skin Sens. 1 - H317 Aquatic Chronic 4 - H413			
ETHYLBENZENE			<1%
CAS number: 100-41-4	EC number: 202-849-4	REACH registration number: 01- 2119489370-35-XXXX	
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H332 STOT RE 2 - H373 Asp. Tox. 1 - H304			

NAPHTHA (PETROLEUM), HYD			<1%
CAS number: 64742-48-9	EC number: 919-857-5	REACH registration number: 01- 2119463258-33-XXXX	
Classification			
Flam. Liq. 3 - H226			
STOT SE 3 - H336			
Asp. Tox. 1 - H304			
ZIRCONIUM SALT, 2-ETHYLHE	XANOIC ACID		<1%
CAS number: 22464-99-9	EC number: 245-018-1	REACH registration number: 01- 2119979088-21-XXXX	
Classification Repr. 2 - H361			
zinc oxide			<1%
CAS number: 1314-13-2	EC number: 215-222-5	REACH registration number: 01- 2119463881-32-XXXX	
M factor (Acute) = 1	M factor (Chronic) = 1		
Classification			
Aquatic Acute 1 - H400			
Aquatic Chronic 1 - H410			
2-butanone oxime			<1%
CAS number: 96-29-7	EC number: 202-496-6	REACH registration number: 01- 2119539477-28-XXXX	
Classification			
Acute Tox. 4 - H312			
Eye Dam. 1 - H318			
Skin Sens. 1 - H317			
Carc. 2 - H351			
The full text for all hazard stateme	nts is displayed in Section 16.		
SECTION 4: First aid measures			
4.1. Description of first aid measur			
	ove affected person to fresh air and keep	warm and at rest in a position comfortable f	or

	breathing. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.
Ingestion	Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.

Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.
4.2. Most important symptoms	and effects, both acute and delayed
General information	See Section 11 for additional information on health hazards.
4.3. Indication of any immediat	e medical attention and special treatment needed
Notes for the doctor	Treat symptomatically.
SECTION 5: Firefighting meas	ures
5.1. Extinguishing media	
Suitable extinguishing media	Foam, carbon dioxide or dry powder.
5.2. Special hazards arising fro	om the substance or mixture
Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.
5.3. Advice for firefighters	
Protective actions during firefighting	Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.
SECTION 6: Accidental releas	e measures
6.1. Personal precautions, prot	tective equipment and emergency procedures
Personal precautions	Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.
6.2. Environmental precautions	3
Environmental precautions	Avoid discharge into drains.
6.3. Methods and material for o	containment and cleaning up
Methods for cleaning up	Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.
6.4. Reference to other section	
Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
SECTION 7: Handling and stor	rage
7.1. Precautions for safe handl	ing
Usage precautions	Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.
Advice on general occupational hygiene	Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke when using this product.
7.2. Conditions for safe storage	e, including any incompatibilities
Storage precautions	Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³ Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³ Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³ Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³ Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³ Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³ Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³ Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³ Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³ Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³ Sk, Sk

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m³ Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m³ Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m³ Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m³ Sk, Sk

WEL = Workplace Exposure Limit Sk = Can be absorbed through the skin.

ACETONE (CAS: 67-64-1)

DNEL	Workers - Dermal; Long term systemic effects: 186 mg/kg/day Workers - Inhalation; Short term local effects: 2420 mg/m³ Workers - Inhalation; Long term systemic effects: 1210 mg/m³
PNEC	- Sediment (Freshwater); 30.4 mg/kg - Sediment (Marinewater); 3.04 mg/kg - marine water; 1.06 mg/l - Soil; 29.5 mg/kg
	XYLENE (CAS: 1330-20-7)
DNEL	Consumer - Dermal; Long term systemic effects: 108 mg/kg/day Workers - Dermal; Long term systemic effects: 180 mg/kg/day Consumer - Inhalation; Short term local effects: 174 mg/m ³ Consumer - Inhalation; Short term systemic effects: 174 mg/m ³ Workers - Inhalation; Short term systemic effects: 289 mg/m ³ Workers - Inhalation; Short term local effects: 289 mg/m ³ Consumer - Inhalation; Long term systemic effects: 14.8 mg/m ³ Workers - Inhalation; Long term systemic effects: 77 mg/m ³

PNEC	 Fresh water; 0.327 mg/l marine water; 0.327 mg/l Intermittent release; 0.327 mg/l STP; 6.58 mg/l Sediment (Freshwater); 12.46 mg/kg Sediment (Marinewater); 12.46 mg/kg Soil; 2.31 mg/kg
8.2. Exposure controls	
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
Hand protection	No specific requirements are anticipated under normal conditions of use.
Other skin and body protection	Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.
Respiratory protection	No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Black.
Odour	Solvent.
Odour threshold	No information available.
рН	No information available.
Melting point	No information available.
Initial boiling point and range	-41 (-41 TO 215)°C @
Flash point	-40°C Closed cup.
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.8 % Upper flammable/explosive lim
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	0.866
Solubility(ies)	Insoluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	240°C
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.

7/13

Oxidising properties	No information available.	
9.2. Other information		
Other information	None.	
SECTION 10: Stability and reactivity		
10.1. Reactivity		
Reactivity	No test data specifically related to reactivity available for this product or its ingredients.	
10.2. Chemical stability		
Stability	The product may not be stable under some conditions of storage or use.	
10.3. Possibility of hazardous	reactions	
Possibility of hazardous reactions	None known.	
10.4. Conditions to avoid		
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.	
10.5. Incompatible materials		
Materials to avoid	None known.	
10.6. Hazardous decompositio	on products	
Hazardous decomposition products	None at ambient temperatures.	
SECTION 11: Toxicological inf	formation	
11.1. Information on toxicologi	cal effects	
Acute toxicity - dermal		
ATE dermal (mg/kg)	12,087.91	
Acute toxicity - inhalation ATE inhalation (vapours mg/l)	120.88	
Inhalation	May cause drowsiness or dizziness. Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.	
Skin contact	Repeated exposure may cause skin dryness or cracking. May cause sensitisation or allergic reactions in sensitive individuals.	
Eye contact	Causes serious eye irritation.	
Acute and chronic health hazards	No known chronic or acute health risks.	
Route of exposure	Inhalation Skin and/or eye contact	
Toxicological information on in	gredients.	
	<u>•</u>	

ACETONE

Acute toxicity - oral Acute toxicity oral (LD₅₀ 5,800.0 mg/kg)

Species	Rat
ATE oral (mg/kg)	5,800.0
Acute toxicity - dermal	
Acute toxicity dermal (LD₅₀ mg/kg)	7,800.0
Species	Rabbit
ATE dermal (mg/kg)	7,800.0
Acute toxicity - inhalation	
Acute toxicity inhalation (LC∞ vapours mg/l)	21.0
Species	Rat
ATE inhalation (vapours mg/l)	21.0
	XYLENE
Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	4,300.0
Species	Rat
ATE oral (mg/kg)	4,300.0
Acute toxicity - dermal	
Acute toxicity dermal (LD₅₀ mg/kg)	3,200.0
Species	Rabbit
ATE dermal (mg/kg)	1,100.0
Acute toxicity - inhalation	
ATE inhalation (vapours mg/l)	11.0
	ETHYLBENZENE
Acute toxicity - inhalation	
ATE inhalation (vapours mg/l)	11.0
	NAPHTHA (PETROLEUM), HYDROTREATED HEAVY
Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	5,001.0
Species	Rat
ATE oral (mg/kg)	5,001.0
Acute toxicity - dermal	

	Acute toxicity dermal (LD₅o mg/kg)	3,001.0
	Species	Rabbit
	ATE dermal (mg/kg)	3,001.0
		2-butanone oxime
	Acute toxicity - dermal	
	ATE dermal (mg/kg)	1,100.0
SECTION 12	2: Ecological information	
12.1. Toxicit	<u>v</u>	
Ecological ir	nformation on ingredients.	
		ACETONE
	Acute aquatic toxicity	
	Acute toxicity - fish	EC₅₀, 96 hours: 8300 mg/l, Lepomis macrochirus (Bluegill)
	Acute toxicity - aquatic invertebrates	EC₅₀, : 8800 mg/l, Daphnia magna
		XYLENE
	Acute aquatic toxicity	
	Acute toxicity - fish	LOEC, : >1 - <10 mg/l, Fish
	Acute toxicity - aquatic plants	LOEC, : >1 - <10 mg/l, Algae
		trizinc bis(orthophosphate)
	Acute aquatic toxicity	
	LE(C)₅₀	0.1 < L(E)C50 ≤ 1
	M factor (Acute)	1
	Chronic aquatic toxicity	
	NOEC	0.01 < NOEC ≤ 0.1
	Degradability	Non-rapidly degradable
	M factor (Chronic)	1
		zinc oxide
	Acute aquatic toxicity	
	LE(C)∞	0.1 < L(E)C50 ≤ 1
	M factor (Acute)	1
	Chronic aquatic toxicity	
	NOEC	0.01 < NOEC ≤ 0.1
	Degradability	Non-rapidly degradable

M factor (Chronic) 1				
12.2. Persistence and degradability				
Persistence and degradability	No data available.			
12.3. Bioaccumulative potentia	<u>u</u>			
Partition coefficient	No information available.			
12.4. Mobility in soil				
Mobility	No data available.			
12.5. Results of PBT and vPvE	3 assessment			
Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.			
12.6. Other adverse effects				
Other adverse effects	None known.			
SECTION 13: Disposal consid	erations			
13.1. Waste treatment method	<u>s</u>			
General information	Dispose of waste product or used containers in accordance with local regulations Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.			
Disposal methods	Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.			
Waste class	The waste code classification is to be carried out according to the European Waste Catalogue (EWC).			
SECTION 14: Transport inform	nation			
14.1. UN number				
UN No. (ADR/RID)	1950			
UN No. (IMDG)	1950			
UN No. (ICAO)	1950			
UN No. (ADN)	1950			
14.2. UN proper shipping name	<u>e</u>			
Proper shipping name (ADR/RID)	AEROSOLS, FLAMMABLE			
Proper shipping name (IMDG)	AEROSOLS, FLAMMABLE			
Proper shipping name (ICAO)	AEROSOLS, FLAMMABLE			
Proper shipping name (ADN)	AEROSOLS, FLAMMABLE			
14.3. Transport hazard class(e	<u>es)</u>			
ADR/RID class	2.1			
ADR/RID classification code	5F			
ADR/RID label	2.1			
IMDG class	2.1			

ICAO class/division	2.1

ADN class 2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



EmS	F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
--

National regulations	The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
EU legislation	 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended). Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	25/03/2019
Revision	2
Supersedes date	18/12/2014
SDS number	5207

Lineard statements in fall	
Hazard statements in full	H220 Extremely flammable gas.
	H222 Extremely flammable aerosol.
	H225 Highly flammable liquid and vapour.
	H226 Flammable liquid and vapour.
	H229 Pressurised container: may burst if heated.
	H280 Contains gas under pressure; may explode if heated.
	H304 May be fatal if swallowed and enters airways.
	H312 Harmful in contact with skin.
	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H318 Causes serious eye damage.
	H319 Causes serious eye irritation.
	H332 Harmful if inhaled.
	H335 May cause respiratory irritation.
	H336 May cause drowsiness or dizziness.
	H351 Suspected of causing cancer.
	H361 Suspected of damaging fertility or the unborn child.
	H373 May cause damage to organs through prolonged or repeated exposure.
	H400 Very toxic to aquatic life.
	H410 Very toxic to aquatic life with long lasting effects.
	H411 Toxic to aquatic life with long lasting effects.
	H412 Harmful to aquatic life with long lasting effects.
	H413 May cause long lasting harmful effects to aquatic life.
	EUH208 Contains reaction mass of: N,N'-ethane-1,2-diylbis(hexanamide), 2-butanone oxime.
	May produce an allergic reaction.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.