

# **SAFETY DATA SHEET**

# Indasa Abrasives UK Limited - Spray Adhesive 500ml Aerosols

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Indasa Abrasives UK Limited - Spray Adhesive 500ml Aerosols

Product number 472743

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Indasa Abrasives UK Limited

Viking Works Greenstead Road Colchester Essex CO1 2ST

Tel: +44 1206 870366 Fax: +44 1206 860525 office@indasa.co.uk

1.4. Emergency telephone number

**Emergency telephone** +44 (0) 1206 870 366 (Hours 09:00 - 17:00 Mon to Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

**Health hazards** Skin Irrit. 2 - H315 Eye Irrit. 2 - H319

**Environmental hazards** Aquatic Chronic 3 - H412

Human health Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional

information on health hazards.

**Environmental** The product contains a substance which is harmful to aquatic organisms.

**Physicochemical** Containers can burst violently or explode when heated, due to excessive pressure build-up.

The product is extremely flammable. Vapours may form explosive mixtures with air.

2.2. Label elements

Hazard pictograms





Signal word

Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing vapour/ spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Supplementary precautionary

statements

P264 Wash contaminated skin thoroughly after handling.

P273 Avoid release to the environment.

P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/ container in accordance with national regulations.

#### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

# SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

#### PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE

30-60%

CAS number: 68476-85-7 EC number: 270-704-2

Classification

Flam. Gas 1 - H220

Press. Gas (Comp.) - H280

10-30% **ACETONE** 

CAS number: 67-64-1 EC number: 200-662-2 REACH registration number: 01-

2119471330-49-XXXX

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

# LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED LIGHT

10-30%

CAS number: 64742-49-0 EC number: 265-151-9

Classification

Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

General information Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Get medical attention if any discomfort continues.

**Inhalation** Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. If in doubt, get medical attention promptly.

**Ingestion** Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for

breathing. Get medical attention.

Skin contact Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur

after washing.

**Eye contact** Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of

water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms

occur after washing.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

## 4.2. Most important symptoms and effects, both acute and delayed

**General information** See Section 11 for additional information on health hazards.

## 4.3. Indication of any immediate medical attention and special treatment needed

#### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media Foam, carbon dioxide or dry powder.

## 5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

# 5.3. Advice for firefighters

Protective actions during

firefighting

Use water to keep fire exposed containers cool and disperse vapours. Cool containers

exposed to heat with water spray and remove them from the fire area if it can be done without

risk.

## SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory

protection is worn during removal of spillages in confined areas.

#### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near

spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into

containers.

#### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health

hazards. See Section 12 for additional information on ecological hazards. For waste disposal,

see Section 13.

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Read and follow manufacturer's

recommendations. When sprayed on a naked flame or any incandescent material the aerosol

vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.

Advice on general occupational hygiene

Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke

when using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources

or expose to high temperatures. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

#### SECTION 8: Exposure controls/Personal protection

## 8.1. Control parameters

#### Occupational exposure limits

#### PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³ Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³ Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³ Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

#### **ACETONE**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³ Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³ Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³ Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

WEL = Workplace Exposure Limit

#### **ACETONE (CAS: 67-64-1)**

**DNEL** Workers - Dermal; Long term systemic effects: 186 mg/kg/day

Workers - Inhalation; Short term local effects: 2420 mg/m³ Workers - Inhalation; Long term systemic effects: 1210 mg/m³

PNEC - Sediment (Freshwater); 30.4 mg/kg

- Sediment (Marinewater); 3.04 mg/kg

- marine water; 1.06 mg/l

- Soil; 29.5 mg/kg

#### 8.2. Exposure controls

**Eye/face protection** Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible.

**Hand protection** No specific requirements are anticipated under normal conditions of use.

Other skin and body

Wear suitable protective equipment for prolonged exposure and/or high concentrations of

**protection** vapours, spray or mist.

Respiratory protection No specific recommendations. If ventilation is inadequate, suitable respiratory protection must

be worn.

#### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Clear.

Odour Solvent.

Odour threshold No information available.

pH No information available.Melting point No information available.

Initial boiling point and range -41 (-41 TO 95)°C @

Flash point -40°C Closed cup.

Evaporation rate

No information available.

Evaporation factor

No information available.

Flammability (solid, gas)

No information available.

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 1.0 % Upper flammable/explosive limit: 13.0 %

Vapour pressureNo information available.Vapour densityNo information available.

Relative density 0.654

Solubility(ies) Insoluble in water.

Partition coefficient No information available.

Auto-ignition temperature 413°C

Decomposition TemperatureNo information available.ViscosityNo information available.Explosive propertiesNo information available.Oxidising propertiesNo information available.

9.2. Other information

Other information None.

#### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity**No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability The product may not be stable under some conditions of storage or use.

#### 10.3. Possibility of hazardous reactions

Possibility of hazardous

None known.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high

temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid None known.

10.6. Hazardous decomposition products

Hazardous decomposition None

products

None at ambient temperatures.

# **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Inhalation Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness

and nausea.

**Skin contact** Causes skin irritation.

**Eye contact** Causes serious eye irritation.

Acute and chronic health

hazards

No known chronic or acute health risks.

Route of exposure Inhalation Skin and/or eye contact

# Toxicological information on ingredients.

#### **ACETONE**

Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> 5,800.0

mg/kg)

**Species** Rat

**ATE oral (mg/kg)** 5,800.0

Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 7,800.0

mg/kg)

Species Rabbit

Revision date: 22/03/2019 Revision: 2 Supersedes date: 11/12/2014

# Indasa Abrasives UK Limited - Spray Adhesive 500ml Aerosols

**ATE dermal (mg/kg)** 7,800.0

Acute toxicity - inhalation

Acute toxicity inhalation

(LC<sub>50</sub> vapours mg/l)

21.0

**Species** Rat

ATE inhalation (vapours

21.0

mg/l)

## SECTION 12: Ecological information

#### 12.1. Toxicity

Ecological information on ingredients.

#### **ACETONE**

Acute aquatic toxicity

Acute toxicity - fish EC₅₀, 96 hours: 8300 mg/l, Lepomis macrochirus (Bluegill)

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, : 8800 mg/l, Daphnia magna

#### 12.2. Persistence and degradability

Persistence and degradability No data available.

#### 12.3. Bioaccumulative potential

Partition coefficient No information available.

12.4. Mobility in soil

**Mobility** No data available.

#### 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

Other adverse effects None known.

## SECTION 13: Disposal considerations

## 13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations Waste

codes should be assigned by the user, preferably in discussion with the waste disposal

authorities.

**Disposal methods**Containers should be thoroughly emptied before disposal because of the risk of an explosion.

Do not pierce or burn, even after use.

Waste class

The waste code classification is to be carried out according to the European Waste Catalogue

(EWC).

## **SECTION 14: Transport information**

#### 14.1. UN number

**UN No. (ADR/RID)** 1950

UN No. (IMDG) 1950 UN No. (ICAO) 1950 UN No. (ADN) 1950

#### 14.2. UN proper shipping name

Proper shipping name

AEROSOLS, FLAMMABLE

(ADR/RID)

Proper shipping name (IMDG) AEROSOLS, FLAMMABLE
Proper shipping name (ICAO) AEROSOLS, FLAMMABLE
Proper shipping name (ADN) AEROSOLS, FLAMMABLE

2.1

#### 14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

#### Transport labels



**ADN class** 

# 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



## 14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

#### SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

#### **EU legislation** Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Council Directive of 20 May 1975 on the approximation of the laws of the Member States

relating to aerosol dispensers (75/324/EEC) (as amended).

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on

waste

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### SECTION 16: Other information

Revision date 22/03/2019

Revision 2

Supersedes date 11/12/2014

SDS number 5181

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H229 Pressurised container: may burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.