



## High Build Primer Aerosol

High Build Primer has been specially designed for application to a wide range of substrates. It has been specially formulated to be compatible with all commonly used automotive finishes including the very latest water-based coatings. It offers excellent opacity and contains advanced anti-corrosive pigmentation giving increased protection. It is quick drying with excellent adhesion and can easily be applied to clean, dry, abraded surfaces, producing a film thickness equivalent to that of a spray gun applied primer.

Part No.	Description	Size
472934	High Build Primer Grey Aerosol	500ml
472927	High Build Primer Dk Grey Aerosol	500ml
472941	High Build Primer White Aerosol	500ml

### ADDITIONAL INFORMATION

#### APPLICATION

Ensure all surfaces to be applied are clean, dry and rust free.

Abrade area with 280 or 320# disc.

Shake Aerosol can for 2 - 3 minutes.

Apply 1 - 2 light even coats.

Allow 5 - 10 minutes flash off time between coats.

Allow 20 minutes before over coating.

Drying time is dependent on film thickness.

High build primer should be dry sanded with 400# disc.

Basis	Acrylic
Chromates	Chromate free
VOC	303 grms per 500ml can
Storage	Store in a dry and cool place
Shelf Life	Min:18 months

**infra red  
compatible**

**variety of  
colours available**

**non clog nozzle**



**INDASA**

**INDASA Abrasives (UK) Ltd**  
Viking Works, Greenstead Rd,  
Colchester, CO1 2ST  
Tel: 01206 870366  
Fax: 01206 860525  
Email: office@indasa.co.uk