



EXTERIOR EXTRA DURABLE WOOD STAIN

Product Description	A UV stable weather resistant wood stain, containing a unique blend of silicone & urethane resins. Provides a durable hard wearing coating that offers long lasting wood protection on exterior timber.			
Recommended Uses	Formulated for exterior use with carefully selected resins on new or bare timber and suitably prepared timber. Used as a finish coat on exterior doors, soffits, facias and most exterior timber surfaces.			
VOC Content & Compliance	399 + 20 g/litre 2004/42/EC (2010)* sub-category (e) - VOC level below 400 g/l.			
Finish	Satin			
Volume Solids	50 ± 2% - Varies with colour			
Pack Sizes Available	1L, 2.5L, 5L.			
Film Thickness & Coverage		Dry Film Thickness	Wet Film Thickness	Theoretical Coverage
	Minimum	40 µm	80 µm	12.5 m ² /litre
	Actual coverage varies considerably with factors including surface porosity, roughness, application methods and conditions.			
Minimum Application Temperature	Air temperature 15°C		Substrate temperature 10°C	
Drying & Overcoating Times	Applied to 30 microns DFT	+10°C	+20°C	+30°C
	Touch Dry	8 hr	3 hr	2 hr
	Hard Dry	48 hr	24 hr	24 hr
	Full Hardness	Minimum	7 Days	5 Days
	Overcoating	Maximum	24 hr	16 hr
	Drying and re-coating times are related to the film thickness, temperature, the relative humidity of the air and ventilation.			
Colour Range	15 Ready mixed colours. Tintable to Colorgrain system			
Product Code	EWSNCS1L - EWSNCS2.5L - EWSNCS5L			
Specific Gravity	0.85 – 0.98 kg/lit varies with colour			
Storage Conditions	Between 15°C - 25°C for at least 12 hours prior to use. Do not allow to freeze.			
Shelf Life	Minimum 2 years if stored as above in unopened containers			
Flash Point	Above 38°C (closed cup)			
Surface Preparation	On previously painted surfaces, ensure it is sound and non-flaking. Abrade the surface removing all previous coatings, preferably by mechanical abrasion to provide a “key” and maximise adhesion of the subsequent coating. For surfaces that have been exposed to weathering clean with a mould and mildew remover. If any signs of insect wood boring or rot has occurred use, remove and replace severely affected areas with a high performance wood filler and then treat with a woodworm killer treatment.			
Typical Viscosity	4 - Poise @ 25 °C			



EXTERIOR EXTRA DURABLE WOOD STAIN

Mixing	Stir the paint with a drill stirrer or wooden baton at least 2" wide. Continue to stir during application to avoid settling of the product.				
Thinner	White Spirit		Equipment Cleaner: White Spirit		
Application	Apply by brush, solvent resistant roller or spray. Use a paint brush for cutting in if applicable. Avoid applying the paint too thickly to avoid delaying drying times. If the substrate is porous, thin the first coat with 10% White Spirit. The second and subsequent coats can be applied as soon as the first / preceding coat is dry usually after 6-12 hours, and should be applied within 5 days. If more than 5 days elapse, the previous coat should be lightly abraded before the second coat is applied.				
Preceding Coat	For best results on new or weathered bare timber, treat with a solvent based clear wood preservative applied as per the manufacturers guidance.				
Subsequent Coat	Recommended 2-3 coats				
Application Methods	Method	Airless Spray	Conventional Spray	Brush	Roller
		Yes	Yes	Yes	Yes
	<ul style="list-style-type: none"> • Airless Spray: Tip size range: .009 - .011. Gun filter: Red (Very Fine). Always spray at the lowest possible pressure which will give a good spray pattern. • Application by brush can achieve up to 80 microns dft. • When applying by roller, use a solvent resistant sleeve. • Avoid excessive film thickness as this will cause the product to run onto other surfaces and potentially cause through-drying problems. 				
Product Notes	As dictated by normal good painting practice. Care must be taken during application that the temperature is above the dew point to avoid any contamination. In confined spaces, provide adequate ventilation during application and drying. You may need to use a smaller tip in warm weather, as the paint will be thinner. Equally you may need to use a larger tip in cold weather.				
Health & Safety	Containers are provided with safety labels which should be observed. Further information about hazardous influences and protection are detailed in individual Product Safety Data Sheets. A Safety Data Sheet for this product is available on request from				

The information given on this sheet is, to the best of our knowledge, true and accurate. No guarantee of the results implied, or any loss or damage arising out of this material, however, are possible as the conditions of application are beyond our control. This is notwithstanding any liability arising from the Consumer Protection Act 1987 and the Health & Safety at Work Act. Health and Safety data is available on this product and should be referred to prior to its use



Palatine Paints & Chemicals Limited
55 Smallbrook Lane
Leigh
Lancashire
WN7 5PZ
TEL: 01942 884122
sales@palatinepaints.co.uk