

MATERIAL SAFETY DATA SHEET Part 1 Proplas 2K PU

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name

PROXL 2K PU REPAIR

Chemical name and synonym

Polyurethane 2K Adhesive technology

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Polyurethene based adhesive.

1.3. Details of the supplier of the safety data sheet

Full address
District and Country

Capella Solutions Group Second Avenue Chatham, ME4 5AU United Kingdom Tel. +44(0)1634 823900

e-mail address of the competent person

responsible for the Safety Data Sheet

Product distribution by

sales@capellasolutionsgroup.com

1.4. Emergency telephone number

For urgent inquiries refer to

Tel. +44(0)1634 823900

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2

H319

Causes serious eye irritation.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



Signal words:

Warning

Hazard statements:



H319 Causes serious eye irritation.

Precautionary statements:

P264Wash . . . thoroughly after handling.P280Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing

P337+P313 If eye irritation persists: Get medical advice / attention.

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.1. Substances.

Information not relevant.

3.2. Mixtures.

Contains:

Identification. Conc. %. Classification 1272/2008

(CLP).

1,1',1"',1"'-Ethylene nitrile tetra propan-2-ol

CAS. 102-60-3 20 - 50 Eye Irrit. 2 H319

EC. 203-041-4 INDEX. -

Reg. no. 01-2119552434-41-0001

Glyseryl poly (ossipropylene) triamine

CAS. 64852-22-8 1 - 3 Eye Dam. 1 H318, Skin Irrit. 2

H315, Aquatic Chronic 3

H412

EC. -INDEX. -

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.



4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.



6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use.

7.2. Conditions for safe storage, including any incompatibilities.

Keep the product in clearly labelled containers. Keep containers away from any incompatible materials, see section 10 for details.

Keep containers tightly close in a cool, dry place. Protect from temperatures over 70° c. The properties of the product change irreversably when this temperature is exceeded.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

| 1,1',1"',1"'-Ethylenedinit | | ol | | | | | | |
|--|------------------------|----------------|---|------------------|------------------------|-------------------|---------------|------------------|
| Normal value in fresh water Normal value in marine water Normal value for fresh water sediment Normal value for marine water sediment Normal value for water, intermittent release Normal value of STP microorganisms Normal value for the terrestrial compartment | | | 0,085 mg/l 0,0085 mg/l 0,193 mg/k 0,0193 mg/k 1,51 mg/l 70 mg/l 0,0183 mg/k | | g | | | |
| Health - Derived no-effect level - DNEL / DMEL Effects on Effects on | | | | | | | | |
| Route of exposure | consumers. Acute local | Acute systemic | Chronic local | Chronic systemic | workers Acute local | Acute systemic | Chronic local | Chronic systemic |



MATERIAL SAFETY DATA SHEET

Proplas 2K PU

Oral. VND 2,5 mg/kg/d

 Inhalation.
 VND
 8,7 mg/m3
 VND
 29,4 mg/m3

 Skin.
 VND
 2,5 mg/kg/d
 VND
 4,2 mg/kg/d

Legend:

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance liquid black Colour Odour Not available. Odour threshold. Not available. Not available. Melting point / freezing point. Not available. > 200 °C. Initial boiling point. Boiling range. Not available. Flash point. 182 °C. **Evaporation Rate** Not available Flammability of solids and gases Not available.



Lower inflammability limit. Not available. Upper inflammability limit. Not available. Lower explosive limit. Not available. Upper explosive limit. Not available. Vapour pressure. 0,1 Pa Vapour density Relative density. Not available. 0,980 Kg/l Solubility Not available. Partition coefficient: n-octanol/water Not available. Not available. Auto-ignition temperature. Decomposition temperature. Not available. Viscosity 3500 mPas Explosive properties Not available. Oxidising properties Not available.

9.2. Other information.

VOC (Directive 2010/75/EC): 0 VOC (volatile carbon): 0

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials.

Materials to avoid: strong acids, strong oxidizing agents, reactive products.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.



11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Glicerilpoli(ossipropilen)triammina LD50 (Oral).2690 mg/kg LD50 (Dermal).12500 mg/kg

SECTION 12. Ecological information.

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

| harmful effects on aquifers. | | | |
|------------------------------|--|--|--|
| 12.1. Toxicity. | | | |
| | | | |
| | | | |

Glicerilpoli(ossipropilen)triam mina LC50 - for Fish. 68 mg/l/96h

12.2. Persistence and degradability.

Information not available.

12.3. Bioaccumulative potential.

Information not available.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.



13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

| SECTION 14. Transport information. |
|--|
| 14.1. UN number. |
| Not applicable. |
| 14.2. UN proper shipping name. |
| Not applicable. |
| 14.3. Transport hazard class(es). |
| Not applicable. |
| 14.4. Packing group. |
| Not applicable. |
| 14.5. Environmental hazards. |
| Not applicable. |
| 14.6. Special precautions for user. |
| Not applicable. |
| 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code. |
| Information not relevant. |
| SECTION 15. Regulatory information. |



| 15.1. Safety, health and env | vironmental regulation | ns/legislation specific for the substance or mixture. | |
|-----------------------------------|---------------------------|---|--|
| Service category. | None. | | |
| Restrictions relating to the proc | duct or contained substa | ances pursuant to Annex XVII to EC Regulation 1907/2006. | |
| Product. Point. | 3 | | |
| Contained substance. | | | |
| Point. | 20 | dibutilbis(dodecilitio)s tannano Reg. no.: 01- 2119841260-50-0000 | |
| Substances in Candidate List (| Art. 59 REACH). | | |
| None. | | | |
| Substances subject to authoris | arion (Annex XIV REAC | <u>CH).</u> | |
| None. | | | |
| Substances subject to exportat | tion reporting pursuant t | to (EC) Reg. 649/2012: | |
| None. | | | |
| Substances subject to the Rott | erdam Convention: | | |
| lone. | | | |
| Substances subject to the Stoo | kholm Convention: | | |
| None. | | | |
| lealthcare controls. | | | |

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

workers' health and safety are modest and that the 98/24/EC directive is respected.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Eye Dam. 1 Serious eye damage, category 1

Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2



MATERIAL SAFETY DATA SHEET

Proplas 2K PU

Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H318 Causes serious eye damage.H319 Causes serious eye irritation.

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008 - DNEL: Derived No Effect Level
- DNEL: Derived No Effect Leve - EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

