

PAINTS, PRIMERS AND SPECIALISED COATINGS

SAFETY DATA SHEET

138/W224 - GUARD-COAT HARDENER FOR GREEN

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 138/W224 - GUARD-COAT HARDENER FOR GREEN

Product number 138/W224/15 - hardener for green

UK

UFI UFI: VFVP-72V7-0000-75K5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses HARDENER FOR TWO COMPONENT FLOOR COATING

1.3. Details of the supplier of the safety data sheet

Supplier COO-VAR TEAL & MACKRILL EU B.V.

> **Queens Towers** Lockwood Street Hull Deflandlaan 1 HU2 0HN 1062 EA Amsterdam

The Netherlands +441482328053 (T) +31 (0)208 004828 (T) +441482219266 (F) +441482219266 (F) info@coo-var.co.uk info@coo-var.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 328053 Coo-Var (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SDS No. 11276

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Eye Dam. 1 - H318

Environmental hazards Not Classified

Human health The product contains a small amount of sensitising substance. May cause skin sensitisation

or allergic reactions in sensitive individuals.

Physicochemical When handled correctly, undamaged units represent no danger.

2.2. Label elements

138/W224 - GUARD-COAT HARDENER FOR GREEN

Hazard pictograms



Signal word Danger

Hazard statements H318 Causes serious eye damage. **Precautionary statements** P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P313 Get medical advice/ attention.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/ container in accordance with national regulations.

Contains Teta, polymer with Bisphenol A diglycidyl Ether, Formaldehyde, MXDA, sulphamic acid and

Ethoxylated nonyl Phenol

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Teta, polymer with Bisphenol A diglycidyl Ether,

10-30%

Formaldehyde, MXDA, sulphamic acid and Ethoxylated nonyl

Phenol

CAS number: 238080-05-2

Classification Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 4 - H302 Xn;R22. Xi;R41.

Eye Dam. 1 - H318

Chromic Oxide 10-30%

CAS number: 1308-38-9 EC number: 215-160-9 REACH registration number: 01-

211943395-39-xxxx

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified

138/W224 - GUARD-COAT HARDENER FOR GREEN

Barium Sulphate 1-5%

CAS number: 7727-43-7 EC number: 231-784-4 REACH registration number: 01-

2119491274-35-0001

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified -

Calcium Magnesium Silicate 1-5%

Classification (67/548/EEC or 1999/45/EC)

Not Classified -

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Remove affected person from source of contamination. Get medical attention if any discomfort

continues.

Ingestion Rinse mouth thoroughly with water. Do not induce vomiting. If vomiting occurs, the head

should be kept low so that stomach vomit doesn't enter the lungs. Give plenty of water to

drink. Get medical attention immediately.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical

attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of

water. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue

to rinse.

4.2. Most important symptoms and effects, both acute and delayed

Ingestion Harmful if swallowed.

Eye contact Causes serious eye damage. May cause permanent damage if eye is not immediately

irrigated.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or

vapours.

5.3. Advice for firefighters

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

138/W224 - GUARD-COAT HARDENER FOR GREEN

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of

vapours and contact with skin and eyes. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Spillages or uncontrolled

discharges into watercourses must be reported immediately to the Environmental Agency or

other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Absorb with inert, damp, non-combustible material, then flush area with water. Collect and

place in suitable waste disposal containers and seal securely. For waste disposal, see Section

13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid inhalation of vapours/spray and contact with skin and eyes. Provide adequate

ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Chromic Oxide

Long-term exposure limit (8-hour TWA): 0.5 mg/m³

Barium Sulphate

Long-term exposure limit (8-hour TWA): 10 mg/m³ inhalable dust Long-term exposure limit (8-hour TWA): 4 mg/m³ respirable dust

Calcium Magnesium Silicate

Long-term exposure limit (8-hour TWA): WEL 1 mg/m³

WEL = Workplace Exposure Limit.

Ingredient comments No exposure limits known for ingredient(s).

Chromic Oxide (CAS: 1308-38-9)

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

138/W224 - GUARD-COAT HARDENER FOR GREEN

Protective equipment







Appropriate engineering controls

Provide adequate ventilation. Mechanical ventilation or local exhaust ventilation may be required. Ensure operatives are trained to minimise exposure.

Personal protection

Unprotected persons should be kept away from treated areas.

Eye/face protection

The following protection should be worn: Wear eye protection. Tight-fitting safety glasses. Full face visor or shield. Workers should not contact their eyes or skin with hands contaminated with the material.

Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturers' performance data suggest that the optimum glove for use should be: Nitrile rubber. Thickness: ≥ 0.3 mm Neoprene. Thickness: ≥ 0.4 mm or Butyl rubber. Thickness: ≥ 0.3 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Viscous liquid. Liquid

Colour Yellowish
Odour Ammonia.

Odour threshold Not determined.

pH pH (concentrated solution): 8.9

Initial boiling point and range >100°C @ 760 mm Hg

Flash point °C Does not flash.

Evaporation rate Not determined.

Evaporation factor Not determined.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or

explosive limits

Data lacking.

Other flammability Not applicable.

138/W224 - GUARD-COAT HARDENER FOR GREEN

Vapour density Not determined.

Relative density 1.27 @ @ 20 C°C

Solubility(ies) Soluble in water.

Auto-ignition temperature Not determined.

Decomposition Temperature Not determined.

Viscosity > 20.5 mm²/s.

Explosive properties Not applicable.

Oxidising properties Data lacking.

9.2. Other information

Other information No information required.

Volatile organic compound EU: (cat A/j): 140 g/l 2010. This product contains a maximum VOC content of <1 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

products

The following materials may react violently with the product: Peroxides.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Acids. sodium hypochlorite Peroxides.

10.6. Hazardous decomposition products

Hazardous decomposition

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or

vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 2,279.48

Skin corrosion/irritation

Animal data Data lacking.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye damage.

Respiratory sensitisation

Respiratory sensitisation Data lacking.

Skin sensitisation

Skin sensitisation Data lacking.

138/W224 - GUARD-COAT HARDENER FOR GREEN

Germ cell mutagenicity

Genotoxicity - in vitro Data lacking.

Carcinogenicity

Carcinogenicity Data lacking.

Reproductive toxicity

Reproductive toxicity - fertility Data lacking.

Specific target organ toxicity - single exposure

STOT - single exposure

Data lacking.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure

Data lacking.

Aspiration hazard

Aspiration hazardBased on available data the classification criteria are not met.

Inhalation Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following

overexposure may include the following: Coughing.

Ingestion Irritating. Symptoms following overexposure may include the following: Nausea, vomiting.

Stomach pain.

Skin contact Irritating to skin. May cause sensitisation or allergic reactions in sensitive individuals.

Eye contact Risk of serious damage to eyes. Irritating to eyes. Symptoms following overexposure may

include the following: Redness. Pain.

Route of exposure Inhalation Skin absorption. Ingestion. Skin and/or eye contact.

Toxicological information on ingredients.

3-(Polyoxyethylene)propylheptamethyltrisiloxane

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 5,050.0

mg/kg)

Species Rat

ATE oral (mg/kg) 5,050.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,050.0

mg/kg)

Species Rabbit

ATE dermal (mg/kg) 2,050.0

Acute toxicity - inhalation

Acute toxicity inhalation

5,921.05

14.47

(LC₅ gases ppmV)

Species Rat

Acute toxicity inhalation

(LC50 vapours mg/l)

138/W224 - GUARD-COAT HARDENER FOR GREEN

Species Rat

Acute toxicity inhalation 1.97

(LC50 dust/mist mg/l)

Species Rat

ATE inhalation (gases

ppm)

5,921.05

ATE inhalation (vapours

mg/l)

14.47

1.97

ATE inhalation

(dusts/mists mg/l)

SECTION 12: Ecological information

Ecotoxicity The product components are not classified as environmentally hazardous. However, this does

not exclude the possibility that large or frequent spills can have a harmful or damaging effect

on the environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish No information available.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Do not puncture or incinerate even when empty.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

Waste class Used containers, drained and/or rigorously scraped out and containing dry residues of the

> supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging). Wear protective clothing during disposal operations. If disposal is by waste contractor, make sure that he has sufficient information and that waste containers are properly labelled. Ideally this component should be mixed with

> the appropriate resin base and allowed to react fully producing a solid non hazardous waste.

SECTION 14: Transport information

138/W224 - GUARD-COAT HARDENER FOR GREEN

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

138/W224 - GUARD-COAT HARDENER FOR GREEN

Abbreviations and acronyms used in the safety data sheet

ATE: Acute Toxicity Estimate.
CAS: Chemical Abstracts Service.

DNEL: Derived No Effect Level.
GHS: Globally Harmonized System.

ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

LD₅o: Lethal Dose to 50% of a test population (Median Lethal Dose).

PBT: Persistent, Bioaccumulative and Toxic substance.

PNEC: Predicted No Effect Concentration.

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

(EC) No 1907/2006.

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

SVHC: Substances of Very High Concern. vPvB: Very Persistent and Very Bioaccumulative. EC₅₀: 50% of maximal Effective Concentration.

Classification abbreviations and acronyms

Acute Tox. = Acute toxicity

Aquatic Acute = Hazardous to the aquatic environment (acute)

Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Eye Dam. = Serious eye damage

Eye Irrit. = Eye irritation

Resp. Sens. = Respiratory sensitisation

Repr. = Reproductive toxicity Skin Corr. = Skin corrosion Skin Sens. = Skin sensitisation

STOT RE = Specific target organ toxicity-repeated exposure STOT SE = Specific target organ toxicity-single exposure

Revision comments

Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Addition of EU supplier information Unique Formula Identifier (UFI) added

Issued by Technical Dept. (N.O.)

Revision date 11/11/2021

Revision 5.0

Supersedes date 16/11/2018

SDS number 11276

SDS status Approved.

Hazard statements in full H302 Harmful if swallowed.

H318 Causes serious eye damage.

Signature Initials

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.