



PALATINE PAINTS



PRODUCT GUIDE

Protected by Performance

www.palatinepaints.co.uk

Welcome to our World of Manufacturing Excellence

At Palatine Paints, we pride ourselves on our rich heritage and unwavering commitment to manufacturing excellence. As a SME enterprise, we have carved out a niche foothold in the paint manufacturing industry, delivering high-quality products and exceptional service to our customers. Our journey began in the 1940s with the establishment of our first manufacturing facility in Leigh, Lancashire. Over the decades, we have evolved and expanded, embracing innovation and sustainability while maintaining our core values of quality and customer satisfaction.

Expertise in Paint Manufacturing

Our expertise in paint manufacturing is built on a foundation of extensive experience and a deep understanding of the industry. We specialise in producing a wide range of paints and coatings, including industrial, decorative, and maintenance coatings. Our product portfolio includes everything from high-performance paints and primers to specialised coatings for specific applications. Each product is meticulously formulated to meet the highest standards of performance, durability, and environmental safety.

Innovation and Quality Control

Innovation is at the heart of our manufacturing process. We invest heavily in research and development to stay ahead of industry trends and meet the evolving needs of our customers. Our team of in-house chemists works tirelessly to develop new formulations and improve existing products. We leverage advanced technologies and state-of-the-art equipment to ensure that our paints and coatings deliver superior performance and reliability.

Quality control is a critical aspect of our manufacturing process. We adhere to stringent quality assurance protocols at every stage of production, from raw material selection to final product testing. Our commitment to quality is reflected in our ISO 9001 certification, which underscores our dedication to maintaining the highest standards of manufacturing excellence.

Sustainability and Environmental Responsibility.

At Palatine Paints, we recognise the importance of sustainability and environmental responsibility. We are committed to minimising our environmental footprint through sustainable manufacturing practices and the development of eco-friendly products. Our efforts include the use of low-VOC (volatile organic compounds) formulations, recycling initiatives, and energy-efficient production processes. We continuously seek ways to reduce waste, conserve resources, and promote a greener future for our industry.

Customer-Centric Approach

Our customers are at the centre of everything we do. We take pride in building long-lasting relationships with our clients, understanding their unique needs, and providing tailored solutions. Our customer-centric approach extends beyond product quality to include exceptional service and support. We offer technical assistance, product training, and after-sales service to ensure that our customers achieve the best possible results with our products.

Community Engagement and Social Responsibility

As a conscientious business, we are deeply rooted in our local community. We believe in giving back and supporting the communities where we operate. Our social responsibility initiatives include charitable contributions, community outreach programs, and support for local schools and organizations. We are committed to making a positive impact and fostering a sense of community and shared purpose.

Contents

Fire Protection 76-80	Primer & Undercoat
	Anti Rust Primer43
Floors & Walls	• Etching44
Floor Paint4-5	Oil Based Undercoat45
 Epoxy Floor Paint5-6 	Multi Surface Primer45
Floor Preparation7	Rust Inhibiting44
 Floor Repairs7 	Water Based Undercoat 15
 Linemarking8 	Wood Primer47
Special Use8-9	Wall Primer46
 Anti Slip 9-11 	
 Masonry / Wall11-13 	Special Use
• • • • • •	Aerosol-Home48-49
Home & Outdoor	Aerosol-Primer 49-51
Home Interior14-19	Aerosol-Topcoat 51-54
• Emulsion20-22	Aerosol-Varnish54
Heritage22	Anti Condensation55
Home Exterior23-26	Multi Surface Paint56
• Garden27-28	Thermal Insulating57
_ lu di catulul	Hygiene Coatings57
Industrial 20, 20	Safety & Security 58
Agricultural	
01 02	Solvents & Chemicals
Plant & Machinery33 Water Proofing 33 34	Cleaners / Degreasers 61-63
Water Proofing	• Thinners59-60
• Roof Coating 35-36	• Chemicals
Marine	• De-Icer67
Primer & Undercoat	Vehicle Refinishing
Bilge Paint37	• Topcoats 68-69
• Topcoats38	• Aerosols 68-70
Hull Blacking39	Aerosois0070
Anti Slip Paint39	Wood Care
• Varnish39-40	Knotting Solution74
Paint Removal 40	Polishes & Shellacs 74
T diffe Koffio Val	Wood Lacquer74
Preparation & Accessories	• Wood Oil
• Brushes	Wood Preserver
Extension Poles41	Wood Treatments
• Frames41	Wood Varnish
 Preparation & Sundries 42 	70
Roller Sleeves42	
Trays & Scuttles42	
Paint Removal 43	
Rust Treatment43	



Paint Colour Matching Service

You are able to choose from the below colour charts: British Standard (BS 4800 & BS 381C),

RAL Classic,

NCS 2050 colour charts alongside other manufacturer colours. Please feel free to contact us for more information





Carbotread Polyurethane Floor Paint

A hard-wearing, single-pack floor paint, it provides a tough, durable, and easy-to-clean finish, ideal for internal floors. Perfect for warehouses, commercial, and domestic agrages, this floor paint offers high performance and visual appeal.

Suitable Substrates: Mature Concrete - Wood - Metal



Size: 2.5L 5L 20L

Drying Times: Touch 3hr Hard (Overcoat (24hr)

Application Coverage: (12-14m²/L Method







Carbotread Exterior Floor Paint

A polyurethane floor coating designed for use on outdoor surfaces. Provides a durable satin finish to the floor that is resistant to the effects of weather and sunlight. The paint also protects the floor from long term wear caused by everyday foot traffic.

Suitable Substrates: Mature Concrete - Wood - Metal

Colours:

R MG ADG DG LBG MBL TINT

Satin Finish:

1L 2.5L 5L Size:

3hr 8hr Overcoat (24hr) **Drying Times:** Touch

Coverage: (12-14m²/L Method

Application





Garage Floor Paint

An oil based floor coating, which offers durability and a highperformance finish. Making it ideal for both commercial and residential use. Perfect for protecting and enhancing your garage floors and ensuring long-lasting protection and easy maintenance

Suitable Substrates: Mature Concrete - Metal

Colours: В W LG MG ADG DG LBG MBL TR TINT

Finish: Gloss

2.5L 5L 20L Size:

3hr 8hr Overcoat (24hr **Drying Times:** Touch (Hard (

Coverage: (12-14m²/L





Floor Paint for Wood

An alkyd paint designed for use on wooden floors. It provides a decorative satin finish to the floor while protecting it from the everyday wear of foot traffic. A resin rich coating, suitable for both indoor and outdoor use

Suitable Substrates: Bare Wood - Floor boards - Hardwood



Size: (1L) (2.5L) (5L)

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: 12-14m²/L

Application Method





Polyurethane Floor Varnish

Achieve a hard, protective, finish with our polyurethane floor varnish. Easy to apply, it's perfect for coating, touch-ups, and restoration projects. Providing a tough, durable finish ideal for med - high traffic areas.

Suitable Substrates: Bare Wood - Floor boards - Hardwood



Finish: Gloss Satin

Size: (2.5L) (5L)

Drying Times: Touch 3hr Hard 12hr Overcoat 24hr

Coverage: 13-14m²/L Application Method







Two Pack Epoxy Floor Primer

Designed for concrete and exposed steel reinforcement before applying epoxy floor paint. It offers excellent adhesion, low viscosity for easy application, and great penetration properties. With low odour, it's ideal for food factories, creating a durable base for epoxy floor paint.

Suitable Substrates: Concrete - Steel

Colours:

LG MG DG TR

TINT

Finish: Satin

Size: (5kg) (11kg) Curing Type: (Standard) (Fast

Traffic Times (Hrs): Light 10-12 Full 24-48 Full Cure 7days

Coverage: 25m²/5kg





PALATINE PAINTS

DAMP PROOF MEMBRANE

(DPM)

Two Pack Epoxy Floor Paint

Durable, high-performance coating for industrial and commercial floors. It offers hygienic, easy-to-clean surfaces with good chemical and abrasion resistance. Withstands mid - heavy traffic. Ideal for laboratories, factories, showrooms, schools, and food processing areas.

Suitable Substrates: Concrete - Steel

MG

Colours:

TR DG

TINT

Finish: Satin

5kg Size: 11kg

LG

Curing Type: (Standard)

Fast Full Cure (7days)

Traffic Times (Hrs):

Light (10-12)

Full 24-48



Application Method





Suitable Substrates: Mature Concrete - Wood - Metal

Colours:



Finish: Matt

Size:

5kg 11kg

Light (10-12

Full (24-48)

Full Cure (7days)

Coverage: (1m²/0.25kg)

Traffic Times (Hrs):

Application Method







Two Pack Epoxy Dust Sealer

A two pack dust sealer for new and old concrete floors. It is ideal for use in areas such as warehouse and production floors, where dust can quickly build up. It prevents the dust from becoming difficult to remove, allowing fore a cleaner and safer working area.

Suitable Substrates: Mature Concrete - Wood - Metal

Colours:

CL

Matt

Finish: Gloss

(20kg) Curing Type: (Standard) 5kg Size:

Traffic Times (Hrs): Full (24-48) Full Cure 7days Light (10-12

Coverage: 1m²/0.15kg







Acid Etch for Concrete

Acid Etch for Floors is a solution that prepares floors for painting fresh concrete that is less than six months old. Surface alkalinity needs to be neutralised by etching. This is down to the fact that high alkalinity is not ideal for single pack alkyd based paints, surface.

Size:

5L)

25L

Features & Uses:

Main purpose is to remove surface laitance, (which is a fine layer that forms after the floor cures).

Creates a porous substrate better known as a "key" for the paint to fully adhere to the floor that does not easily peel away from the surface.



Epoxy Concrete Patch Repair System

Ideal for repairing worn, cracked, and damaged concrete. It offers good abrasion and chemical resistance and comes in pre-weighed packs. Provides a non-skid, abrasive-resistant surface and resists dilute acids, petrol, oil, and grease

Suitable Substrates: Concrete

Colours:

G

Finish: Matt

Size: (5kg) (11kg)

Traffic Times (Hrs): Light 10-12 Full 24-48 Full Cure 7days

Coverage: (1m²/11.50kg)

Application Method







<u>Coldcrete Epoxy Patch Repair System</u>

Epoxy Patch Repair System for use in the repair of worn and damaged concrete where a high strength repair material is required in cold store areas as low as – 40 °C or when temperatures do not permit the use of Epoxy Concrete Patch Repair System.

Suitable Substrates: Mature Concrete - Wood - Metal

Colours:



Finish: Matt

Size: (5kg) (11kg)
Traffic Times (Hrs):

Light 10-12 Full 24-48

Full Cure 7days

Coverage: (1m²/11.50kg







Carboline Road Line Paint

A fast-drying paint known for its exceptional durability. Ideal for marking walkways, safety routes, parking bays, and restricted zones. Easy to apply when marking out walkways, safety routes, parking bays, or restricted areas

Suitable Substrates: Mature Concrete - Steel - Road Surfaces

Colours:

В

Finish: Gloss

2.5L Size: 5L

Drying Times: Touch (15min) Hard (30min) Overcoat (

Coverage: (12-14m²/L

Application Method



Line Marking Solutions

Linemarking spray, applicators and stencils provide precise, durable markings for sports fields, parking lots, and industrial areas. Easy to use, they ensure clear, long-lasting lines with quickdrying, weather-resistant paint.











Epoxytread Single Pack Floor Paint

Ideal for various industrial applications. It offers good adhesion and flexibility, with improved resistance to water, chemicals, oils, and greases. Suitable for interior and exterior concrete and light to medium foot and wheeled traffic.

Suitable Substrates: Mature Concrete - Wood - Metal

Colours:

В LG MG ADG SR TR MBL SY TINT

Finish: Gloss

5L Size:

Overcoat (24hr **Drying Times:** 3hr Hard (8hr Touch (

Coverage: (12-14m²/L **Application** Method







Carbotread Floor Sealer

A concrete floor sealer that protects and enhances concrete surfaces by sealing out moisture, stains, and chemicals. It provides a durable, finish that resists wear and tear, making it ideal for areas with light to mid traffic. Extends the life of your concrete floors.

Suitable Substrates: Cured Mature Concrete

Colours:

Finish: (Low Sheen)

Size: 2.5L

Touch 3hr Hard (8hr Overcoat (24hr) **Drying Times:**

Coverage: 12-14m²/L

Application Method







Chlorinated Rubber Floor Paint

20L

A versatile rubberised coating for indoor and outdoor use, perfect for garage and production area floors. It offers resistance to water, chemicals, fungal growth, and atmospheric pollution, ensuring a durable finish for industrial and agricultural environments.

Suitable Substrates: Concrete - Steel - Road Surfaces

Colours:

R Gloss Finish:

5L Size:

2hr **Drying Times:** Touch

8hr Hard (

MG ADG DGR WG MBL

Overcoat (24hr)

TINT

TR

Coverage: (12-14m²/L

Application Method







Anti-Slip Floor Paint for Wood

An anti slip equivalent to our smooth <u>floor paint for wood</u>. It provides a non slip satin finish to the floor while protecting it from the general wear of foot traffic, such as scuffs and scratches. This paint is ideal for use in areas where safety is a main concern, such as outdoor or workshops.

Suitable Substrates: Wood

Colours:













Finish: Satin

1L Size:

Drying Times:





Overcoat (24hr

Coverage: (12-14m²/L







Carbogrip Exterior Anti-Slip

A polyurethane floor paint for exterior surfaces. It provides a durable satin finish resistant to weather and sunlight, protecting against longterm wear from foot traffic. This anti-slip floor paint offers extra grip on wet, slippery surfaces, ideal for areas exposed to rain

Suitable Substrates: Mature Concrete - Wood - Metal

Colours:

В MG ADG DG LBG MBL TR SY TINT LG

Finish: Satin

Size: 1L 2.5L 5L

Drying Times: Touch 3hr Hard (Overcoat (24hr)

Coverage: (12-14m²/L

Application Method







Carbogrip Polyurethane Anti-Slip

An anti slip equivalent to Carbotread Floor Paint. It is a hard wearing, single pack floor paint. Provides a tough, durable finish with anti slip properties and is a great, high performance, choice for internal floors. A visually appealing, hard wearing and easy to clean floor paint.

Suitable Substrates: Mature Concrete - Wood - Metal

Colours:

R MG ADG DGR LBG MBL

Finish: Gloss

2.5L 5L 20L Size:

3hr Overcoat (24hr) **Drying Times:** Touch 8hr

Application Coverage: (12-14m²/L Method





TINT



Chlorinated Rubber Anti Slip

An anti slip rubberised coating designed for painting areas where hygiene is essential, such as livestock areas, kennels and stables. Easy to clean with a hose or jet wash. Providing a durable finish suitable for industrial and agricultural environments.

Suitable Substrates: Mature Concrete - Metal

Colours:

В ۱۸/ LG MG ADG DGR WG MBL TR TINT

Finish: Gloss

5L Size:

2hr 8hr Overcoat (24hr **Drying Times:** Touch (Hard (

Coverage: (12-14m²/L Application Method





Stepgrip Step & Ramp Paint

An anti-slip coating designed for use on steps, ramps and other walkway areas where slips are likely to occur. It is suitable for both indoor and outdoor use. Provides a hardwearing and durable finish, as well as leaving a surface that is safe in both wet and dry conditions.

Suitable Substrates: Mature Concrete - Wood - Metal



Finish: (Satin)

Size: (1L) (2.5L)

Drying Times: Touch (3hr) Hard (8hr) Overcoat (24hr)

Coverage: 12-14m²/L

Application Method





Pliocem Concrete & Masonry Sealer

A Pliolite based breathable clear sealer. Use as a sealer before applying subsequent coatings such as <u>Masonry Paint</u>, or <u>Floor Paint</u>. Use also as a stand alone concrete dust proofer to bind a concrete surface to help reduce dust.

Suitable Substrates: Cured Mature Concrete - Masonry

Colours:

CL

Finish: (Low Sheen)

Size: (2.5L) (5L) (25L)

Drying Times: Touch 6hr Hard 18hr Overcoat 24hr

Coverage: 8m²/L Application Method







<u>Pliocem Masonry Paint</u>

A solvent borne, exterior masonry paint designed for weather protection providing an attractive, decorative finish. Forms a tough, mould and dirt resistant film with superior weathering for outdoor use. Adheres well and acts as a barrier against water and CO2 attack.

Suitable Substrates: Concrete- Masonry

Colours:

B W AG SS CC SKG OG GS MS BR TINT

Finish: Matt

Size: (2.5L) (5L

Drying Times: Touch 2hr Hard 8hr Overcoat 24hr

Coverage: 8m²/L Application Method





Introducing StoneGuard ProSealer

The Ultimate Stone Sealer for Long-Lasting Protection & Beauty



Protect, Enhance, Preserve.

StoneGuard ProSealer is a 100% waterbased, durable, and transparent surface treatment designed to protect and enhance a wide range of building materials:

- Natural Stone
- Marble
- Terra Cotta
- Concrete
- Bricks & Block Paving

Why Choose StoneGuard ProSealer?

- Exceptional Water & Oil Repellence
- · Keeps surfaces safe from rain, cooking oils, and more.
- Powerful Anti-Stain Technology
- Resists stains from olive oil, coffee, ketchup, and food waste.
- Easy to Clean
- Dirt and spills wipe away effortlessly—no harsh chemicals needed.
- Anti-Graffiti Protection
- Ideal for public spaces and high-traffic areas.
- Fast Drying
- Dries in under 3 hours for quick and efficient application.
- Eco-Friendly
- 100% water-based formula—safe for you and the environment.

Product Details:

StoneGuard Stone Sealer, the ultimate solution for protecting and enhancing the beauty of your building materials. This 100% water-based, durable, and transparent surface treatment is specifically designed for natural stones, terra cotta, concrete, bricks, block paving and especially marble. With its advanced formulation, StoneGuard ProSealer offers a range of exceptional features that make it the ideal choice for both residential and commercial applications.

One of the standout features of StoneGuard Stone Sealer is its excellent water and oil repellences. This innovative sealer creates a protective barrier that prevents water and oil from penetrating the surface, ensuring that your substrates remain pristine and free from damage. Whether it's rainwater, cooking oils, or other liquids, you can trust StoneGuard ProSealer to keep your surfaces safe and dry.

In addition to its water and oil repellence, it boasts excellent anti-stain properties. This means that common household stains, such as olive oil, seed oil, coffee, ketchup, and mustard, are no match for this powerful sealer. The treated surfaces are highly resistant to staining, making it easier than ever to maintain a clean and attractive appearance.



Trutex Smooth Masonry Paint

A high quality, durable, water based, weather resistant coating. It gives your masonry excellent protection against weathering, dirt and pollution. Provides an economical and environmentally friendly alternative to solvent based masonry paint.

Suitable Substrates: Concrete - Masonry

Colours:

Finish: Matt

5L 10L Size:

Drying Times: Touch (15min)

12m²/L Coverage:

Application Method

Hard (30min)

Overcoat (



Sandtex Trade offers high-quality exterior paints designed for professionals. Known for durability, these paints provide long-lasting protection against the elements, ensuring buildings remain pristine for years











Coo-Var Floor Paints provide a resilient, hardwearing coating for indoor and outdoor use. It's versatile, easy to apply, and economical, offering protection against dirt, grime, oil, and dust. Available in 12 colours with a semi-gloss finish











Chalkboard & Blackboard Paint

A versatile, matt finish coating that transforms surfaces into writable and erasable chalkboards. Ideal for kitchens, kids' rooms, classrooms, and businesses, it's perfect for notes, drawings, and menus. Quick drying and durable

Suitable Substrates: Plaster-Blockwork-Brickwork-Concrete



Finish: Matt

Size: (0.5L) (1L) (2.5L) (5L)

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: 12-14m²/L Application Method





Furniture Paint

A quick drying decorative and durable topcoat, perfect for repainting wood furniture in black, white and many other colours. An oil based product with a Satin finish which gives a long term tough protective coating with a slight sheen.

Suitable Substrates: Wood - Metal

Colours:



Finish: Gloss Satin

Size: (1L) (2.5L) (5L)

Drying Times: Touch (3hr) Hard (8hr) Overcoat (24hr)

Coverage: 12-14m²/L Application Method









<u>Kitchen Cupboard Paint</u>

A quick drying decorative and tough topcoat. It is ideal for upcycling or adding a personal touch to an old wooden cabinet or Kitchen cupboard. An oil based paint which gives a long term durable protective coating. Scratch and scuff resistant.

Suitable Substrates: Wood - Metal



Finish: Gloss Satin

Size: (1L) (2.5L) (5L)

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: 12-14m²/L Application Method









Interior High Performance Wood Stain

Enhance your home's natural beauty with our Interior Wood Stain. Our ultra-durable formula, with polyurethane, silicone resins, and UV filters, protects doors, cupboards, skirting boards, and more for years.

Suitable Substrates: Bare Wood - Floor boards - Hardwood



Finish: Gloss

Size: (2.5L) (5L)

Drying Times: Touch 3hr Hard 12hr Overcoat 24hr

Coverage: 13-14m²/L

Application Method







Paint for Copper Pipes

Transform and protect your copper pipes with our top-of-the-line oil-based paint. This paint is specifically formulated for durability and a long-lasting finish. Moreover, whether for residential or commercial projects, pipes look great and stay shielded from dirt and grime.

Suitable Substrates: Metal

Colours:

TINT

Finish: Gloss Satin Dead Flat

Size: (0.5L) (1L) (2.5L)

Drying Times: Touch 2hr Hard 8hr Overcoat 24hr

Coverage: 12-14m²/L Application Method









ProFinish Tile Paint

An oil based paint with enhanced adhesion, perfect for direct application on tiled surfaces. Ideal for kitchens and bathrooms, it can recoat tired tiles or update their look with a fresh colour, allowing you to redesign a room without replacing existing tiles

Suitable Substrates: Wood - Metal

Colours:

B W AG WW BH CW SHG DB LG S TINT

Finish: Gloss Satin

Size: (1L) (2.5L) (5L

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: (12-14m²/L) Application Method

5





Garden Furniture Primer Undercoat

An oil based coating designed for use as a primer or undercoat for <u>Palatine Professional Garden Furniture Paint</u> when applying it to garden furniture such as chairs, tables and benches and will provide an even surface to ensure you achieve the best finish for your furniture.

Suitable Substrates: Wood - Metal

Colours: В R G



Finish: Matt

Size: 1L 2.5L 5L

Drying Times: Touch 3hr Hard (Overcoat (

Coverage: (12-14m²/L

Application Method







<u>Acrylic Primer and Undercoat</u>

An acrylic water based coating for wood. Specifically formulated to offer a tough, fast drying base coat. When used in conjunction with our Two Hour Gloss, your surface can be completely transformed within 4

Suitable Substrates: Wood

Colours:

۱۸/ G

Matt Finish:

1L 2.5L Size:

Touch (30min) 1hr **Drying Times:** Hard Overcoat (

Application Coverage: (12-14m²/L Method









Stain Blocking Primer

An oil based primer, designed to prevent the stain from bleeding through future coats applied to the surface. It is suitable for use on a variety of indoor and outdoor surfaces. Stops stains showing through the topcoat and diminishing the appearance.

Suitable Substrates: Wood - Metal

Colours: W G



TINT

Finish: Matt

Size: 1L 2.5L 5L

2hr 8hr 24hr **Drying Times:** Touch Hard (Overcoat (

Application 12-14m²/L Coverage: Method







ProFinish Gloss Wood Paint

A durable oil based top coat for indoor wood, ideal for doors, doorframes, and skirting boards. This oil-based paint offers a quickdrying, protective finish., it's perfect for updating old woodwork or adding a fresh look.

Suitable Substrates: Wood - Metal

Colours:

B W AG SG LI SB PB G DVG GG TINT

Finish: Gloss

Size: (1L) (2.5L) (5L

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: (12-14m²/L)

Application Method







ProFinish Satin Wood Paint

A a quick-drying, protective finish for internal woodwork such as doors, skirting boards, and stair banisters. An oil based decorative paint that withstands daily wear and tear, perfect for high traffic areas. Ideal for updating old woodwork or adding a fresh look.

Suitable Substrates: Wood - Metal

Colours:

B W AG SG LI SB PB G DG

Finish: Gloss

Size: (1L) (2.5L) (5L

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: 12-14m²/L Application Method







GG TINT



Radiator & Appliance Paint

Radiator paint is an oil solvent-based coating for radiators and metal appliances. It offers a durable gloss finish, heat resistance, and easy application with brush or roller. Available in 29 colours, including Anthracite Grey. Ideal for touching up or repainting appliances

Suitable Substrates: Wood - Metal

Colours:

B W AG DG SB LI GG CC IB BG TINT

Finish: Gloss Satin

Size: 1L 2.5L 5L

Drying Times: Touch 2hr Hard 8hr Overcoat 24hr

Coverage: 12-14m²/L Application Method







ProFinish Gloss

An oil based gloss, protective, decorative top coat. Suitable for interior and exterior use. Surfaces coated with our professional gloss will have durable and long term protection. A great choice for professional projects.

Suitable Substrates: Wood - Metal

Colours:

B W AG SG SHG PB PG CC SB SKG TINT

Finish: Gloss

Size: (0.5L) (1L) (2.5L) (5L)

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: (12-14m²/L)

Application Method







ProFinish Satin

An oil based decorative top coat for interior and exterior use. If you're looking for a contemporary alternative to a high gloss finish, then satin is a good choice. A satin finish means your surface will reflect some light, but won't have the high 'mirror' finish of gloss.

Suitable Substrates: Wood - Metal

Colours:

B W AG SG SHG PB PG CC SB SKG TINT

Finish: (Satin)

Size: (1L) (2.5L) (5L)

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: 12-14m²/L Application Method







ProFinish Matt



An oil based, flat matt enamel decorative top coat, provides durable long term protection. This matt paint is suitable for interior and exterior use. It's great for coordinating on a variety of different surfaces such as skirting boards, window frames, doors etc.

Suitable Substrates: Wood - Metal

Colours:

B W AG SG SHG PB PG CC SB SKG TINT

Finish: Matt

Size: (1L) (2.5L) (5L

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: 12-14m²/L Application Method









Kitchen Paint

Specially formulated to withstand the unique challenges of a kitchen environment. Designed to resist moisture, steam, and grease, making it easy to clean and maintain

Suitable Substrates: Plaster-Blockwork-Brickwork-Concrete

Colours:

V M TINT

Finish: Matt

Size: (2.5L) (5L) (10L)

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: (12-14m²/L)

Application Method







Bathroom Paint

Designed to handle the high humidity and moisture levels typical in bathrooms. With a matt finish, which provides excellent moisture resistance and durability. Easy to clean and help prevent mould and mildew growth

Suitable Substrates: Plaster-Blockwork-Brickwork-Concrete

Colours:

W M TINT

Finish: Matt

Size: (2.5L) (5L) (10L)

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: 12-14m²/L Application Method









Ceiling Paint

Specially formulated to cover overhead surfaces effectively. It typically has a flat finish to minimize glare and hide imperfections, creating a smooth, uniform appearance. Brighten your room and enhance the feeling of space

Suitable Substrates: Plaster-Blockwork-Brickwork-Concrete

Colours: W M TINT

Finish: Matt

Size: (2.5L) (5L) (10L

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: 12-14m²/L Application Method

n 🔊





Truflat Contract Matt

Palatine Truflat Contract Emulsion Paint is an economical full bodied matt emulsion. Formulated to provide an economical solution making it ideal for new work application. For Interior Walls & Ceilings.

Suitable Substrates: Plaster-Blockwork-Brickwork-Concrete

Colours:

W M

Finish: Matt

Size: (5L) (10L) (15L)

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr)

Coverage: 12-14m²/L

Application Method







Supercote Trade Matt

Supercote Trade Matt Emulsion provides an economical trade quality matt finish. High opacity and one coat coverage power make it ideal for jobs where efficiency and speed are necessary. Suitable for interior walls & ceilings in residential, commercial and factory settings.

Suitable Substrates: Plaster-Blockwork-Brickwork-Concrete

TINT

Colours:

W M Finish: Matt

Size: 5L 10L 15L

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: 12-14m²/L Application Method







Trumatt Premium Matt

Trumatt Premium Vinyl Matt Emulsion gives a full bodied matt finish. It is easy to apply and dries fast, whilst maintaining a high quality finish use. Trumatt Premium Vinyl Matt Emulsion gives a hard wearing, matt finish suitable for interior walls & ceilings.

Suitable Substrates: Plaster-Blockwork-Brickwork-Concrete

Colours:

W M BGR BH

Finish: Matt

Size: (2.5L) (5L) (10L

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

CW DP

Coverage: 12-14m²/L Ap

Application Method



DB DNG HGR



TINT



Trusheen Premium Silk

A high-quality, full-bodied silk finish ideal for residential and commercial projects. It offers high opacity and coverage power, allowing you to cover large areas quickly. Wipeable and hard-wearing, it's perfect for new work applications



Method

Coverage: (12-14m²/L

Application







Trucryl Acrylic Eggshell Emulsion

A low odour coating for interior use. Ideal for indoor surfaces, including walls, ceilings, wood and metal. With stain blocking and moisture resistant properties, ideal for rooms such as bathrooms and kitchens. Also durable and washable, making the coating easy to maintain

Suitable Substrates: Plaster-Blockwork-Brickwork-Concrete



Application Coverage: (12-14m²/L Method









A premium paint brand designed for professionals. Known for its high-quality and extensive range of colors, it offers excellent coverage and durability. Ideal for both domestic and commercial projects, Crown Trade is trusted by contractors, decorators, and builders









Royal County Luxury Matt

Our premium designer collection offers a variety of carefully curated colours that cater to both modern and classic tastes. Our luxury paint is formulated with the highest quality ingredients. It provides a rich, matt finish that exudes elegance and durability.

Suitable Substrates: Plaster-Blockwork-Brickwork-Concrete

Colours:

HI VF MO TO AM TUO CV WS TL DT TINT

Finish: Matt

Size: (2.5L) (5L

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: 12-14m²/L

Application Method







Royal County Luxury EggShell

Our premium designer collection offers a variety of carefully curated colours that cater to both modern and classic tastes. Our luxury paint is formulated with the highest quality ingredients. It provides a rich, eggshell finish that exudes elegance and durability.

Suitable Substrates: Plaster-Blockwork-Brickwork-Concrete

Colours: HI VF MO TO AM TUO CV WS TL DT TINT

Finish: (Eggshell)

Size: (2.5L) (5L

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: 12-14m²/L Application Method









Royal County Luxury Satinwood

Our premium designer collection offers a variety of carefully curated heritage inspired colours colours that cater to both modern and classic tastes. Our luxury Satinwood is and oil based decorative coating. Providing a rich, eggshell finish that exudes elegance and durability.

Suitable Substrates: Wood - Metal

Colours:

HI VF MO TO AM TUO CV WS TL DT TINT

Finish: Satin

Size: (1L) (2.5L) (5L

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: 12-14m²/L Application Method









ProFinish Exterior Gloss Paint

An alternative to our <u>ProFinish Gloss Paint</u> that is better suited for outdoor use. Its unique formulation gives it additional durability, allowing it to better withstand the elements. A versatile and durable product, suitable for a variety of outdoor applications.

Suitable Substrates: Wood - Metal

Colours:

B W AG SG LI SB PB G TGI GG TINT

Finish: Gloss

Size: (1L) (2.5L) (5L)

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: 12-14m²/L

Application Method







ProFinish Exterior Satin Paint

An alternative to our <u>ProFinish Satin Paint</u> that is more suitable for outdoor use. Its unique formulation gives it additional durability, allowing it to better withstand the elements. A versatile and durable product, suitable for a variety of outdoor applications.

Suitable Substrates: Wood - Metal

Colours:



Finish: Satin

Size: 1L 2.5L 5L

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: 12-14m²/L Application Method





TG1

GG TINT





<u>Garage Door Paint</u>

Transform your garage door with Garage Door Paint, the ultimate solution for a long-lasting, attractive finish. This premium paint is specially formulated to withstand the harshest conditions, ensuring your garage door remains vibrant and protected for years to come.

Suitable Substrates: Wood - Metal

Colours:

B W AG SG SLG PB GB POR RO GY TINT

Finish: Gloss

Size: 1L 2.5L

Drying Times: Touch 2hr Hard 8hr Overcoat 24hr

Coverage: (12-14m²/L) Application Method







Carbodeck UV Complete Decking Oil

Our Decking Oil has a rich, flexible resin that prevents blistering and flaking. Containing unique UV absorbers that protect the surface and prevent harmful damage to the surface. The penetrating oils soak deep into the wood which helps to prevent twisting and cracking.

Suitable Substrates: Bare Wood - Decking boards - Hardwood



2.5L 5L Size:

Drying Times: Touch Hard (12hr Overcoat (

Coverage: (13-14m²/L

Application Method







Carbodeck UV Complete Decking Paint

Carbodeck UV Complete Decking Paint is a tough, durable polyurethane oil based coating for the decoration and protection of old & new timber deck boards, spindles and most exterior woodwork.

Suitable Substrates: Bare Wood - Decking boards - Hardwood



Finish: Sheen

Size: 2.5L 5L

Drying Times: Touch 3hr 12hr Overcoat (

Coverage: (13-14m²/L **Application** Method







Garden Furniture Paint

An oil based decorative topcoat, designed to paint a variety of garden furniture, such as outdoor chairs, tables and benches including wooden and metal furniture. It provides long term protection and greater opacity compared to many water based alternatives.

Suitable Substrates: Wood

Colours: PB В ۱۸/ AG SG SB G TG4 GG TINT

Finish: Matt

1L 2.5L Size: 5L

8hr 24hr Touch (**Drying Times:** Hard (Overcoat (

12-14m²/L Coverage:







<u>Alkali Resisting Primer</u>

A low odour, oil based wall primer designed for use on interior and exterior masonry surfaces that may contain alkalis. It prevents alkalis from attacking the topcoat, avoiding visible damage from occurring on the surface. It can also be used as a sealer or stabiliser.

Suitable Substrates: Lime plaster - Cement Rendering -Concrete block - Stone - Blockwork Colours: w Finish: Matt 2.5L Size: 1L 5L 3hr 16hr Overcoat 24hr **Drying Times:** Touch Hard (12-14m²/L **Application** Coverage: (Method



Silicone Water Repellent

Prevents water penetration on masonry. Creates a breathable membrane as can be seen by moisture evaporates & water cannot penetrate. Silicone water repellent as a result is not affected by UV light. For exterior use only.

Suitable Substrates: Masonry-Brick-Stone-Concrete- Rendering

Colours:

CL

Finish: Gloss

Coverage: (

Size: 5L 25L

Drying Times: Touch (2hr

11-14m²/L

Application Method

Hard



Overcoat (24hr)





Aluminium Wood Primer

Aluminium wood primer acts as an outstanding barrier to protect wood and ferrous metals. It is also excellent for sealing naturally oily timber and creosote. Apply aluminium primer paint for wood as a base coat to smoke-damaged surfaces to prevent "bleeding" through top coats.

Suitable Substrates: Wood - Steel - Masonry - Iron

Colours:

S

Finish: Gloss

Size: (1L) (2.5L) (5L

Drying Times: Touch 2hr Hard 8hr Overcoat 24hr

Coverage: (12-14m²/L) Application Method

5







Coo-Var MDF primer is a water based primer that is suitable for a variety of Medium Density Fibreboard surfaces such as doors, desks and furniture.

Suitable Substrates: Wood

Colours:

W

1L

Finish: Matt

Size:

2.5L

5L

coo-var



Coo-Var Shellac Prime-All is a heavy duty shellac based stain blocker that can be overcoated with both oil based and water based paints.

Suitable Substrates: Wood-Composites-Plaster-Cement-most Colours: Plastics and Brickwork

5L

W

Finish: Matt

Size:

1L (2.5L)

COO-VAT®



Coo-Var Stain Lock Sprayable Primer is a water based multi surface primer and sealer that helps prevent stains from bleeding through the finishing coat.

Suitable Substrates: Wood-Plaster-Masonry-Most PLastics

Colours:

W

Finish: Matt

Size:



2.5L 5L



Gate & Railings Paint

An oil based gloss paint for metal railings and gates. Can be used on a variety of types and styles of gates and railings, including modern and older structures. The paint provides a durable finish that is resistant to weather conditions, water, wear and surface damage.

Suitable Substrates: Wood - Metal

Colours:

Coverage: (

Finish: Gloss

Size: 1L 2.5L

Drying Times: Touch (

12-14m²/L

Application Method

Hard

Overcoat (



ProFinish Log Cabin Paint

A protective, decorative top coat for exterior use on wood. A stylish and modern alternative to a wood stain effect, transform log cabins, timber lodges and outdoor buildings. With high opacity paint provides a superb finish. Oil based paint, offers a flexible, protective coating

Suitable Substrates: Wood - Metal

Colours:

R ۸G Satin

2.5L 5L Size:

Finish:

Finish:

Drying Times:

Coverage: (

Size:

3hr **Drying Times:** Touch

Coverage: (12-14m²/L **Application** Method

8hr

Hard

SKG MG GBR GDB SAB TINT





Shed Paint & Fence Paint

An oil based paint that provides a durable matt finish to a variety of outdoor wooden surfaces. Ideal for painting fence panels, sheds, summer houses and other outdoor wooden surfaces. Protects most types of wood from the effects of the weather and sunlight.

Suitable Substrates: Wood - Metal

Colours:



1L



12-14m²/L



SG



Application Method



SKG MG GBR GDB SAB TINT

Overcoat (24hr



Pond Paint

Pond Paint is a chlorinated rubber based product specially formulated to waterproof concrete ponds with an appealing decorative finish. Once this product is fully dried it is Fish friendly. This product is resistant to water, fungal growth (mould resistance) & atmospheric pollution.

Suitable Substrates: Concrete - Metal

Colours: B W LB

S

Finish: Gloss

Drying Times:

Size: (2.5L) (5L

Hard 8hr Overcoat 24hr

Coverage: (12-14m²/L)

Application Method







Exterior Extra Durable Wood Stain

A translucent, UV-stable wood stain for outdoor surfaces, offering a hard-wearing coating, making it durable for doors, soffits, fascia, and most timber. The stain allows the wood grain to remain visible, preserving its natural beauty while providing protection

Suitable Substrates: Bare Wood - Hardwood

Touch (

Colours:

CL B 60 59 58 57 56 48 38 20 TINT

Finish: Gloss

Size: (2.5L) (5L

Drying Times: Touch (3hr) Hard (12hr) Overcoat (24hr)

Coverage: 13-14m²/L Application









Sodium Hypochlorite Patio Cleaner

Sodium Hypochlorite Patio Cleaner is a 15% liquid sterilant. a powerful solution designed to clean and disinfect outdoor surfaces. It effectively removes stains, algae, mold, and mildew from patios, leaving them spotless and rejuvenated

Size:



(25L)

Features & Uses:

Effectively lifts stains from concrete, stone, and other patio material Sanitises the surface, making it safer for family and pet Kills and prevents the regrowth of these common issues, keeping your patio clean and safe

Removes dirt, grime, and organic material, revitalizing the appearance of your patio

Regular use helps maintain the cleanliness and longevity of outdoor surfaces



Carbolustre 2000 Barn Paint

Our bitumen-based barn paint ensures maximum protection and a polished look. Providing a tough, weather-resistant finish that guards against the elements. Whether for maintenance or a fresh coat, our barn paint delivers outstanding performance.

Suitable Substrates: Wood - Metal

Colours: R SAR NR PBR RO MG AG

Finish: Matt

2.5L Size: 5L

Drying Times: Touch (Hard (Overcoat (24hr

Coverage: (12-14m²/L

Application Method








Carboxide Agricultural & Industrial

A traditional oxide gloss paint that is durable, resilient and protective against the elements. It is a great choice for an agricultural and industrial gloss paint. Ideal for metal surfaces, it enhances the appearance and longevity of your farm equipment

Suitable Substrates: Wood - Metal

Colours:



Finish: 1L 2.5L 5L

Size:

20L 3hr 8hr Overcoat (24hr) **Drying Times:** Touch Hard

Application Coverage: (12-14m²/L Method



LBG



POR AG TINT





Carbotrak Tractor & Implement Paint

Protect and enhance your machinery with our premium tractor paint. This high-performance formula offers excellent coverage and a durable, weather-resistant finish. It resists rust and wear, ensuring your equipment stays in top condition

Suitable Substrates: Wood - Metal

Colours: В JCB JDG LG MFG MFY MFR DBC POR TINT W

Gloss Finish:

2.5L 1L Size: 5L

8hr 24hr **Drying Times:** Touch (Hard (Overcoat (

Coverage: 12-14m²/L **Application** Method







Farm Fence Paint

Protect your farm fences with our durable oil-based farm fence paint. This high-quality paint provides excellent coverage and a long-lasting finish. Resists weathering and wear, ensuring your fences stay in top condition and protected.

Suitable Substrates: Wood - Metal

Colours:

B W RR MG AG GB DB SB TINT

Finish: Matt

Size: (2.5L) (5L

Drying Times: Touch (3hr) Hard (8hr) Overcoat (24hr)

Coverage: 12-14m²/L

Application Method







Stable Paint

Protect your stables with our eco-friendly water-based stable paint. This durable formula provides excellent coverage and a long-lasting finish. Ideal for wooden and metal surfaces, it resists wear and tear while being safe for the environment

Suitable Substrates: Wood-Metal-Brickwork-Plaster-Masonry

Colours:

B W SB MG AG NB PB RO TINT

Finish: Matt

Size: (2.5L) (5L

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: 12-14m²/L Application Method







Rapid Milkstone Remover



An effective product in the removal and prevention of milkstone and water deposits. This phosphoric acid based descaler can be used in hot or cold solutions. As well as its main purpose this product removes rust and iron stains

Size: 5L 25L

Features & Uses:

Used in the dairy industry to clean bulk tanks, pipelines, utensils, and other dairy equipment.

Sometimes used in metalworking to remove rust from tools and equipment.

Can be used to remove mineral deposits from various surfaces in industrial settings.



Fast Dry Gloss

High performance, direct to metal coating that provides an excellent gloss finish top coat, formulated for spray application. ideal for use on steel work, railings, skips, containers and industrial machinery

Suitable Substrates: Wood - Metal Colours: В POR LG DEG MIG MBL RO GΥ TINT Finish: Gloss Size: 2.5L 5L 20L **Drying Times:** Touch (20min) Hard (Overcoat (**Application** Coverage: (12-14m²/L

Method



Fast Dry Semi Gloss

High performance, direct to metal coating that provides an excellent semi gloss finish top coat, formulated for spray application. ideal for use on steel work, railings, skips, containers and industrial machinery

Suitable Substrates: Wood - Metal

B W MG LG DEG POR MIG MBL RO GY TINT

Finish: (Semi Gloss)

Size: (2.5L) (5L) (20L)

Drying Times: Touch (20min) Hard (1hr) Overcoat (2hr)

Coverage: 12-14m²/L Application Method



Hammershield Hammer Finish Paint

A fast drying, decorative and protective direct to metal paint. Easy to use – this solvent borne, top coat, comes in hammered or smooth finish. Hammered Paint is ideal for garden furniture, gates, railings, garage doors and more.

Suitable Substrates: Wood - Metal

Colours:

B S

Finish: (Hammered)

Size: (0.5L) (1L) (2.5L) (5L

Drying Times: Touch 30min Hard 1hr Overcoat 2hr

Coverage: 12-14m²/L Application Method





Hammershield Smooth Finish Paint

A fast drying, decorative and protective direct to metal paint. Easy to use - this solvent borne, top coat, comes in hammered or smooth finish. Hammershield Paint is ideal for garden furniture, gates, railings, garage doors and more.

Suitable Substrates: Wood - Metal

Colours:

s

Finish: (Smooth)

Size: 0.5L 2.5L 5L

Drying Times: Touch (30min) Hard (Overcoat (

Coverage: (12-14m²/L

Application Method







Two Hour Gloss

A high gloss, fast drying, protective and decorative top coat for interior and exterior use. This professional gloss gives long term, durable protection and is ideal for restoration projects, structural steelwork, machinery, railings, pipework and more.

Suitable Substrates: Wood - Metal

Colours:



Gloss Finish:

1L 2.5L 5L Size:

2hr 8hr Overcoat (24hr) **Drying Times:** Touch Hard

Application Coverage: (12-14m²/L Method







TINT



Direct To Metal Paint (DTM)

Transform your metal surfaces with DTM paint, these paints offer excellent adhesion, corrosion resistance, and a durable finish, making them perfect for both indoor and outdoor applications. Bonds directly to metal surfaces without the need for a primer

Suitable Substrates: Metal

Colours: R



Touch (









Finish: Size:





24hr Overcoat (

Coverage: (12-14m²/L

Drying Times:

Application Method

3hr







Bright Aluminium Paint

A universal resin-based gloss finish for interior and exterior use on wood, bare steel, and primed surfaces. It offers excellent barrier protection and can be used on decorative ironwork, wheels, and as a solar reflective paint on roofs

Suitable Substrates: Wood - Steel - Masonry - Iron

Colours:



S

Finish: Gloss

11 2.5L Size:

5L 2hr **Drying Times:** Touch (

Coverage: 12-14m²/L **Application**

Method

Hard (8hr







Plant & Machinery Paint

Our plant and machinery paint offers exceptional durability, weather resistance, and long lasting protection. With excellent coverage, easy application, and a quick-drying, high-gloss finish, it ensures your equipment stays protected and looks professional

Suitable Substrates: Wood - Metal

Colours:

R TR Finish: Gloss

1L 2.5L 5L Size:

2hr 8hr 24hr **Drying Times:** Touch Hard Overcoat (

AG GB RG SG POR

Application Coverage: (12-14m²/L Method







MG TINT



Carbochlor Chlorinated Rubber Paint

Chlorinated rubber paint is resistant to salt water and many chemicals. It's popular for swimming pools, poolside areas, and animal housing. Widely used in hygienic areas like livestock and dairy parlours. Suitable for road surfaces, and manhole covers.

Suitable Substrates: Steel - Concrete - Road Surfaces

Colours:



Gloss Finish:

В

2.5L 5L Size:

8hr Overcoat (24hr **Drying Times:** Touch Hard (

Coverage: (12-14m²/L





Black Bitumen Paint

A versatile and durable coating used for various applications. This type of paint is ideal for waterproofing and protecting surfaces from corrosion. Its bituminous composition ensures long-lasting protection. sSuitable for both residential and commercial projects.

Suitable Substrates: Wood - Metal - Concrete

Colours:

В

Finish: Gloss

Size: 1L 2.5L 5L

3hr 24hr Overcoat (16hr **Drying Times:** Touch Hard

11.6m²/L Coverage:

Application Method





Green Bitumen Paint

An attractive alternative to traditional black bitumised paint. This paint provides an excellent flexible weatherproofing coating, because of its versatility, Green Bitumen can be used in a wide variety of applications and on several types of surfaces.

Suitable Substrates: Wood - Metal - Concrete

Colours: G

Finish: Gloss

2.5L 5L Size:

Touch **Drying Times:**

11.6m²/L **Application** Coverage: Method





Overcoat (16hr



Carbosil Bitumen Aluminium

For over coating bitumen based surfaces such as roofing felt and substrates. It protects surfaces from heat and UV light damage so makes a practical, decorative and solar reflective coating. Enhancing the lifespan of bitumen-type roofing materials.

Suitable Substrates: Wood - Metal - Concrete - Brick - Asbestos

Colours:

s

Gloss Finish:

Size: 1L 2.5L 5L

8hr **Drying Times:** Touch (Hard (Overcoat (24hr)

Coverage: (12-14m²/L





Carbobond Felt Adhesive

A homogenous solution of bitumen, fillers and fibres in solvent. Used as a whole or lap adherent for mineral materials. For bonding all types of roofing felts to metal, concrete, roofing felt, wood such as shed felt adhesive and sealing roofing laps. Can also be used for gritting.

Suitable Substrates: Wood - Metal - Concrete - Felt

Colours:

В

Finish: Matt

Size: (IL) (2.5L) (5L

Drying Times: Touch 3hr Hard 24hr Overcoat

Coverage: 12-14m²/L

Application Method





Carbotex All Weather Compound

A tough, flexible bitumen-based coating ideal for waterproofing roofs, gutters, and flashings. Provides instant protection against rain and damp, making it perfect for emergency repairs and long-term weatherproofing. Suitable for year-round use on most surfaces.

Suitable Substrates: Asphalt-Felt-Concrete-Slate-Tiles-Metal

Method

Colours:

Finish: Matt

Size: (2.5L) (5L) (20L)

No. Of Coats Min 2 Coverage: $1-6m^2/L$ Application







Carbosealit Roofing Mastic

Bituminous mastic for roofs is a highly viscous solution of modified bitumen, fillers and fibres. A general purpose roof coating for trowel application for repairing and filling large cracks and holes. Best used to reseal, waterproof and repair many different types of roof coverings

Suitable Substrates: Asphalt - Felt - Concrete - Asbestos - Metal

Colours:



Finish: Matt

Size: 1L 2.5L 5L

Drying Times: Touch 3hr Hard 24hr Overcoat 16hr

Coverage: 12-14m²/L Application







Carbopol Acrylic Roof Coating

Premium, solvent-based acrylic coating that incorporates synthetic fibres to provide a tough yet flexible seamless coating for industrial and domestic roofs. Designed for long-term maintenance, excels in all weather conditions, including damp environments

Suitable Substrates: Asphalt-Bitumen-Concrete-Brickwork-Colours:

Slates-Metals-Plastic Guttering

В

(Semi-Liquid Paste) Appearance:

Size: 5Kg

48 - 72 hrs **Drying Times:**

0.5-1m²/L Application Coverage: (Method





New Product

Tarmac Restorer

Specially formulated with a blend of bitumens, this Tarmac & Driveway Restorer is designed to rejuvenate paths, drives, car parks, and more. It effectively repairs small cracks and holes, restoring the surface to its original condition

Suitable Substrates: Paths - Drives - Car Parks

Colours:

В

Finish: Matt

5L 20L Size:

Overcoat 24hr Touch 12hr **Drying Times:**

Coverage: 1-2m²/L

Application Method





Rubber Bitumen Emulsion DPM

Rubber Bitumen Emulsion is a thixotropic, cold-applied rubberised bitumen emulsion that dries to form a tough, black, flexible coating. Ideal for waterproofing concrete and brick foundations, retaining walls, and bridge abutments

Suitable Substrates: Concrete-Brick-Felt-Asphalt-Lead-Zinc-Aluminium-Slate-Timber Colours:

В

Finish: Matt

Size: 5L 25L

Drying Times: Touch 12hr Overcoat (24hr

Application 1-2m²/L Coverage: Method

New Product



MarineMaster Boat & Barge Primer

An anti corrosive metal primer for iron and steel. The primer is based on alkyd resin and contains modified zinc phosphate and binding pigments. This means that long term protection is provided.

Suitable Substrates: Wood - Metal

Colours:

G

Finish: Matt

1L 2.5L 5L Size:

Drying Times: Touch 3hr Hard (Overcoat (24hr

Coverage: (12-14m²/L

Application Method







MarineMaster Boat & Barge Undercoat

A multi purpose, high build, oil based universal base coat. For use on wood, metal and painted surfaces, it offers the ability to easily change between contrasting colours. Being a solvent based undercoat gives this paint excellent adhesion as well as a high film thickness.

Suitable Substrates: Wood - Metal

Colours:

G R

Matt Finish:

1L 2.5L Size:

Drying Times: Touch 3hr

Application Coverage: (12-14m²/L

8hr





Overcoat (24hr)



MarineMaster Deepseal Bilge Paint

Method

A chemical resistant coating makes this ideal for use in bilge areas, where you commonly find chemicals such as oil, fuel, and cleaning products. designed for exceptional durability and resistance to water, oil, and chemicals.

Suitable Substrates: Wood - Metal

Colours: ۱۸/

G R

Finish: Gloss

В

1L 2.5L Size: 5L

Touch (3hr 8hr Overcoat (24hr **Drying Times:** Hard (

Coverage: (12-14m²/L Application Method



MarineMaster Boat & Barge Gloss

A protective, decorative paint designed to give long term, durable protection to your marine surfaces, including narrow boats, canal boats and barges. A versatile, water resistant, solvent borne paint

Suitable Substrates: Wood - Metal

Colours:

В LG GB POR GΥ TINT AG AB LBG

Finish: Gloss

Size: 1L 2.5L 5L

Drying Times: Touch 2hr Hard (Overcoat (

Application Coverage: (12-14m²/L Method







MarineGuard Gloss Paint

Our premium marine gloss is designed for all marine surfaces, including boats, bridges, and storage areas. It offers excellent durability and protection against weather, UV rays, and saltwater. Ideal for docks and marinas, it ensures a high-gloss, long-lasting finish on any surface.

Suitable Substrates: Wood - Metal - GRP

Colours:



Finish: Gloss

1L 2.5L 5L Size:

8hr Overcoat (24hr) **Drying Times:** Touch 3hr

Application Coverage: (12-14m²/L Method









MarineGuard Satin Paint

Our premium marine satin is designed for all marine surfaces, including boats, bridges, and storage areas. It offers excellent durability and protection against weather, UV rays, and saltwater. Ideal for docks and marinas, it ensures a long-lasting finish on any surface.

Suitable Substrates: Wood - Metal - GRP

Colours: В W AG LG AΒ LBG LI GB POR GΥ TINT

Finish: Satin

2.5L 1L Size: 5L

3hr 8hr **Drying Times:** Touch (24hr Hard (Overcoat (

Coverage: (12-14m²/L Application Method







MarineMaster Hull Blacking

A bituminous coating designed to be applied directly to the hull of a boat. The coating provides protection from water and weather, preventing the hull from becoming worn and damaged from everyday use of the boat. Suitable for narrowboats and cruisers

Suitable Substrates: Wood - Steel - Iron Hulls

Colours:

Finish: Semi Gloss

Size: (1L) (2.5L) (5L) (25L)

Drying Times: Touch (2hr) Hard (8hr) Overcoat (24hr)

Coverage: 12-14m²/L

Application Method





MarineGrip Anti-Slip

A single pack coating designed for use in marine areas and on boat decks. The anti slip additive in the paint provides much more grip than standard coatings, making it ideal for use in areas where safety is a concern, or surfaces exposed to significant rainfall.

Suitable Substrates: Wood - Metal - GRP

Colours:

B W LI BU R LG TINT

Finish: Satin

Size: (1L) (2.5L) (5L

Drying Times: Touch (3hr) Hard (8hr) Overcoat (24hr)

Coverage: 12-14m²/L Application Method







MarineGuard Varnish

A hard-wearing gloss varnish designed for marine environments. It protects wood and other surfaces from scuffs, scratches, and long-term weather exposure. Ideal for boats and marine surfaces, it prevents deterioration from water and weather.

Suitable Substrates: Wood - Metal - GRP

Colours:

CL

Finish: Gloss Satin
Size: 1L (2.5L) 5L

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: 12-14m²/L Application Method





Yacht Varnish

A tough, traditional varnish for new, previously painted, stained or varnished surfaces. Its quality and high gloss finish means it's perfect for yachts and boats. Provides superb durability, also making it ideal as a coating for windows and doors to protect them from poor weather.

Suitable Substrates: Wood - Metal

Colours:

CL

Finish: Gloss

Size: 1L 2.5L

Drying Times: Touch (2hr) Hard (

5L

Coverage: (12-14m²/L)

Application Method



8hr





Teamac Marine Paints offers a comprehensive range of high-quality coatings designed for marine environments. Their products include marine-grade varnishes, topcoats, undercoats, primers, antifouling paints, and bilge paints.











Peelaway® Marine is a water-based antifouling remover that strips multiple layers of coatings in one go. It includes a poultice blanket to reduce contamination, suitable for GRP, wood, steel, and concrete hulls.





Preparations & Accessories

Brushes

Rodo paint brushes are known for their high quality and durability, making them a favourite among professionals and DIY enthusiasts alike. They offer a wide range of brushes suitable for various painting tasks, ensuring excellent coverage and a smooth finish











Extension Poles

Extension poles are versatile tools designed to extend your reach for painting, cleaning, and other tasks. Made from lightweight materials with fixed and adjustable poles available. Making them ideal for high walls, ceilings, and hard-to-reach area







Frames

Roller and double arm frames are essential tools for painting large surfaces efficiently. Roller frames: Hold the roller sleeve and come in various sizes. Double arm frames: Provide extra stability and are ideal for heavy-duty task



Preparations & Accessories

Preparation & Sundries

Proper preparation is key to a successful painting project. Here are some essential preparation tools. Dust sheet rolls to protect floors and furniture. Tape, for clean edges and protecting trim. Abrasives to smooth surfaces for better paint adhesion. Scrapers to remove old paint



Roller Sleeves

Roller sleeves are crucial for a smooth paint finish. Available in various materials and pile lengths. Short pile: For smooth surfaces. Medium pile: For semi-smooth surfaces. Long pile: For rough surfaces



Trays & Scuttles

Plastic trays and scuttles are durable and versatile tools for painting projects. Made from strong, rigid plastic, they are designed to hold large quantities of paint, making them ideal for use with rollers. These trays and scuttles are perfect for both professional and DIY use



Preparations & Accessories



Peelaway Paint Remover is a powerful, heavy-duty product designed to strip multiple layers of paint and varnish in a single application. It is effective on various surfaces, including wood, brick, stone, and metal, and is particularly useful for removing old, lead-based paints









Paint Panther is a fast-acting, non-drip paint and varnish remover. It effectively strips multiple layers of coatings, including metal and hammer paints. Its gel consistency makes it ideal for vertical surfaces and intricate areas







Rust Treatment

Rust Treatment designed to remove rust quickly and effectively from various metal surfaces. It is reusable, non-flammable, and safe to handle, making it ideal for multiple treatments. This product is perfect for restoring rusted metal without the need for scrubbing or sanding





CARBOXIDE

METAL PRIMER

Fast Dry Metal Primer

Fast dry metal primer is an anti corrosive, quick drying, solvent based metal primer undercoat for ferrous metals. Recommended for spray application. Gives excellent protection to your surface before application of <u>Fast Dry Gloss</u> top coat.

Suitable Substrates: Metal - Iron - Steel

Colours:

B W G R

Finish: Matt

Size: (2.5L) (5L) (20L)

Drying Times: Touch (15min) Hard (30min) Overcoat (1hr

Coverage: (12-14m²/L)

Application Method





Anti-Corrosive Metal Primer

An anti corrosive zinc phosphate metal primer. Based on alkyd resin and contains modified zinc phosphate and binding pigments. This means that long term protection is provided. An ideal choice for metal gates, metal doors, architectural ironwork etc.

Suitable Substrates: Wood - Metal - Iron - Steel

Colours: B W G R

B W G

Sizo: O.S. II

Size: (0.5L) (1L) (2.5L) (5L) (20L)

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: 12-14m²/L Application Method









Carbogalv Zinc Rich Primer

A cold galvanising paint for iron and steel; use as a self-finish coating or a durable, weld through rust inhibiting primer. Suitable for all ferrous metals, such as carbon steel, stainless steel, mild steel, cast iron and wrought iron. Recommended for the protection of structural steel work

Suitable Substrates: Iron - Steel

Colours:



Finish: Matt

Size: (0.5L) (1L) (2.5L) (5L

Drying Times: Touch (2hr) Hard (8hr) Overcoat (24hr)

Coverage: 14m²/L Application Method

S







Mordant Solution (T Wash)

T wash, a galvanised steel metal wash used to as a pre-treatment for galvanised surfaces, aids the adhesion of future coats of paint. Supplied as a blue solution that has a characteristic blackening effect on the galvanised surface.

(0.75L) Size:

2L

5L

25L

Features & Uses:

Commonly used in industrial settings where galvanised steel needs to be painted, such as in structural steelwork, columns, beams, and other structural element.

Ideal for use where blasting or abrasion is not possible. Enhancing the bonding of high-temperature coatings.



Carboxide All Purpose Primer Undercoat

A high build multi-purpose, oil based universal base coat designed for wood surfaces. Use on new or unpainted wood and metal or previously painted surfaces. Recommended for brush, roller or conventional and airless spray.

Suitable Substrates: Wood - Metal

Colours:

G RU

TINIT

Finish: Matt

R

Size:

0.5L 1L **Drying Times:** Touch

2.5L 5L 3hr

Overcoat (

Coverage: (12-14m²/L **Application** Method



20L







Universal Multi Surface Primer

An oil based primer that can be applied to variety of surfaces. It is designed for use on surfaces that can have difficulty with adhesion when using standard paints, the increased adhesion strength of this primer allows it to be applied to these surfaces without issue.

> **Application** Method

Suitable Substrates: Wood - Metal - MDF - Tiles - Plastic

5L

Colours: W



TINT

24hr

Finish: Satin

Coverage:

1L 2.5L Size:

Drying Times: Touch (Hard (12-14m²/L

G

8hr



Overcoat (





Carboxide Red Oxide Primer

A traditional (red lead free paint) oil based, air drying primer which gives a smooth, protective surface. Our primer is a multi purpose, high build, rust inhibiting primer.

Suitable Substrates: Wood - Ferrous Metal

Colours:

RO

Finish: Matt

0.5L Size: 2.5L 5L 20L

Drying Times: Touch (3hr Hard 8hr Overcoat (

Coverage: (12-14m²/L

Application Method







Carboxide Grey Oxide Primer

A traditional oil based, air drying primer which gives a smooth, protective surface. Our grey oxide primer is a multi purpose, high build, rust inhibiting primer.

Suitable Substrates: Wood - Ferrous Metal

Colours:

G

Finish: Matt

Size: 0.5L 1L 2.5L 5L 20L

8hr Overcoat (24hr) **Drying Times:** Touch 3hr

Application Coverage: (12-14m²/L Method









Carboxide Black Oxide Primer

Carboxide Black Oxide Metal Primer is an alternative option to the more traditional Red Oxide Primer and is solvent based and air drying. It creates a smooth, protective surface to your surfaces. This means it is easy for you apply your top coat without too much sanding.

Suitable Substrates: Wood - Ferrous Metal

Colours:



Finish: Matt

2.5L Size: 1L 5L

Touch (8hr Overcoat (24hr **Drying Times:** Hard (

12-14m²/L Coverage: (

Application Method







Plant & Machinery Primer

An anti-corrosive primer designed for use on iron and steel machinery and plant equipment. It provides long term protection from rust and is designed for use before applying Palatine Plant & Machinery Paint.

Suitable Substrates: Wood - Metal

Colours:

G

Finish: Matt

Size: 1L 2.5L

Drying Times: Touch (3hr

Coverage: (12-14m²/L

Hard (**Application** Method

Overcoat (24hr)

Primers & Undercoats

Alongside our own brand primers and undercoats, we also offer a wide brand of alternative brands, such as Indura, ProXL and Indasa. Using the right primer can make a significant difference in the quality and longevity of your paint job.









Coo-Var offers a wide range of specialist primers designed for various applications. Their selection includes anti-damp primers, alkali-resistant primers, red oxide primers, stain-blocking primers, shellac primers, and primers for metal and wood









Chassis, Vehicle & Military QuickCoat

A tough, durable alkyd based finish, which is designed to provide your vehicle chassis and bodywork with a protective decorative coating in an easy to use aerosol form.

Suitable Substrates: Metal

Colours:



Finish: Gloss Matt Satin

0.4L Size:

Hard (30min) **Drying Times:** Touch (15min) Overcoat

Coverage: 2m²/can



<u>Furniture PrimeSpray</u>

Designed to be applied to new or previously painted furniture such as chairs, tables and benches before application of our Furniture Paint. Ensuring a longer lasting durable coating

Suitable Substrates: Wood - Metal

Colours: R

Finish: Matt

Size: 0.4L

Drying Times: Touch (15min) Hard (30min) Overcoat(

Coverage: (2m²/can)



Carbosol Furniture QuickCoat

Aerosol format of our Furniture Paint. With a gloss finish and is ideal for touching up or to reach areas that are difficult to access with a brush or roller. With a range of colours available

Suitable Substrates: Wood - Metal

Colours: R AG SG SHG BD DC POR CC TINT

Gloss Satin Finish:

0.4L Size:

Drying Times: Touch (15min) Hard (30min) Overcoat



<u>Carbosol Garden Furniture PrimeSpray</u>

Designed to be applied to new or previously painted furniture such as chairs, tables and benches before application of our Carbosol Garden Furniture QuickCoat.

Suitable Substrates: Wood - Metal

Colours:



Finish: Matt

Size: (0.4L)

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: (2m²/can)



Carbosol Garden Furniture QuickCoat

Transform your garden furniture with this durable, decorative spray paint. Offers vibrant colours and a long-lasting finish. Easy to apply, UV resistant, and quick drying, it ensures your outdoor furniture looks stunning year-round

Suitable Substrates: Wood - Metal

Colours:



Finish: Gloss Matt Satin

Size: 0.4L

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: (2m²/can)



<u>CarboGalv PrimeSpray</u>

A fast drying, rust inhibiting, weldable primer spray. Resistant to spray from salt water. Ideal for protecting bare iron and steel to reduce the effects of corrosion. Used on machinery, guttering and pipework. Also used for the protection of chassis and heavy machinery.

Suitable Substrates: Iron - Steel

Colours:



Finish: Matt

Size: 0.4L

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr



High Build PrimeSpray

Carbosol High Build Primer/Undercoat is now available in an aerosol format. Use on wood, metal, previously painted surfaces and most other surfaces. This means you can select the correct shade type for your suitable top coat.

Suitable Substrates: Wood - Ferrous Metal - Masonry

Colours:



Finish: Matt

Size: (0.4L)

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: 2m²/can



Carbosol Metal PrimeSpray

An anti corrosive metal primer aerosol, contains zinc phosphate. This means that long term protection is provided. It can be used with a variety of top coats so is a good choice for metal gates and architectural iron work.

Suitable Substrates: Iron - Steel

Colours:



Finish: Matt

Size: 0.4L

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: (2m²/can)



<u>Carbosol Oxide PrimeSpray</u>

Quick drying and easy to apply oxide primer. Allowing you to complete smaller jobs quickly and efficiently. The aerosol is also ideal for accessing hard to reach areas, giving a protective layer over which to apply a topcoat.

Suitable Substrates: Wood - Metal

Colours:



Finish: Matt

Size: (0.4L)

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr



Radiator PrimeSpray

An anti corrosive aerosol, which contains zinc phosphate and binding pigments. This means that long term protection is provided. Designed to be applied before application of the Carbosol Radiator QuickCoat.

Suitable Substrates: Wood - Metal

Colours:

В G

Finish: Matt

0.4L Size:

Hard (30min) **Drying Times:** Touch (15min) Overcoat (

Coverage: (2m²/can)



Carbosol Radiator QuickCoat

Aerosol format of our Furniture Paint. With a gloss finish and is ideal for touching up or to reach areas that are difficult to access with a brush or roller. With a range of colours available

Suitable Substrates: Wood - Metal

Colours:



Satin Finish: Gloss

Size: 0.4L

Drying Times: Touch (15min) Hard (30min) Overcoat (

Coverage: (2m²/can)



Carbosol Fast Dry Gloss Aerosol

High performance, direct to metal coating that provides an excellent gloss finish top coat, formulated for spray application. ideal for use on steel work, railings, skips, containers and industrial machinery

DEG POR MIG MBL RO

GΥ TINT

Suitable Substrates: Wood - Metal

Colours:

MG LG

В Gloss Finish:

Size: 0.4L

Touch (15min) Hard (30min) Overcoat (**Drying Times:**



<u>Carbosol Fast Dry Semi Gloss Aerosol</u>

High performance, direct to metal coating that provides an excellent semi gloss finish top coat, formulated for spray application. ideal for use on steel work, railings, skips, containers and industrial machinery

RO

GΥ

MG TINT

TINT

Suitable Substrates: Wood - Metal

Colours:

W MG LG DEG POR MIG

Finish: Semi Gloss

Size: (0.4L)

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: 2m²/can



<u>Carbosol Garage Door QuickCoat</u>

A coating designed for use on garage doors. It can be used on a variety of types of garage door types, including metal and wood. It provides long term protection and a high quality gloss finish.

Suitable Substrates: Wood - Metal

Colours:



Finish: Gloss Matt Satin

Size: (0.4L)

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: 2m²/can



HammerShield Hammered QuickCoat

A fast drying, tough decorative and protective direct to metal hammer finish aerosol. Easy to use for hard to reach areas. Ideal for gates, railings, garage doors and more.

Suitable Substrates: Wood - Metal

Colours:



Finish: Gloss

Size: (0.4L)

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr



HammerShield Smooth QuickCoat

A fast drying, tough decorative and protective direct to metal smooth finish aerosol. Easy to use aerosol for hard to reach areas. Ideal for garden furniture, gates, railings, garage doors and more.

Suitable Substrates: Wood - Metal

Colours:

B S

Finish: Gloss

Size: 0.4L

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: (2m²/can)



Pipe Identification Aerosol

A fast-drying, long term durable coating produced in BS 1710 industry standard colours for pipeline and pipework identification. Ensure your building is correctly identified with approved industry standard colours.

Suitable Substrates: Metal

Colours:









DY PWB EG FR EDO AAV OB WG OLB TI

Finish: Gloss

Size: (0.4L)

Drying Times: Touch (15min)

Hard (30min)

Overcoat 2hr

Coverage: 2m²/can



Carbosol UPVC QuickCoat

Offers a robust, long-lasting finish, ensuring your surfaces remain protected and looking fresh. With even coverage and a smooth, professional finish. Whilst enhancing the aesthetic appeal and providing durable protection.

Suitable Substrates: Wood - Metal - Plastic - UPVC - Tiles

Colours:

B W AG SG SHG PB GB POR RO GY MG

Finish: (Gloss) (Satin

Size: 0.4L

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr



Carbosol Professional OuickCoat

An aerosol spray paint for a superior, quick-drying finish, supplied in an easy-to-apply spray can. It provides a stunning decorative top coat that ensures your surfaces looks great and stays protected.

Suitable Substrates: Wood - Metal

Colours:

W AG SG SHG PB GB POR RO GY MG TINT

Finish: Gloss Matt Satin

Size: (0.4L)

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: (2m²/can)



Polyurethane Varnish QuickCoat

An aerosol format of our <u>Polyurethane Gloss Varnish</u>. Provides a lustrous, glossy appearance, whilst offering excellent scratch and stain resistance. It is designed to provide protection to a variety of surfaces

Suitable Substrates: Wood - Metal-Stone-Concrete-Slate

Colours:

CL

Finish: (Gloss

Size: (0.4L)

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr

Coverage: (2m²/can)



Yacht Varnish QuickCoat

A tough traditional clear gloss varnish aerosol. With great quality and a high gloss finish, our spray varnish is the ideal tough coating for keeping your yachts and boats looking fantastic.

Suitable Substrates: Wood - Previously Painted, Stained or Varnished

Colours: CL

Finish: Gloss

Size: 0.4L

Drying Times: Touch (15min) Hard (30min) Overcoat (2hr



TruTherm Anti Condensation Paint

TruTherm Anti-condensation thermal paint prevents moisture on walls and ceilings, inhibits mould growth, and enhances thermal performance. Designed for condensation-prone rooms, it uses highstrength, low-density additives to create an insulating layer.

Suitable Substrates: Wood - Metal - Walls - Ceilings

Colours:

Finish:

Drying Times:

Size:

TINT

Matt

0.5L

2.5L

Touch (30min)

5L 10L

Coverage: (12-14m²/L

Application Method



Overcoat (2-4hr





Anti Mould Paint

This ultimate solution combats mould and mildew effectively. Provides long-lasting protection, ensuring your walls stay clean and healthy. Ideal for bathrooms, kitchens, basements, and any damp areas,

Suitable Substrates: Wood - Metal

Colours:





Finish: Matt

Size: 1L **Drying Times:** 2.5L 2hr Touch

8hr Hard (

Overcoat (24hr)

TINT

Coverage: (12-14m²/L

Application Method

10L







Protection Paints offers advanced anti-mould paints like Zero-Mould and Mould-Guard. These paints prevent mould recurrence, are resistant to wet scrubbing, and ensure long-lasting protection in high-moisture areas, promoting a healthier home environment









Universal Gloss Multi Surface Paint

Provides a long lasting and weather resistant finish, making it ideal for use in outdoor environments as well as indoor surfaces. It features increased adhesion strength to allow application on materials that are otherwise difficult to paint

Suitable Substrates: Wood - Metal - Plastic - MDF - Tiles



Size: (1L) (2.5L) (5L)

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: 12-14m²/L Application Method

500





Universal Satin Multi Surface Paint

Provides a long lasting and weather resistant finish, making it ideal for use in outdoor environments as well as indoor surfaces. It features increased adhesion strength to allow application on materials that are otherwise difficult to paint

Suitable Substrates: Wood - Metal - Plastic - MDF - Tiles



Finish: Satin

Size: (1L) (2.5L) (5L

Drying Times: Touch (3hr) Hard (8hr) Overcoat (24hr)

Coverage: 12-14m²/L Application Method









UPVC & Plastic Paint

Ideal for rejuvenating and revamping, old tired looking fascia boards, UPVC window frames and UPVC doors. Formulated for excellent adhesion to most hard and flexible plastic surfaces including UPVC

Suitable Substrates: UPVC - Plastic

Colours: B W AG

Finish: Satin

Size: (1L) (2.5L) (5L

Drying Times: Touch (3hr) Hard (8hr) Overcoat (24hr)

Coverage: 12-14m²/L Application Method







6

Zenova IP Insulating Paint

Thermal insulating paint designed to optimize thermal management and conserve energy. It reduces heat transfer, reflects solar rays, and helps maintain indoor temperatures, making it ideal for residential, commercial, and industrial applications



Thermoguard Safewood

Thermoguard SafeWood is a specialized coating system designed to provide both fire protection and anti-viral properties for wood surfaces. It includes: Anti-Viral Properties: Reduces bacteria by 99.9% in 24 hours. Durability: Suitable for both interior and exterior wood, providing a durable, weather-resistant finish









Thermoguard Safewalls

Thermoguard SafeWalls is a highly effective coating solution designed to provide both decorative finishes and enhanced fire protection for walls and ceilings. It offers: Antiviral protection: Reduces bacteria by 99.9% in 24 hours. Durability: Forms a smooth, hard, and cleanable surface











Pipe Identification Paint

A fast-drying, long term durable coating produced in BS 1710 industry standard colours for pipeline and pipework identification. Ensure your building is correctly identified with approved industry standard colour identification.

Suitable Substrates: Wood - Metal

Colours:

ОВ GYO EG EDO AAV WG OLB TINT

Finish: Gloss

Size: 1L 2.5L 5L

Drying Times: Touch 2hr Hard (Overcoat (

Coverage: (12-14m²/L

Application Method







Barrier Paint

A high gloss, fast drying, protective and decorative top coat for interior and exterior use. This high gloss safety barrier paint gives long term, durable protection and is designed to ensure safety devices and barriers are clearly visible and identified.

Suitable Substrates: Wood - Metal



2hr

Method



Finish: Gloss

Drying Times:

1L 2.5L 5L Size:

Touch **Application** Coverage: (12-14m²/L









Anti-Graffiti Paint: A two-pack clear polyurethane coating that resists graffiti, making it easy to clean and durable. Vandelene Paint: A non-drying, sticky anti-climb paint that deters intruders by creating a slippery surface. Glocote Paint: High-visibility fluorescent paint effective in daylight and under lights at night, ideal for marking hazards and safety equipment Luminous Paint: Glows in the dark after exposure to light, perfect for marking emergency exits and escape routes











<u>Carbosolv Low Odour White Spirit</u>

Low Odour White Spirit is ideal as a thinner for traditional oil based paints and varnishes. It can also be used as a general cleaning and degreasing agent. Can be used with a wide range of paints and wood finishing products.

Size:

1L

(2.5L)

5L) (

25L)

(205L)

Compatible coatings:

Carboxide Primer & Undercoat
ProFinish Gloss / Satin / Matt
ProFinish Wood Paints - ProFinish Exterior Gloss
Plant & Machinery - Shed & Fence



<u>Carbosolv Multi Purpose Thinners</u>

Ideal for diluting fast dry and hammer finish paint for use in spray guns. Can also be used for cleaning equipment after use. When thinning for spraying please refer to the technical data sheet of the relevant paint. This will offer guidance in order to dilute at the correct ratio.

Size:



2.5L

5L)

25L) (205L)

Compatible coatings:

Fast Dry Metal Primer
Fast Dry Gloss & Fast Dry Semi Gloss
Chlorinated Rubber Paint
Pond Paint
Hammershield



Carbosolv Standard Thinners

Standard thinners are a blend of recycled solvents commonly used for thinning cellulose paints and cleaning spray guns. They are versatile and effective in reducing the viscosity of various coatings, making them easier to apply.

Size:









Features & Uses:

Excellent for cleaning spraying equipment Cost effective solution for thinning paint

2.5L



Carbosolv Xylene Thinners

Xylene paint thinner is a versatile solvent widely used in the painting and coatings industry. Known for its effectiveness in thinning oil-based paints, varnishes, and enamels. A clear and colourless liquid, is characterized by its strong dissolving power.

Size:







25L `

205L

Compatible coatings:

Fast Dry Metal Primer Fast Dry Gloss & Fast Dry Semi Gloss Chlorinated Rubber Paint Pond Paint Hammershield



Carbosoly Gun Wash

Gun wash is a powerful solvent blend specifically designed for cleaning spray guns and painting equipment. It effectively removes paint residues and ensures that spray equipment remains in optimal working condition

Size:



Features & Uses:

Quickly dissolves and removes paint residues from spray guns

Often less flammable than other solvents like acetone, making it safer to use in certain environments

Suitable for various types of paint and equipment



Carbosolv Cellulose Thinners

Cellulose thinners, also known as lacquer thinners, are a mixture of solvents designed to dissolve cellulose-based paints, lacquers, and varnishes. They are commonly used in automotive and woodworking applications to achieve a smooth, high-gloss finish

Size:



2.5L)

5L



205L

Features & Uses:

Anti Bloom properties.

For use as a high performance cleaner before working on surfaces to obtain the best possible finish.

Recommended for thinning cellulose based primers and topcoats



ProXL Panelwipe Degreaser

Effectively removes contaminants like dirt, grease, oil, and more from surfaces. Its non-aggressive formula is safe for bare metal and prepainted surfaces. It ensures a clean, static-free surface ready for painting

5L Size:

Features & Uses:

Suitable for use over bare metal surfaces as well as existing paint surfaces.

Available in slow, fast, and extra fast evaporation times Also in Aerosol form

Helps to remove static charge from surfaces Formulated to avoid attacking existing paint films Ideal for larger areas



ProXL Water Based Degreaser

An eco-friendly solution that effectively removes silicone, grease, wax, dirt, and more. Safe for old paintwork, bare metal, and plastics, it ensures a clean, static-free surface ready for painting. Easy to apply and non-aggressive on surfaces

Size:

5L

Features & Uses:

Suitable for old paintwork, bare metal and plastic surfaces Effectively removes grease, silicone, waxes and dirt, including tree resin and other contaminants

Reduces the organic solvent impact on the environment Can be applied with a pump sprayer or cloth



Isopropyl Alcohol (IPA) 99.9%

A versatile cleaner and disinfectant, ideal for removing oils, greases, and residues. It evaporates quickly, leaving no residue, and is suitable for electronics, surfaces, and medical use. Colourless, odourless, and highly effective, it ensures thorough cleaning and disinfection.

Size:

1L

5L

25L

205L)

Features & Uses:

Removes oils, greases, and residues Leaves no residue.

2.5L

Suitable for electronics, surfaces, and medical use Easy to use without strong smells

Cleans engine parts, windshields, and other surfaces, effectively removing grease and oil



Carbochem Cement Remover

Carbochem Cement Remover contains an organic, naturally occurring, plant based active ingredient that is excellent at breaking down bonds, dissolving and releasing hardened cement from common construction site surfaces.

Size:

5L

Features & Uses:

Efficient, fast acting and highly effective at penetrating and removes concrete spills, waste and mortar.

Effectively dissolves hardened cement, mortar, and grout from tools, mixers, and other construction equipment

Removes cement residues from floors, walls, tiles, and other surfaces, making them ready for further treatment or painting



Carbowash Acid Brick Cleaner

Carbowash Acid Brick Cleaner is a strong hydrochloric acid cleaner that removes stains, limescale and dirt. It is suitable for surfaces including brick, concrete, paying, scaffolding and tools.

Size:

5L)

(25L)

Features & Uses:

Effectively cleans off mortar smears from newly constructed brick walls

Removes white, powdery deposits caused by water-soluble salts on brick surface

Ideal for cleaning fireplace surrounds and exterior brick walls affected by pollution

Effective in eliminating rust stains from brick and masonry



Carbosoly Toluene

A clear, colourless liquid with a distinctive smell, commonly used as an industrial solvent. Also known as toluol, with numerous uses in the chemical and manufacturing industries. Known for its effectiveness, toluene solvent is widely utilized in chemical reactions.

25L

Size:



(2.5L) (

5L) (

(205L)

Compatible coatings:

Compatible Oil Based Paints

Features & Uses:

Paint Thinning, it helps achieve smooth, even finishes by dissolving paint and varnish

Excellent at dissolving a wide range of organic compounds, ideal for use with adhesives, and inks



Carbosoly Methylated Spirits

Also known as denatured alcohol, is a versatile solvent commonly used for cleaning, degreasing, and as a fuel for alcohol burners. It consists mainly of ethanol mixed with additives to make it unfit for consumption.

Size:

1L

2.5L) (5L)

(2

25L 205L

Features & Uses:

Excellent for cleaning glass, metal, and other surfaces.
Used in camping stoves and alcohol burners.
Antiseptic properties, can be used for disinfecting surfaces.



Carbosoly Acetone

Pure 99.7 % Acetone. A colourless, flammable liquid with a powerful smell that breaks down & dissolves other substrates easily. With its many uses such as paint remover, heavy degreasing job to nail polish remover Acetone is a popular product.

25L `

Size:

TL)

(2.5L) (5

5L (

(205L)

Compatible coatings:

Compatible Oil Based Paints

Features & Uses:

Clean and degrease surfaces, including electronics and laboratory equipment

Paint thinning with compatible oil-based paints and cleaning painting tools



Sodium Hypochlorite 15%

Sodium hypochlorite 15% is a potent solution commonly used for disinfection, bleaching, and cleaning. It is highly effective in killing bacteria, viruses, and fungi, making it a popular choice for sanitising surfaces and treating water

Size:

25L

(205L)

Features & Uses:

Suitable for use in household cleaning, industrial applications, and water treatment

Removes stains and whitens fabrics and surfaces Perfect for the maintenance of swimming pools Can be used for odour Removal



Alkalinity Reducer

Alkalinity Reducer is used primarily to reduce the pH level of alkaline substances in swimming pool or spa water. If an Alkaline Reducer isn't used in high pH water then problems such as cloudy water and scaling of surfaces, including pipework will occur.

Size:

25L

Features & Uses:

In swimming and paddling pools to maintain balanced water chemistry, ensuring the pH remains stable and preventing issues like cloudy water and scaling.

For aquariums, to create a suitable environment for aquatic life by maintaining appropriate alkalinity levels



<u>Premium Liquid Paraffin</u>

Premium Liquid Paraffin is a premium C1 grade paraffin (sometimes also referred to as Kerosene). Commonly used for domestic paraffin heaters and greenhouse heaters, this is a high heat and clean burning paraffin, making it ideal for this use.

Size:

5L

Features & Uses:

Widely used in portable heaters and central heating systems to provide warmth in homes and industrial settings Commonly used in lamps and lanterns

Effective solvent for cleaning machinery and degreasing equipment

Paraffin is also a cleaning fluid for automotive parts, as well as a lubricant in machinery and mechanical equipment.



Barrettine Premium Liquid Paraffin

C1 Grade Paraffin and Kerosene has many uses. The most popular being a fuel for domestic paraffin heaters and greenhouse heaters. This paraffin is a clean burning high heat output paraffin refined to BS2869C1

Size:



Features & Uses:

Widely used in portable heaters and central heating systems to provide warmth in homes and industrial settings

Commonly used in lamps and lanterns

Effective solvent for cleaning machinery and degreasing equipment

Paraffin is also a cleaning fluid for automotive parts, as well as a lubricant in machinery and mechanical equipment.

Caustic Soda Micropearl

High-Purity Sodium Hydroxide for Industrial Excellence



Powerful. Precise. Professional.

Caustic Soda Micropearl (Sodium Hydroxide) is a highly effective, 99% pure, and easy-to-handle alkali used across a wide range of industries:

- Textile Processing
- Soap & Detergent Manufacturing
- Water Treatment
- Pulp & Paper Production
- Chemical Manufacturing
- Alumina Refining

Key Features & Benefits

- High Purity (99%)
 - Delivers maximum chemical effectiveness.
- Versatile Applications
 - Ideal for pH adjustment, neutralization, and cleaning.
- Micropearl Form
 - Reduces dust, improves handling, and ensures precise dosing.
- Powerful Cleaning Agent
 - Cuts through grease, grime, and industrial residues.
- Long Shelf Life
 - When stored properly, retains potency over time.

Product Details:

Caustic Soda Micropearl, also known as sodium hydroxide, is a versatile and strong alkaline substance essential for pH adjustment, neutralization, and cleaning in various industries. Available in micropearl form for easy handling and precise application.

Caustic Soda Micropearl, a highly corrosive alkali widely used across numerous industries. This product is available in micropearl form, created through the evaporation of water from its liquid state followed by solidification into pearls. These micropearls offer strong alkalinity and are ideal for applications such as pH adjustment, neutralization, and effective cleaning.

Benefits:

- Efficient Handling: Micropearl form ensures uniform feeding and easy application.
- Cost-Effective: High purity and strong performance reduce the amount needed for effective results.
- Extended Shelf Life: Proper storage extends product usability.

Please note: this product can only be used for professional and industrial applications.

Purchasing products for professional use only, by purchasing you are acknowledging that you are a professional user and are not purchasing for the general public



Calcium Chloride Flake 77 – 80%

Calcium Chloride Flake is a compound used across a wide range of industries, including the Chemical, Manufacturing and Pottery industries. It has a number of different uses, such as dust control and as an agent to remove moisture.

Size:

5Kg)

(10Kg) (15Kg) (25Kg)

Features & Uses:

Calcium Chloride is a key component within the pottery industry to aid the application of glazes to non porous surfaces such as bisque porcelain.

Dust control, helps to suppress dust on unpaved roads by keeping the surface moist



Soda Ash – Sodium Carbonate

Also known as Sodium Carbonate is a white, odourless powder that is highly soluble in water. It is commonly used in various industrial and domestic applications due to its alkaline properties. Used in a wide range of industries, including glass manufacturing,

Size:

5Kg)

(10Kg) (25Kg)

Features & Uses:

Uses within the pottery industry as well as various other industries. Its primary use within the pottery industry is as a deflocculant, reducing the viscosity of the clay slip. This allows the clay to be more easily poured and manipulated without increasing the water content of the slip. Used to soften water and adjust pH levels

Sodium Silicate C100 | C140 | NS75



Sodium Silicate is a chemical used in a variety of industries, and a wide range of applications, from adhesives and detergents to water treatment and construction. Also known as water glass or liquid glass, and is a viscous alkaline liquid.

Size:

5L

10L

20L 205L

Features & Uses:

In car exhaust and head gasket repair, sand casting and as a component in drilling fluids.

It is also used as an adhesive in the production of cardboard and when bonding glass.

In the pottery industry, sodium silicate is mainly used as a deflocculant during the preparation of casting slips.



Premium Ice Melt

Highly effective de-icing agent that works by absorbing moisture from the environment, which helps it to quickly melt ice and snow. It is commonly used in both residential and commercial settings to ensure safe, ice-free surfaces

Size:

5Kg

10Kg)

15Kg

25Kg

Features & Uses:

Driveways and Sidewalks, to prevent slips and falls by melting ice and snow

Suitable for use on roadways

Melts ice faster than many other ice melt products Effective at temperatures as low as -32°C



White Rock Salt 20KG

A 20KG bag of white rock salt. Ideal for roads, path and driveways, it keeps surfaces clear of snow and ice. The rock salt helps to keep areas accessible and safe, which is especially important in working environments and public areas. White rock salt is cleaner than brown, which makes it ideal for areas that lead indoors. The salt works quickly to remove ice and snow to create a safe path for both foot and vehicle traffic.

Size:

20kg

Features & Uses

The brown colour makes it easy to see on treated surfaces, reducing the risk of over-application

Works well at melting ice and snow, providing good traction on slippery surfaces

Generally cheaper than white rock salt due to its abundance



Brown Rock Salt 20KG

A 20KG bag of premium brown rock salt. Ideal for roads, path and driveways, it keeps surfaces clear of snow and ice. The rock salt helps to keep areas accessible and safe, which is especially important in working environments and public areas. Brown rock salt is more cost effective than white, making it ideal for larger areas or places that are more likely to be affected by ice or snow.

Size:

20kg

Features & Uses:

The brown colour makes it easy to see on treated surfaces, reducing the risk of over-application

Works well at melting ice and snow, providing good traction on slippery surfaces

Generally cheaper than white rock salt due to its abundance

Vehicle Refinishing



Chassis, Vehicle & Military Paint

A tough durable coating, designed to provide your vehicle chassis and bodywork with a protective decorative coating. Making our chassis paint ideal for vehicle restorations.

Suitable Substrates: Wood - Metal

Colours:

B W LBG MIG DBG GY POR NG OG OXB TINT

Finish: Gloss Matt Satin

Size: (1L) (2.5L) (5L)

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: 12-14m²/L Application Method

tion





ProFinish Coach Enamel

A coating designed for classic vehicle restoration. It is suitable for a range of vehicle types, including cars, tractors, motorbikes and railway locomotives. With a highly durable finish, our coach enamel will endure harsh weather conditions and protect the metal underneath.

Suitable Substrates: Wood - Metal

Colours:

B W LBG MIG DBG Finish: Gloss

Size: (1L) (2.5L) (5L)

Drying Times: Touch (2hr) Hard (8hr) Overcoat (24hr)

GY POR GB NG

Coverage: 12-14m²/L Application Method







OG TINT



Carbosol Wheel Silver QuickCoat

A metallic silver decorative, high-quality, fast-drying coating provides a durable, glossy finish that resists chips and fading. Perfect for touch-ups or complete wheel makeovers

Suitable Substrates: Wood - Metal

Colours:

Gloss

Finish: Gloss

Size: (0.4L)

Drying Times: Touch (15min) Hard (30min) Overcoat (2hi

Vehicle Refinishing



Indura 2k Epoxy Primer

Indura 2K Epoxy High Build Primer is a premium quality Epoxy Metal Primer for Commercial and Industrial applications. Ideal as a base coat for commercial vehicles and Standard corrosion protection systems for buildings

Features & Uses:

- Epoxy Polyamide with activated zinc phosphates
- High etching adhesion
- High resistance to chemicals
- · Smooth finish
- Good chemical and mechanical resistance
- Achieves Standard systems for C rated environment categories



Indura 2k Acrylic PU Gloss

Indura two pack gloss designed to have good weather resistance and colour retention. It is ideal for use on surfaces constantly exposed to weather and dirt, such as bodywork on commercial vehicles

Features & Uses:

- Weather Resistance: Suitable for outdoor applications.
- Durability: Provides a long-lasting finish.
- Fast Drying: Speeds up the application process.
- Versatile Application: Can be applied using conventional or airless spray methods
- · Commercial Bodywork
- Industrial Structures



2k Scratch Resistant Clearcoat

Scratch Resistant 2K Clearcoat is a 2 pack automotive clear coat for use over base coats. It provides the surface with scratch resistance and can be overcoated within 24 hours if a further coat is desired

Features & Uses:

- Offers excellent scratch resistance, enhancing the durability of the surface.
- Provides strong adhesion to both waterborne and solvent base coats.
- Extremely stable when applied on vertical surfaces.
- Can be overcoated within 24 hours without additional sanding.
- Theoretical coverage of 8-9 m² per litre at 50 microns dry film thickness

Vehicle Refinishing



ProXL offers a comprehensive range of aerosol products designed for automotive and industrial applications. Key products include:

PlastiColour: A fast-drying coloured coating for plastics.

Bumper Spray: Designed for repairing and refinishing plastic bumpers.

Stonechip Spray: Provides durable protection against stone chips and corrosion









ProXL offers a comprehensive range of aerosol products designed for automotive and industrial applications. Key products include

2K Repair: A high-performance repair filler.

2K Primer: Offers superior adhesion and corrosion resistance













Indasa offers a variety of high-quality aerosol products designed for automotive and industrial applications. Key products include: Acrylic Gloss Black: Provides a durable, glossy finish. Clearcoat: Delivers a protective, clear finish. High Build Primers, available in various colours for excellent adhesion and coverage









Cedar Wood Treatment

Seals rough, sawn, or smooth timber, reducing decay, swelling, and twisting. Its UV-resistant pigments protect wood from UV damage, making it ideal for outdoor structures like sheds, fences, trellises, pergolas, and gazebos. Transparent/translucent finish

Suitable Substrates: Wood

Colours:



Finish: Matt

Size: (2.5L) (5L

Drying Times: Touch (

Coverage: 12-14m²/L

Hard 8hr

 \sim

Overcoat (



Boiled Linseed Oil

Boiled linseed oil, blended with driers for faster drying, comes from ripened flax seeds. Used for centuries, it penetrates unsealed wood, providing a natural, water-resistant, protective finish that darkens slightly with age.

Application Method

Suitable Substrates: Wood-Terracotta Tiles-Concrete-Stone
** Not suitable for oak

Finish: Matt

 Size:
 1L
 2.5L
 5L
 25L

 Drying Times:
 Overcoat 12-24hr

Drying Times: Overcoat

Coverage: 8-10m²/L

Application Method





Raw linseed Oil

A natural flax seed oil that penetrates unsealed wood, providing a water-resistant finish with a slightly enhanced colour that darkens with age. Ideal for oak beams, canes, cricket bats, woodcraft, and as a lubricant in French Polishing (not for furniture or flooring).

Suitable Substrates: Wood Finishing- Painting-Concrete-Stone-Food/Toy safe when dry, certified by EN 1186:2002 & EN71:3

Finish: Matt

Size: (1L) (2.5L) (5L) (25L

Drying Times: Overcoat (12-24hr)

Coverage: 8-10m²/L Application Method



Teak oil

Barrettine Teak Oil enhances and protects outdoor wood, providing a rich, natural finish. It penetrates deeply to nourish and preserve, offering UV resistance and water repellency. Water resistant finish

Suitable Substrates: Wood - Teak - Hardwood - Cedar - Iroko
** Not suitable for Oak

Size:

1L

2.5L) (

5L)

25L

Features & Uses:

Outdoor Furniture

Wooden Boat Decks Interior Woodwork Exterior Woodwork



Danish oil

Barrettine Danish Oil is a blend of rich oils, including Tung Oil, that enhances and protects wood surfaces. It provides a low-lustre, natural finish with high water repellency. Ideal for doors, furniture, and wood turning projects, both indoors and sheltered outdoors.

Suitable Substrates: Wood - Teak - Hardwood - Cedar - Iroko ** Not suitable for Oak

Size:

1L

2.5L)

5L)

(25L

Features & Uses: Furniture

Wooden Utensils Doors & Trims Wood Turning

Sheltered Exterior Wood



Garden Furniture Oil

Barrettine Garden Furniture Oil is a natural blend of clear oils and resins that penetrates unsealed wood, leaving a beautiful, water-resistant finish. Ideal for outdoor furniture, it nourishes, protects, and reduces greying. Treat annually to maintain appearance.

Suitable Substrates: Wood

Size:

(1L

Features & Uses:

Protecting and enhancing all types of garden furniture. Nourishing and preserving unsealed wood. Providing a natural, water-resistant finish. Reducing the greying appearance



General Purpose Varnish

General purpose varnish which provides a tough, durable gloss finish. It can be used over bare wood and previously painted, stained or varnished surfaces. Oil based varnish for both internal and external work

Suitable Substrates: Wood - Metal

Colours:

CL

Finish: Gloss

Size: 1L 2.5L 5L

Drying Times: Touch 3hr Hard 8hr Overcoat 24hr

Coverage: 12-14m²/L

Application Method









Polyurethane Gloss Varnish

Polyurethane gloss varnish is a durable finish, which seals and protects a wide range of surfaces. With a wide range of properties it protects your wood work from knocks, heat, scratches and chemical spills. Use to brighten up colours and protect wooden surfaces

Suitable Substrates: Wood - Stone - Slate - Concrete

Colours:

CL

Finish: Gloss Satin

Size: (1L) (2.5L) (5L

Drying Times: Touch 3hr Hard 8hr Overcoat (

Coverage: 12-14m²/L Application Method







Floor Varnish

High-quality floor varnishes like the Quick Drying Floor Varnish and CooVar Polyurethane Floor Varnish. These products provide excellent protection, durability, and a beautiful finish for wood floors





Waxes & Lacquers

Barrettine provides premium waxes and sealers designed to protect and enhance wood surfaces. Suitable for both indoor and outdoor applications, their products offer long-lasting durability, a beautiful finish, and help maintain the natural beauty of wood. Ideal for furniture, floors, and more.







Polishes & Shellacs

Barrettine offers a range of high-quality polishes and shellacs designed to protect and enhance wood surfaces. Their polishes provide a smooth, glossy finish, while their shellacs offer a durable, protective coating that brings out the natural beauty of the wood. Ideal for furniture, floors, and more.







Knotting Solutions

Knotting Solution is a high-quality product designed to seal knots and resinous areas in wood before painting. It prevents natural resins from seeping through and discolouring the paint finish. Suitable for both interior and exterior use, it ensures a smooth, long-lasting result





Wood Preservers

Barrettine Wood Preserver, a high quality, deep penetrating, low odour preserver to protect wood against wet rot and wood boring insects. Its semi transparent low sheen finish allows viewing of the natural wood texture. Ideal for use on pressure treated wood, treated timber or untreated wood







Wood Protective Treatment

Barrettine Wood Protective Treatment deeply penetrates wood, providing water repellency, UV resistance, and protection against mould and algae. Its oil-based, low-odour formula is suitable for all timber types, offering a semi-transparent finish that enhances natural wood beauty







Wood Care

Barrettine offers comprehensive wood care solutions: Woodworm Killer eradicates insects and protects timber, Wood Reviver restores weathered wood to its natural tone, and Cut End Preserver shields exposed end grain from rot and fungi







Fire Protection

Intumescent Basecoat

An intumescent basecoat is a specialized fire-retardant coating designed to expand when exposed to high heat or flames. This expansion forms a thick, insulating layer that protects the underlying substrate, such as steel or wood, from the effects of fire, significantly delaying structural failure







Fire Retardant Paint

Fire retardant paint is designed to slow the spread of flames and reduce smoke production in the event of a fire. It works by forming a protective barrier on the surface, which helps to insulate and protect the underlying material. This type of paint is commonly used on wood and metals





Fire Varnish

Thermoguard Fire Varnish is a clear intumescent varnish designed to provide fire protection for timber surfaces. Fire Resistance: Achieves BS Class 1, Class 0, and EN Class B s2 d0 standards. Suitable for both interior and exterior use, providing a tough, durable finish.





Fire Protection

A Brief Summary of the Process When Purchasing Intumescent Paint:

Step 1.

Complete Relevant Enquiry Form: Fill out the enquiry form specific to your substrate to provide details about your project and requirements:

Steel Enquiry Form Wood enquiry Form Walls & Ceilings.

Step 2.

Return the Completed Form: Send the completed form back to us. We will then confirm the correct product details, and the volume required to achieve the requested fire rating. A reference number will also be provided, which is required when requesting certification.

Step 3.

Purchase and Apply Intumescent Paint: After purchasing the recommended intumescent paint, carefully follow the manufacturer's application instructions. Ensure the recommended number of coats and film thickness are applied.

Step 4.

Apply Topcoat (if required): If needed, apply a topcoat to protect the intumescent paint from environmental factors and enhance its durability.

Step 5.

Request Fire Certification: Once the intumescent paint has been applied and dried, you can request a fire certification from Thermoguard or Nullifire.

Steel Enquiry Form



Palatine Paints & Chemicals Ltd 55 Smallbrook Lane, Leigh, Lancs, WN7 5PZ T: 01942 884122

E: sales@palatinepaints.co.uk

Please complete the below details and return back to us: sales@palatinepaints.co.uk

From this information we are able to confirm that you have purchased sufficient product to
achieve the required fire rating level/standard you wish to achieve

Customer Name:								Customer Contact Details:											
Site Addre	ess:																_		
Fire Protec	tion Ratir	ng Red	quired:														_		
30 Mins		60 Mins						Mins 120				ins							
Is the stee	ol:														J	_	_		
Primed		Visible		Dry Inter	nal			Damp In		ternal			External						
Are	the Roof an	ıd Wall	s Erecte	t															
Sectio Type/Sh Serial Size &	Section No Sides Vertical Post (V) Type/Shape to be Post (V) Serial Size & Mass painted Floor Beam Rafter (H)			Supporting Floor Y/N		Veb epth nm *	Flange Width mm *		Either Mass Per Kg (if known)		Or Thickness of Flance mm		Total Length		Steel Design ie. BS5950 or Eurocode BS EN1993				
			1			ST	EEL S	IZES		s	erial Si	ze an	d Mass	e.g. UC	203x	203x46			
				+			П	Γ	C										
Jo	oist Uni Uni	versal Co versal Be		reiform FERMI	Channel INOLOGY	Angle	e Te	STE		ins IDES	EXP	SH OSE			R	HS			
		ange lickne	55	\	Flange				4 SIDES		3 SIDES		er levels						
						Web		1		-	i DE	I	1 120						

Wood Enquiry Form



Palatine Paints & Chemicals Ltd 55 Smallbrook Lane, Leigh, Lancs, WN7 5PZ T: 01942 884122

E: sales@palatinepaints.co.uk

Please complete the below details and return back to us: sales@palatinepaints.co.uk

From this information we are able to confirm that you have purchased sufficient product to
achieve the required fire rating level/standard you wish to achieve

Customer Name:								Customer Contact Details:							
							7 [
Site Addre															
Site Addre	988.														
Protection	Require	d: (For	Doors	see s	eper	ate she	et)								
Class 1, O, B, C 30 mins										60 mins					
Is the prot	ection fo	r:													
·						red for Bu	or Building Regulations								
About the	Wood					-								_	
Softw	Softwood				Hardwood			Rough S			Sawn Open Grained				
Plan	Planed			Plywood		ı		v		Vood Derivative - Please Spe			cify *1		
Inter	Internal			Externa										1	
Previously	Coated	With													
Nothing		Painted		Clear F		r Finish		Sto		d Finish		Other Please Spe		er - pecify *2	
Tune if Fin	iah Damı	:uad													
T .	Type if Finish Required Painted Clear Finish				h		Stained Finish			Nat			tural		
Full	iteu			Ciec	JI FIIIIS	"		3	tuiriet	1 FII II 511			iturur		
Beams or	Joists											•			
Depth	& Width			w			What is	Vhat is above *3							
Cladding	or Panell	ing													
Type *4 and Thickness What is Behind *5															
Cladding	or Panell	ing													
Type *4 and Thickness What is Behind *5															
Flooring a	nd Unde	rside													
Type *6 and Thickness What is Above *7															

- * 1 Wood Derivative e.g. MDF,OSB Cross Laminated Timber
- *2 Previously Coated e.g. Tantalised or Waterproofed
- *3 Beams What is above e.g. Room, Loft, Roof.
- *4 Cladding Type e.g. Tongue & Groove, Feather Edge, Solid.
- *5 What is behind e.g. Blockwork, Plasterboard, Cement Board.
- *6 Flooring Type e.g. Tongue & Groove, Solid.
- *7 Flooring Underside what is Above e.g. concrete, Further wooden flooring.

Please Note:

To help us provide the correct specification and certification please complete as much detail as possible. If you have different levels of protection please complete an enquiry for each. Please note that class 1,0,8,C are not the same as 30 and 60 minutes fir resistance.

Wood Enquiry Form



Palatine Paints & Chemicals Ltd 55 Smallbrook Lane, Leigh, Lancs, WN7 5PZ T: 01942 884122 E: sales@palatinepaints.co.uk

Please complete the below details and return back to us: sales@palatinepaints.co.uk

From this information we are able to confirm that you have purchased sufficient product to
achieve the required fire rating level/standard you wish to achieve

Customer Name:								Cı	Customer Contact Details:								
Site Addre	ess:							_									
Type of Pr	otection	Required	: (plea	se se	elect)												
Compliance with 'Fire Safety Order 2005'								Class	l sac								
Maintain Existing Fire Standard						Class O or EU Class B s2 d0											
Type of Fir	nish Rea	uired				-				-					-		
Nothing					Clear Fir	Finish			Stained Finish				Other - Please Specify *2				
Colour Re	guired																
Pain	ted		С	lear f	Finish				Stained	d Finish	inish		Natural				
Is the Project Inte						Interr	nal					External					
Total Area to Protect												1					
		ublic spa	ce' or 's	shar	ed are	a', no	on-d	lome	stic pre	nises	incl	uding t	he c	ommı	unal areas	of	
aprtment blocks YES This is a 'public space' or 'shared area'						area'		NO This is				s NOT a 'public space' or 'shared area'					
What sub	strates o	ıre you wi	shing t	o pr	otect (plea	se se	elect	all that	apply)						
Plasterbo	oard		Brick / C	oncr	ete				Plaster				Wood Panelling				
Other pled	ise specif	y:															
Has the su	ırface be	en previo	ously d	ecor	ated:												
YES, previously decorated and records exist of previous work																	
YES, previo	ously deco	rated and	NO reco	rds e	xist of p	revio	us wo	ork									
Previously	decorate	d but stripp	ed / rub	bed	down c	ompl	etely										
No NOT pro	eviously d	ecorated															

Please Note:

To help us provide the correct specification and certification please complete as much detail as possible. If you have different levels of protection please complete an enquiry for each. Please note that class 1,0,B,C are not the same as 30 and 60 minutes fire resistance.

Product Index

Product	Page	Product	Page	Product	Page			
Acid Etch for Concrete	7	Chassis, Vehicle & Military QuickCoat	49	Pliocem Masonry Paint	11			
Acrylic Primer and Undercoat	16	Chlorinated Rubber Anti-Slip	10	Polishes & Shellacs	75			
Alkali Resisting Primer	25	Chlorinated Rubber Floor Paint	9	Polyurethane Floor Varnish	5			
Alkalinity Reducer	65	Coldcrete Epoxy Patch Repair System	7	Polyurethane Gloss Varnish	74			
Aluminium Wood Primer	25	Damp Proof Membrane (DPM)	6	Polyurethane Varnish QuickCoat	55			
Anti Mould Paint	56	Danish Oil	73	Pond Paint	29			
Anti-Corrosive Metal Primer	45	Direct To Metal Paint (DTM)	33	Premium Ice Melt	68			
Anti-Slip Floor Paint for Wood	9	Epoxy Concrete Patch Repair System	7	Preparation & Sundries	43			
Barrettine Premium Paraffin	65	Epoxytread Single Pack Floor Paint	8	ProFinish Coach Enamel	69			
Barrier Paint	59	Extension Poles	42	ProFinish Exterior Gloss Paint	23			
Bathroom Paint	19	Exterior Extra Durable Wood Stain	29	ProFinish Exterior Satin Paint	23			
Black Bitumen Paint	35	Farm Fence Paint	31	ProFinish Gloss	18			
Boiled Linseed Oil	72	Fast Dry Gloss	32	ProFinish Gloss Wood Paint	17			
Bright Aluminium Paint	34	Fast Dry Metal Primer	46	ProFinish Log Cabin Paint	27			
Brown Rock Salt 20KG	68	Fast Dry Semi Gloss	32	ProFinish Matt	18			
Brushes	42	Fire Retardant Paint	77	ProFinish Satin	18			
Calcium Chloride Flake 77-80%	67	Fire Varnish	77	ProFinish Satin Wood Paint	17			
Carbobond Felt Adhesive	36	Floor Paint for Wood	4	ProFinish Tile Paint	14			
Carbochem Cement Remover	63	Frames	42	Protection Paints	56			
Carbochlor Chlorinated Rubber Paint	34	Furniture Paint	14	ProXL Degreaser	62			
Carbodeck UV Complete Decking Oil	24	Furniture PrimeSpray	49	ProXL Panelwipe	62			
Carbodeck UV Complete Decking Paint	24	Garage Door Paint	23	Radiator & Appliance Paint	17			
Carbogalv PrimeSpray	47	Garage Floor Paint	24	Radiator PrimeSpray	52			
Carbogalv Zinc Rich Primer	45	Garden Furniture Oil	73	Rapid Milkstone Remover	31			
Carbogrip Exterior Anti-Slip	10	Garden Furniture Paint	24	Raw Linseed Oil	72			
Carbogrip Polyurethane Anti-Slip	10	Garden Furniture Primer Undercoat	15	Roller & Sleeves	43			
Carboline Road Line Paint	8	Gate & Railings Paint	27	Royal County Luxury EggShell	22			
Carbolustre 2000 Barn Paint	30	General Purpose Varnish	74	Royal County Luxury Matt	22			
Carbosealit Roofing Mastic	36	Green Bitumen Paint	35	Royal County Luxury Satinwood	22			
Carbosil Bitumen Aluminium	35	Hammershield Hammer Finish Paint	32	Rust Treatment	44			
Carbosol Fast Dry Gloss Aerosol	52	Hammershield Hammered QuickCoat	53	Shed & Fence Paint	27			
Carbosol Fast Dry Semi Gloss Aerosol	53	Hammershield Smooth Finish Paint	33	Silicone Water Repellent	25			
Carbosol Furniture QuickCoat	49 53	Hammershield Smooth QuickCoat	54 51	Soda Ash - Sodium Carbonate	67			
Carbosol Garage Door QuickCoat	47	High Build PrimeSpray Indura 2K Epoxy Primer	70	Sodium Hypochlorite 15% Sodium Hypochlorite Patio Cleaner	29			
Carbosol Garden Furniture PrimeSpray Carbosol Garden Furniture QuickCoat	47	Indura 2K Epoxy Primer Indura 2K Acrylic PU Gloss	70	Sodium Silicate C100 C140 NS75	67			
Carbosol Metal PrimeSpray	51	Indura Eclipse 2K Scratch Resistant Lacquer		Stable Paint	31			
Carbosol Oxide PrimeSpray	51	Interior high Performance Wood Stain	14	Stain Blocking Primer	16			
Carbosol Professional QuickCoat	55	Intumescent Basecoat	77	Stepgrip Step & Ramp Paint	11			
Carbosol Radiator QuickCoat	52	Isopropyl Alcohol (IPA) 99.9%	62	StoneGuard Prosealer	28			
Carbosol UPVC QuickCoat	54	Kitchen Paint	19	Supercote Trade Matt	20			
Carbosol Wheel Silver QuickCoat	69	Kitchen Cupboard Paint	14	Teak Oil	73			
Carbosolv Acetone	64	Knotting Solutions	75	Thermoguard Safewalls	58			
Carbosoly Cellulose Thinners	61	Line Marking Aerosols	8	Thermoguard Safewood	58			
Carbosoly Gun Wash	61	Line Marking Applicator	8	Trays & Scuttles	43			
Carbosoly Low Odour White SPirit	60	MarineGuard Gloss Paint	39	Trucryl Acrylic Eggshell Emulsion	21			
Carbosolv Methylated Spirits	64	MarineGuard Satin Paint	39	Truflat Contract Matt	20			
Carbosolv Multi Purpose Thinners	60	MarineGuard Varnish	40	Trumatt Premium Matt	20			
Carbosoly Standard Thinners	60	MarineGrip Anti Slip Deck Paint	40	Trusheen Premium Silk	21			
Carbosoly Toluene	63	MarineMaster Boat & Barge Gloss	39	Trutex Smooth Masonry Paint	13			
Carbosolv Xylene Thinners	61	MarineMaster Boat & Barge Primer	38	TruTherm Anti Condensation Paint	56			
Carbotex Roofing Compound	36	MarineMaster Boat & Barge Undercoat	38	Two Hour Gloss	33			
Carbotrak Tractor & Implement Paint	30	MarineMaster Deepseal Bilge Paint	38	Two Pack Epoxy Dust Sealer	6			
Carbotread Exterior Floor Paint	4	MarineMaster Hull Blacking	40	Two Pack Epoxy Floor Paint	6			
Carbotread Floor Sealer	9	MDF Primer	43	Two Pack Epoxy Floor Primer	5			
Carbotread Polyurethane Floor Paint	4	Mordant Solution (T Wash)	46	UPVC & Plastic Paint	57			
Carbowash Acid Brick Cleaner	63	Paint for Copper Pipes	14	Universal Gloss Multi Surface Paint	57			
Carboxide Agricultural & Industrial	28	Paint Panther	44	Universal Multi Surface Primer	46			
Carboxide All Purpose Primer Undercoat	46	Palatine Premium Paraffin	65	Universal Satin Multi Surface Paint	57			
Carboxide Black Oxide Primer	47	Peelaway	44	Waxes & Lacquers	75			
Carboxide Grey Oxide Primer	47	Peelaway Marine	38	White Rock Salt 20KG	68			
Carboxide Red Oxide Primer	47	Pipe Identification Aerosol	54	Wood Preservers	76			
Cedar Wood Treatment	72	Pipe Identification Paint	59	Wood Protective Treatment	76			
Ceiling Paint	19	Plant & Machinery Paint	34	Yacht Varnish	41			
Chalkboard & Blackboard Paint	14	Plant & Machinery Primer	48	Yacht Varnish QuickCoat	55			
Chassis, Vehicle & Military Paint	69	Pliocem Concrete & Masonry Sealer	11	Zenova IP Insulating Paint	58			
		·						











































55 Smallbrook Lane, Leigh, Lancashire, WN7 5PZ (2) +44 (0)1942 884122



